

AI 95° EVEN 40" TIP SPACING

ALL VALUES BASED ON WATER FOR OTHER LIQUIDS SEE USEFUL FORMULAS AND CONVERSIONS

mph			4.0	4.5	5.0	5.5	6.0	6.5	7.0	7.5	8.0	8.5	9.0	9.5	10.0	10.5	11.0	11.5	12.0	
			psi	gpm																
AI95015EVS	30	0.130	4.8	4.3	3.9	3.5	3.2	3.0	2.8	2.6	2.4	2.3	2.1	2.0	1.9	1.8	1.8	1.7	1.6	
	40	0.150	5.6	5.0	4.5	4.1	3.7	3.4	3.2	3.0	2.8	2.6	2.5	2.3	2.2	2.1	2.0	1.9	1.9	
	50	0.168	6.2	5.5	5.0	4.5	4.2	3.8	3.6	3.3	3.1	2.9	2.8	2.6	2.5	2.4	2.3	2.2	2.1	
100 MESH	60	0.184	6.8	6.1	5.5	5.0	4.5	4.2	3.9	3.6	3.4	3.2	3.0	2.9	2.7	2.6	2.5	2.4	2.3	
	70	0.198	7.4	6.5	5.9	5.4	4.9	4.5	4.2	3.9	3.7	3.5	3.3	3.1	2.9	2.8	2.7	2.6	2.5	
	80	0.212	7.9	7.0	6.3	5.7	5.3	4.8	4.5	4.2	3.9	3.7	3.5	3.3	3.2	3.0	2.9	2.7	2.6	
GREEN	90	0.225	8.4	7.4	6.7	6.1	5.6	5.1	4.8	4.5	4.2	3.9	3.7	3.5	3.3	3.2	3.0	2.9	2.8	
	100	0.237	8.8	7.8	7.0	6.4	5.9	5.4	5.0	4.7	4.4	4.1	3.9	3.7	3.5	3.4	3.2	3.1	2.9	
	110	0.249	9.2	8.2	7.4	6.7	6.2	5.7	5.3	4.9	4.6	4.3	4.1	3.9	3.7	3.5	3.4	3.2	3.1	
AI9502EVS	30	0.173	6.4	5.7	5.1	4.7	4.3	4.0	3.7	3.4	3.2	3.0	2.9	2.7	2.6	2.4	2.3	2.2	2.1	
	40	0.200	7.4	6.6	5.9	5.4	5.0	4.6	4.2	4.0	3.7	3.5	3.3	3.1	3.0	2.8	2.7	2.6	2.5	
	50	0.224	8.3	7.4	6.6	6.0	5.5	5.1	4.7	4.4	4.2	3.9	3.7	3.5	3.3	3.2	3.0	2.9	2.8	
50 MESH	60	0.245	9.1	8.1	7.3	6.6	6.1	5.6	5.2	4.8	4.5	4.3	4.0	3.8	3.6	3.5	3.3	3.2	3.0	
	70	0.265	9.8	8.7	7.9	7.1	6.5	6.0	5.6	5.2	4.9	4.6	4.4	4.1	3.9	3.7	3.6	3.4	3.3	
	80	0.283	10.5	9.3	8.4	7.6	7.0	6.5	6.0	5.6	5.3	4.9	4.7	4.4	4.2	4.0	3.8	3.7	3.5	
YELLOW	90	0.300	11.1	9.9	8.9	8.1	7.4	6.9	6.4	5.9	5.6	5.2	5.0	4.7	4.5	4.2	4.1	3.9	3.7	
	100	0.316	11.7	10.4	9.4	8.5	7.8	7.2	6.7	6.3	5.9	5.5	5.2	4.9	4.7	4.5	4.3	4.1	3.9	
	110	0.332	12.3	10.9	9.9	9.0	8.2	7.6	7.0	6.6	6.2	5.8	5.5	5.2	4.9	4.7	4.5	4.3	4.1	
AI95025EVS	30	0.217	8.0	7.1	6.4	5.8	5.4	4.9	4.6	4.3	4.0	3.8	3.6	3.4	3.2	3.1	2.9	2.8	2.7	
	40	0.250	9.3	8.3	7.4	6.8	6.2	5.7	5.3	5.0	4.6	4.4	4.1	3.9	3.7	3.5	3.4	3.2	3.1	
	50	0.280	10.4	9.2	8.3	7.5	6.9	6.4	5.9	5.5	5.2	4.9	4.6	4.4	4.2	4.0	3.8	3.6	3.5	
50 MESH	60	0.306	11.4	10.1	9.1	8.3	7.6	7.0	6.5	6.1	5.7	5.3	5.1	4.8	4.5	4.3	4.1	4.0	3.8	
	70	0.331	12.3	10.9	9.8	8.9	8.2	7.6	7.0	6.5	6.1	5.8	5.5	5.2	4.9	4.7	4.5	4.3	4.1	
	80	0.354	13.1	11.7	10.5	9.5	8.8	8.1	7.5	7.0	6.6	6.2	5.8	5.5	5.3	5.0	4.8	4.6	4.4	
PURPLE	90	0.375	13.9	12.4	11.1	10.1	9.3	8.6	8.0	7.4	7.0	6.6	6.2	5.9	5.6	5.3	5.1	4.8	4.6	
	100	0.395	14.7	13.0	11.7	10.7	9.8	9.0	8.4	7.8	7.3	6.9	6.5	6.2	5.9	5.6	5.3	5.1	4.9	
	110	0.415	15.4	13.7	12.3	11.2	10.3	9.5	8.8	8.2	7.7	7.2	6.8	6.5	6.2	5.9	5.6	5.4	5.1	
AI9503EVS	30	0.260	9.6	8.6	7.7	7.0	6.4	5.9	5.5	5.1	4.8	4.5	4.3	4.1	3.9	3.7	3.5	3.4	3.2	
	40	0.300	11.1	9.9	8.9	8.1	7.4	6.9	6.4	5.9	5.6	5.2	5.0	4.7	4.5	4.2	4.1	3.9	3.7	
	50	0.335	12.5	11.1	10.0	9.1	8.3	7.7	7.1	6.6	6.2	5.9	5.5	5.2	5.0	4.7	4.5	4.3	4.2	
50 MESH	60	0.367	13.6	12.1	10.9	9.9	9.1	8.4	7.8	7.3	6.8	6.4	6.1	5.7	5.5	5.2	5.0	4.7	4.5	
	70	0.397	14.7	13.1	11.8	10.7	9.8	9.1	8.4	7.9	7.4	6.9	6.5	6.2	5.9	5.6	5.4	5.1	4.9	
	80	0.424	15.8	14.0	12.6	11.5	10.5	9.7	9.0	8.4	7.9	7.4	7.0	6.6	6.3	6.0	5.7	5.5	5.3	
BLUE	90	0.450	16.7	14.9	13.4	12.2	11.1	10.3	9.5	8.9	8.4	7.9	7.4	7.0	6.7	6.4	6.1	5.8	5.6	
	100	0.474	17.6	15.7	14.1	12.8	11.7	10.8	10.1	9.4	8.8	8.3	7.8	7.4	7.0	6.7	6.4	6.1	5.9	
	110	0.497	18.5	16.4	14.8	13.4	12.3	11.4	10.6	9.9	9.2	8.7	8.2	7.8	7.4	7.0	6.7	6.4	6.2	
AI9504EVS	30	0.346	12.9	11.4	10.3	9.4	8.6	7.9	7.3	6.9	6.4	6.1	5.7	5.4	5.1	4.9	4.7	4.5	4.3	
	40	0.400	14.9	13.2	11.9	10.8	9.9	9.1	8.5	7.9	7.4	7.0	6.6	6.3	5.9	5.7	5.4	5.2	5.0	
	50	0.447	16.6	14.8	13.3	12.1	11.1	10.2	9.5	8.9	8.3	7.8	7.4	7.0	6.6	6.3	6.0	5.8	5.5	
50 MESH	60	0.490	18.2	16.2	14.5	13.2	12.1	11.2	10.4	9.7	9.1	8.6	8.1	7.7	7.3	6.9	6.6	6.3	6.1	
	70	0.529	19.6	17.5	15.7	14.3	13.1	12.1	11.2	10.5	9.8	9.2	8.7	8.3	7.9	7.5	7.1	6.8	6.5	
	80	0.566	21.0	18.7	16.8	15.3	14.0	12.9	12.0	11.2	10.5	9.9	9.3	8.8	8.4	8.0	7.6	7.3	7.0	
RED	90	0.600	22.3	19.8	17.8	16.2	14.9	13.7	12.7	11.9	11.1	10.5	9.9	9.4	8.9	8.5	8.1	7.7	7.4	
	100	0.632	23.5	20.9	18.8	17.1	15.7	14.4	13.4	12.5	11.7	11.0	10.4	9.9	9.4	8.9	8.5	8.2	7.8	
	110	0.663	24.6	21.9	19.7	17.9	16.4	15.2	14.1	13.1	12.3	11.6	10.9	10.4	9.9	9.4	9.0	8.6	8.2	

AI 95° EVEN 40" TIP SPACING

ALL VALUES BASED ON WATER FOR OTHER LIQUIDS SEE USEFUL FORMULAS AND CONVERSIONS

mph		4.0	4.5	5.0	5.5	6.0	6.5	7.0	7.5	8.0	8.5	9.0	9.5	10.0	10.5	11.0	11.5	12.0	
		psi	gpm																
AI9505EVS	30	0.433	16.1	14.3	12.9	11.7	10.7	9.9	9.2	8.6	8.0	7.6	7.1	6.8	6.4	6.1	5.8	5.6	5.4
	40	0.500	18.6	16.5	14.9	13.5	12.4	11.4	10.6	9.9	9.3	8.7	8.3	7.8	7.4	7.1	6.8	6.5	6.2
	50	0.559	20.8	18.4	16.6	15.1	13.8	12.8	11.9	11.1	10.4	9.8	9.2	8.7	8.3	7.9	7.5	7.2	6.9
50 MESH	60	0.612	22.7	20.2	18.2	16.5	15.2	14.0	13.0	12.1	11.4	10.7	10.1	9.6	9.1	8.7	8.3	7.9	7.6
	70	0.661	24.6	21.8	19.6	17.9	16.4	15.1	14.0	13.1	12.3	11.6	10.9	10.3	9.8	9.4	8.9	8.5	8.2
	80	0.707	26.3	23.3	21.0	19.1	17.5	16.2	15.0	14.0	13.1	12.4	11.7	11.1	10.5	10.0	9.5	9.1	8.8
BROWN	90	0.750	27.8	24.8	22.3	20.3	18.6	17.1	15.9	14.9	13.9	13.1	12.4	11.7	11.1	10.6	10.1	9.7	9.3
	100	0.791	29.3	26.1	23.5	21.3	19.6	18.1	16.8	15.7	14.7	13.8	13.0	12.4	11.7	11.2	10.7	10.2	9.8
	110	0.829	30.8	27.4	24.6	22.4	20.5	18.9	17.6	16.4	15.4	14.5	13.7	13.0	12.3	11.7	11.2	10.7	10.3
AI9506EVS	30	0.520	19.3	17.1	15.4	14.0	12.9	11.9	11.0	10.3	9.6	9.1	8.6	8.1	7.7	7.3	7.0	6.7	6.4
	40	0.600	22.3	19.8	17.8	16.2	14.9	13.7	12.7	11.9	11.1	10.5	9.9	9.4	8.9	8.5	8.1	7.7	7.4
	50	0.671	24.9	22.1	19.9	18.1	16.6	15.3	14.2	13.3	12.5	11.7	11.1	10.5	10.0	9.5	9.1	8.7	8.3
50 MESH	60	0.735	27.3	24.2	21.8	19.8	18.2	16.8	15.6	14.5	13.6	12.8	12.1	11.5	10.9	10.4	9.9	9.5	9.1
	70	0.794	29.5	26.2	23.6	21.4	19.6	18.1	16.8	15.7	14.7	13.9	13.1	12.4	11.8	11.2	10.7	10.2	9.8
	80	0.849	31.5	28.0	25.2	22.9	21.0	19.4	18.0	16.8	15.8	14.8	14.0	13.3	12.6	12.0	11.5	11.0	10.5
GRAY	90	0.900	33.4	29.7	26.7	24.3	22.3	20.6	19.1	17.8	16.7	15.7	14.9	14.1	13.4	12.7	12.2	11.6	11.1
	100	0.949	35.2	31.3	28.2	25.6	23.5	21.7	20.1	18.8	17.6	16.6	15.7	14.8	14.1	13.4	12.8	12.3	11.7
	110	0.995	36.9	32.8	29.6	26.9	24.6	22.7	21.1	19.7	18.5	17.4	16.4	15.6	14.8	14.1	13.4	12.8	12.3
AI9508EVS	30	0.693	25.7	22.9	20.6	18.7	17.1	15.8	14.7	13.7	12.9	12.1	11.4	10.8	10.3	9.8	9.4	8.9	8.6
	40	0.800	29.7	26.4	23.8	21.6	19.8	18.3	17.0	15.8	14.9	14.0	13.2	12.5	11.9	11.3	10.8	10.3	9.9
	50	0.894	33.2	29.5	26.6	24.1	22.1	20.4	19.0	17.7	16.6	15.6	14.8	14.0	13.3	12.6	12.1	11.5	11.1
50 MESH	60	0.980	36.4	32.3	29.1	26.5	24.2	22.4	20.8	19.4	18.2	17.1	16.2	15.3	14.5	13.9	13.2	12.7	12.1
	70	1.058	39.3	34.9	31.4	28.6	26.2	24.2	22.5	21.0	19.6	18.5	17.5	16.5	15.7	15.0	14.3	13.7	13.1
	80	1.131	42.0	37.3	33.6	30.5	28.0	25.8	24.0	22.4	21.0	19.8	18.7	17.7	16.8	16.0	15.3	14.6	14.0
WHITE	90	1.200	44.6	39.6	35.6	32.4	29.7	27.4	25.5	23.8	22.3	21.0	19.8	18.8	17.8	17.0	16.2	15.5	14.9
	100	1.265	47.0	41.7	37.6	34.2	31.3	28.9	26.8	25.0	23.5	22.1	20.9	19.8	18.8	17.9	17.1	16.3	15.7
	110	1.327	49.3	43.8	39.4	35.8	32.8	30.3	28.1	26.3	24.6	23.2	21.9	20.7	19.7	18.8	17.9	17.1	16.4

AI 95° EVEN 40" TIP SPACING

ALL VALUES BASED ON WATER FOR OTHER LIQUIDS SEE USEFUL FORMULAS AND CONVERSIONS

12.5	13.0	13.5	14.0	14.5	15.0	15.5	16.0	16.5	17.0	17.5	18.0	18.5	19.0	19.5	20.0	mph			
																gpm	psi		
1.5	1.5	1.4	1.4	1.3	1.3	1.2	1.2	1.2	1.1	1.1	1.1	1.0	1.0	1.0	1.0	0.130	30	AI95015EVS 100 MESH GREEN	
1.8	1.7	1.7	1.6	1.5	1.5	1.4	1.4	1.4	1.3	1.3	1.2	1.2	1.2	1.1	1.1	0.150	40		
2.0	1.9	1.8	1.8	1.7	1.7	1.6	1.6	1.5	1.5	1.4	1.4	1.3	1.3	1.3	1.2	0.168	50		
2.2	2.1	2.0	1.9	1.9	1.8	1.8	1.7	1.7	1.6	1.6	1.5	1.5	1.4	1.4	1.4	0.184	60		
2.4	2.3	2.2	2.1	2.0	2.0	1.9	1.8	1.8	1.7	1.7	1.6	1.6	1.6	1.5	1.5	0.198	70		
2.5	2.4	2.3	2.3	2.2	2.1	2.0	2.0	1.9	1.9	1.8	1.8	1.7	1.7	1.6	1.6	0.212	80		
2.7	2.6	2.5	2.4	2.3	2.2	2.2	2.1	2.0	2.0	1.9	1.9	1.8	1.8	1.7	1.7	0.225	90		
2.8	2.7	2.6	2.5	2.4	2.3	2.3	2.2	2.1	2.1	2.0	2.0	1.9	1.9	1.8	1.8	0.237	100		
3.0	2.8	2.7	2.6	2.5	2.5	2.4	2.3	2.2	2.2	2.1	2.1	2.0	1.9	1.9	1.8	0.249	110		
2.1	2.0	1.9	1.8	1.8	1.7	1.7	1.6	1.6	1.5	1.5	1.4	1.4	1.4	1.3	1.3	0.173	30	AI9502EVS 50 MESH YELLOW	
2.4	2.3	2.2	2.1	2.0	2.0	1.9	1.9	1.8	1.7	1.7	1.7	1.6	1.6	1.5	1.5	0.200	40		
2.7	2.6	2.5	2.4	2.3	2.2	2.1	2.1	2.0	2.0	1.9	1.8	1.8	1.7	1.7	1.7	0.224	50		
2.9	2.8	2.7	2.6	2.5	2.4	2.3	2.3	2.2	2.1	2.1	2.0	2.0	1.9	1.9	1.8	0.245	60		
3.1	3.0	2.9	2.8	2.7	2.6	2.5	2.5	2.4	2.3	2.2	2.2	2.1	2.1	2.0	2.0	0.265	70		
3.4	3.2	3.1	3.0	2.9	2.8	2.7	2.6	2.5	2.5	2.4	2.3	2.3	2.2	2.2	2.1	0.283	80		
3.6	3.4	3.3	3.2	3.1	3.0	2.9	2.8	2.7	2.6	2.5	2.5	2.4	2.3	2.3	2.2	0.300	90		
3.8	3.6	3.5	3.4	3.2	3.1	3.0	2.9	2.8	2.8	2.7	2.6	2.5	2.5	2.4	2.3	0.316	100		
3.9	3.8	3.6	3.5	3.4	3.3	3.2	3.1	3.0	2.9	2.8	2.7	2.7	2.6	2.5	2.5	0.332	110		
2.6	2.5	2.4	2.3	2.2	2.1	2.1	2.0	1.9	1.9	1.8	1.8	1.7	1.7	1.6	1.6	0.217	30	AI95025EVS 50 MESH PURPLE	
3.0	2.9	2.8	2.7	2.6	2.5	2.4	2.3	2.3	2.2	2.1	2.1	2.0	2.0	1.9	1.9	0.250	40		
3.3	3.2	3.1	3.0	2.9	2.8	2.7	2.6	2.5	2.4	2.4	2.3	2.2	2.2	2.1	2.1	0.280	50		
3.6	3.5	3.4	3.2	3.1	3.0	2.9	2.8	2.8	2.7	2.6	2.5	2.5	2.4	2.3	2.3	0.306	60		
3.9	3.8	3.6	3.5	3.4	3.3	3.2	3.1	3.0	2.9	2.8	2.7	2.7	2.6	2.5	2.5	0.331	70		
4.2	4.0	3.9	3.8	3.6	3.5	3.4	3.3	3.2	3.1	3.0	2.9	2.8	2.8	2.7	2.6	0.354	80		
4.5	4.3	4.1	4.0	3.8	3.7	3.6	3.5	3.4	3.3	3.2	3.1	3.0	2.9	2.9	2.8	0.375	90		
4.7	4.5	4.3	4.2	4.0	3.9	3.8	3.7	3.6	3.5	3.4	3.3	3.2	3.1	3.0	2.9	0.395	100		
4.9	4.7	4.6	4.4	4.2	4.1	4.0	3.8	3.7	3.6	3.5	3.4	3.3	3.2	3.2	3.1	0.415	110		
3.1	3.0	2.9	2.8	2.7	2.6	2.5	2.4	2.3	2.3	2.2	2.1	2.1	2.0	2.0	1.9	0.260	30	AI9503EVS 50 MESH BLUE	
3.6	3.4	3.3	3.2	3.1	3.0	2.9	2.8	2.7	2.6	2.5	2.5	2.4	2.3	2.3	2.2	0.300	40		
4.0	3.8	3.7	3.6	3.4	3.3	3.2	3.1	3.0	2.9	2.8	2.8	2.7	2.6	2.6	2.5	0.335	50		
4.4	4.2	4.0	3.9	3.8	3.6	3.5	3.4	3.3	3.2	3.1	3.0	2.9	2.9	2.8	2.7	0.367	60		
4.7	4.5	4.4	4.2	4.1	3.9	3.8	3.7	3.6	3.5	3.4	3.3	3.2	3.1	3.0	2.9	0.397	70		
5.0	4.8	4.7	4.5	4.3	4.2	4.1	3.9	3.8	3.7	3.6	3.5	3.4	3.3	3.2	3.2	0.424	80		
5.3	5.1	5.0	4.8	4.6	4.5	4.3	4.2	4.1	3.9	3.8	3.7	3.6	3.5	3.4	3.3	0.450	90		
5.6	5.4	5.2	5.0	4.9	4.7	4.5	4.4	4.3	4.1	4.0	3.9	3.8	3.7	3.6	3.5	0.474	100		
5.9	5.7	5.5	5.3	5.1	4.9	4.8	4.6	4.5	4.3	4.2	4.1	4.0	3.9	3.8	3.7	0.497	110		
4.1	4.0	3.8	3.7	3.5	3.4	3.3	3.2	3.1	3.0	2.9	2.9	2.8	2.7	2.6	2.6	0.346	30	AI9504EVS 50 MESH RED	
4.8	4.6	4.4	4.2	4.1	4.0	3.8	3.7	3.6	3.5	3.4	3.3	3.2	3.1	3.0	3.0	0.400	40		
5.3	5.1	4.9	4.7	4.6	4.4	4.3	4.2	4.0	3.9	3.8	3.7	3.6	3.5	3.4	3.3	0.447	50		
5.8	5.6	5.4	5.2	5.0	4.8	4.7	4.5	4.4	4.3	4.2	4.0	3.9	3.8	3.7	3.6	0.490	60		
6.3	6.0	5.8	5.6	5.4	5.2	5.1	4.9	4.8	4.6	4.5	4.4	4.2	4.1	4.0	3.9	0.529	70		
6.7	6.5	6.2	6.0	5.8	5.6	5.4	5.3	5.1	4.9	4.8	4.7	4.5	4.4	4.3	4.2	0.566	80		
7.1	6.9	6.6	6.4	6.1	5.9	5.7	5.6	5.4	5.2	5.1	5.0	4.8	4.7	4.6	4.5	0.600	90		
7.5	7.2	7.0	6.7	6.5	6.3	6.1	5.9	5.7	5.5	5.4	5.2	5.1	4.9	4.8	4.7	0.632	100		
7.9	7.6	7.3	7.0	6.8	6.6	6.4	6.2	6.0	5.8	5.6	5.5	5.3	5.2	5.1	4.9	0.663	110		

AI 95° EVEN 40" TIP SPACING

ALL VALUES BASED ON WATER FOR OTHER LIQUIDS SEE USEFUL FORMULAS AND CONVERSIONS

12.5	13.0	13.5	14.0	14.5	15.0	15.5	16.0	16.5	17.0	17.5	18.0	18.5	19.0	19.5	20.0	mph	
																gpm	psi
5.1	4.9	4.8	4.6	4.4	4.3	4.1	4.0	3.9	3.8	3.7	3.6	3.5	3.4	3.3	3.2	0.433	30
5.9	5.7	5.5	5.3	5.1	5.0	4.8	4.6	4.5	4.4	4.2	4.1	4.0	3.9	3.8	3.7	0.500	40
6.6	6.4	6.1	5.9	5.7	5.5	5.4	5.2	5.0	4.9	4.7	4.6	4.5	4.4	4.3	4.2	0.559	50
7.3	7.0	6.7	6.5	6.3	6.1	5.9	5.7	5.5	5.3	5.2	5.1	4.9	4.8	4.7	4.5	0.612	60
7.9	7.6	7.3	7.0	6.8	6.5	6.3	6.1	6.0	5.8	5.6	5.5	5.3	5.2	5.0	4.9	0.661	70
8.4	8.1	7.8	7.5	7.2	7.0	6.8	6.6	6.4	6.2	6.0	5.8	5.7	5.5	5.4	5.3	0.707	80
8.9	8.6	8.3	8.0	7.7	7.4	7.2	7.0	6.8	6.6	6.4	6.2	6.0	5.9	5.7	5.6	0.750	90
9.4	9.0	8.7	8.4	8.1	7.8	7.6	7.3	7.1	6.9	6.7	6.5	6.3	6.2	6.0	5.9	0.791	100
9.9	9.5	9.1	8.8	8.5	8.2	7.9	7.7	7.5	7.2	7.0	6.8	6.7	6.5	6.3	6.2	0.829	110
6.2	5.9	5.7	5.5	5.3	5.1	5.0	4.8	4.7	4.5	4.4	4.3	4.2	4.1	4.0	3.9	0.520	30
7.1	6.9	6.6	6.4	6.1	5.9	5.7	5.6	5.4	5.2	5.1	5.0	4.8	4.7	4.6	4.5	0.600	40
8.0	7.7	7.4	7.1	6.9	6.6	6.4	6.2	6.0	5.9	5.7	5.5	5.4	5.2	5.1	5.0	0.671	50
8.7	8.4	8.1	7.8	7.5	7.3	7.0	6.8	6.6	6.4	6.2	6.1	5.9	5.7	5.6	5.5	0.735	60
9.4	9.1	8.7	8.4	8.1	7.9	7.6	7.4	7.1	6.9	6.7	6.5	6.4	6.2	6.0	5.9	0.794	70
10.1	9.7	9.3	9.0	8.7	8.4	8.1	7.9	7.6	7.4	7.2	7.0	6.8	6.6	6.5	6.3	0.849	80
10.7	10.3	9.9	9.5	9.2	8.9	8.6	8.4	8.1	7.9	7.6	7.4	7.2	7.0	6.9	6.7	0.900	90
11.3	10.8	10.4	10.1	9.7	9.4	9.1	8.8	8.5	8.3	8.1	7.8	7.6	7.4	7.2	7.0	0.949	100
11.8	11.4	10.9	10.6	10.2	9.9	9.5	9.2	9.0	8.7	8.4	8.2	8.0	7.8	7.6	7.4	0.995	110
8.2	7.9	7.6	7.3	7.1	6.9	6.6	6.4	6.2	6.1	5.9	5.7	5.6	5.4	5.3	5.1	0.693	30
9.5	9.1	8.8	8.5	8.2	7.9	7.7	7.4	7.2	7.0	6.8	6.6	6.4	6.3	6.1	5.9	0.800	40
10.6	10.2	9.8	9.5	9.2	8.9	8.6	8.3	8.0	7.8	7.6	7.4	7.2	7.0	6.8	6.6	0.894	50
11.6	11.2	10.8	10.4	10.0	9.7	9.4	9.1	8.8	8.6	8.3	8.1	7.9	7.7	7.5	7.3	0.980	60
12.6	12.1	11.6	11.2	10.8	10.5	10.1	9.8	9.5	9.2	9.0	8.7	8.5	8.3	8.1	7.9	1.058	70
13.4	12.9	12.4	12.0	11.6	11.2	10.8	10.5	10.2	9.9	9.6	9.3	9.1	8.8	8.6	8.4	1.131	80
14.3	13.7	13.2	12.7	12.3	11.9	11.5	11.1	10.8	10.5	10.2	9.9	9.6	9.4	9.1	8.9	1.200	90
15.0	14.4	13.9	13.4	13.0	12.5	12.1	11.7	11.4	11.0	10.7	10.4	10.2	9.9	9.6	9.4	1.265	100
15.8	15.2	14.6	14.1	13.6	13.1	12.7	12.3	11.9	11.6	11.3	10.9	10.6	10.4	10.1	9.9	1.327	110