

AI 110° / AI UB 85° 40" TIP SPACING

ALL VALUES BASED ON WATER FOR OTHER LIQUIDS SEE USEFUL FORMULAS AND CONVERSIONS

mph		4.0	4.5	5.0	5.5	6.0	6.5	7.0	7.5	8.0	8.5	9.0	9.5	10.0	10.5	11.0	11.5	12.0	
	psi gpm																		
AI110015VS	30	0.130	4.8	4.3	3.9	3.5	3.2	3.0	2.8	2.6	2.4	2.3	2.1	2.0	1.9	1.8	1.8	1.7	1.6
	40	0.15	5.6	5.0	4.5	4.1	3.7	3.4	3.2	3.0	2.8	2.6	2.5	2.3	2.2	2.1	2.0	1.9	1.9
100 MESH	50	0.168	6.2	5.5	5.0	4.5	4.2	3.8	3.6	3.3	3.1	2.9	2.8	2.6	2.5	2.4	2.3	2.2	2.1
	60	0.184	6.8	6.1	5.5	5.0	4.5	4.2	3.9	3.6	3.4	3.2	3.0	2.9	2.7	2.6	2.5	2.4	2.3
	70	0.198	7.4	6.5	5.9	5.4	4.9	4.5	4.2	3.9	3.7	3.5	3.3	3.1	2.9	2.8	2.7	2.6	2.5
GREEN	80	0.212	7.9	7.0	6.3	5.7	5.3	4.8	4.5	4.2	3.9	3.7	3.5	3.3	3.2	3.0	2.9	2.7	2.6
	90	0.225	8.4	7.4	6.7	6.1	5.6	5.1	4.8	4.5	4.2	3.9	3.7	3.5	3.3	3.2	3.0	2.9	2.8
	100	0.237	8.8	7.8	7.0	6.4	5.9	5.4	5.0	4.7	4.4	4.1	3.9	3.7	3.5	3.4	3.2	3.1	2.9
	110	0.249	9.2	8.2	7.4	6.7	6.2	5.7	5.3	4.9	4.6	4.3	4.1	3.9	3.7	3.5	3.4	3.2	3.1
AI11002VS	30	0.173	6.4	5.7	5.1	4.7	4.3	4.0	3.7	3.4	3.2	3.0	2.9	2.7	2.6	2.4	2.3	2.2	2.1
	40	0.200	7.4	6.6	5.9	5.4	5.0	4.6	4.2	4.0	3.7	3.5	3.3	3.1	3.0	2.8	2.7	2.6	2.5
100 MESH	50	0.224	8.3	7.4	6.6	6.0	5.5	5.1	4.7	4.4	4.2	3.9	3.7	3.5	3.3	3.2	3.0	2.9	2.8
	60	0.245	9.1	8.1	7.3	6.6	6.1	5.6	5.2	4.8	4.5	4.3	4.0	3.8	3.6	3.5	3.3	3.2	3.0
	70	0.265	9.8	8.7	7.9	7.1	6.5	6.0	5.6	5.2	4.9	4.6	4.4	4.1	3.9	3.7	3.6	3.4	3.3
YELLOW	80	0.283	10.5	9.3	8.4	7.6	7.0	6.5	6.0	5.6	5.3	4.9	4.7	4.4	4.2	4.0	3.8	3.7	3.5
	90	0.300	11.1	9.9	8.9	8.1	7.4	6.9	6.4	5.9	5.6	5.2	5.0	4.7	4.5	4.2	4.1	3.9	3.7
	100	0.316	11.7	10.4	9.4	8.5	7.8	7.2	6.7	6.3	5.9	5.5	5.2	4.9	4.7	4.5	4.3	4.1	3.9
	110	0.332	12.3	10.9	9.9	9.0	8.2	7.6	7.0	6.6	6.2	5.8	5.5	5.2	4.9	4.7	4.5	4.3	4.1
AI110025VS AIUB85025VS	30	0.217	8.0	7.1	6.4	5.8	5.4	4.9	4.6	4.3	4.0	3.8	3.6	3.4	3.2	3.1	2.9	2.8	2.7
	40	0.250	9.3	8.3	7.4	6.8	6.2	5.7	5.3	5.0	4.6	4.4	4.1	3.9	3.7	3.5	3.4	3.2	3.1
100 MESH	50	0.280	10.4	9.2	8.3	7.5	6.9	6.4	5.9	5.5	5.2	4.9	4.6	4.4	4.2	4.0	3.8	3.6	3.5
	60	0.306	11.4	10.1	9.1	8.3	7.6	7.0	6.5	6.1	5.7	5.3	5.1	4.8	4.5	4.3	4.1	4.0	3.8
	70	0.331	12.3	10.9	9.8	8.9	8.2	7.6	7.0	6.5	6.1	5.8	5.5	5.2	4.9	4.7	4.5	4.3	4.1
PURPLE	80	0.354	13.1	11.7	10.5	9.5	8.8	8.1	7.5	7.0	6.6	6.2	5.8	5.5	5.3	5.0	4.8	4.6	4.4
	90	0.375	13.9	12.4	11.1	10.1	9.3	8.6	8.0	7.4	7.0	6.6	6.2	5.9	5.6	5.3	5.1	4.8	4.6
	100	0.395	14.7	13.0	11.7	10.7	9.8	9.0	8.4	7.8	7.3	6.9	6.5	6.2	5.9	5.6	5.3	5.1	4.9
	110	0.415	15.4	13.7	12.3	11.2	10.3	9.5	8.8	8.2	7.7	7.2	6.8	6.5	6.2	5.9	5.6	5.4	5.1
AI11003VS AIUB8503VS	30	0.260	9.6	8.6	7.7	7.0	6.4	5.9	5.5	5.1	4.8	4.5	4.3	4.1	3.9	3.7	3.5	3.4	3.2
	40	0.300	11.1	9.9	8.9	8.1	7.4	6.9	6.4	5.9	5.6	5.2	5.0	4.7	4.5	4.2	4.1	3.9	3.7
100 MESH	50	0.335	12.5	11.1	10.0	9.1	8.3	7.7	7.1	6.6	6.2	5.9	5.5	5.2	5.0	4.7	4.5	4.3	4.2
	60	0.367	13.6	12.1	10.9	9.9	9.1	8.4	7.8	7.3	6.8	6.4	6.1	5.7	5.5	5.2	5.0	4.7	4.5
	70	0.397	14.7	13.1	11.8	10.7	9.8	9.1	8.4	7.9	7.4	6.9	6.5	6.2	5.9	5.6	5.4	5.1	4.9
BLUE	80	0.424	15.8	14.0	12.6	11.5	10.5	9.7	9.0	8.4	7.9	7.4	7.0	6.6	6.3	6.0	5.7	5.5	5.3
	90	0.450	16.7	14.9	13.4	12.2	11.1	10.3	9.5	8.9	8.4	7.9	7.4	7.0	6.7	6.4	6.1	5.8	5.6
	100	0.474	17.6	15.7	14.1	12.8	11.7	10.8	10.1	9.4	8.8	8.3	7.8	7.4	7.0	6.7	6.4	6.1	5.9
	110	0.497	18.5	16.4	14.8	13.4	12.3	11.4	10.6	9.9	9.2	8.7	8.2	7.8	7.4	7.0	6.7	6.4	6.2
AI11004VS AIUB8504VS	30	0.346	12.9	11.4	10.3	9.4	8.6	7.9	7.3	6.9	6.4	6.1	5.7	5.4	5.1	4.9	4.7	4.5	4.3
	40	0.400	14.9	13.2	11.9	10.8	9.9	9.1	8.5	7.9	7.4	7.0	6.6	6.3	5.9	5.7	5.4	5.2	5.0
50 MESH	50	0.447	16.6	14.8	13.3	12.1	11.1	10.2	9.5	8.9	8.3	7.8	7.4	7.0	6.6	6.3	6.0	5.8	5.5
	60	0.490	18.2	16.2	14.5	13.2	12.1	11.2	10.4	9.7	9.1	8.6	8.1	7.7	7.3	6.9	6.6	6.3	6.1
	70	0.529	19.6	17.5	15.7	14.3	13.1	12.1	11.2	10.5	9.8	9.2	8.7	8.3	7.9	7.5	7.1	6.8	6.5
RED	80	0.566	21.0	18.7	16.8	15.3	14.0	12.9	12.0	11.2	10.5	9.9	9.3	8.8	8.4	8.0	7.6	7.3	7.0
	90	0.600	22.3	19.8	17.8	16.2	14.9	13.7	12.7	11.9	11.1	10.5	9.9	9.4	8.9	8.5	8.1	7.7	7.4
	100	0.632	23.5	20.9	18.8	17.1	15.7	14.4	13.4	12.5	11.7	11.0	10.4	9.9	9.4	8.9	8.5	8.2	7.8
	110	0.663	24.6	21.9	19.7	17.9	16.4	15.2	14.1	13.1	12.3	11.6	10.9	10.4	9.9	9.4	9.0	8.6	8.2
AI11005VS	30	0.433	16.1	14.3	12.9	11.7	10.7	9.9	9.2	8.6	8.0	7.6	7.1	6.8	6.4	6.1	5.8	5.6	5.4
	40	0.500	18.6	16.5	14.9	13.5	12.4	11.4	10.6	9.9	9.3	8.7	8.3	7.8	7.4	7.1	6.8	6.5	6.2
50 MESH	50	0.559	20.8	18.4	16.6	15.1	13.8	12.8	11.9	11.1	10.4	9.8	9.2	8.7	8.3	7.9	7.5	7.2	6.9
	60	0.612	22.7	20.2	18.2	16.5	15.2	14.0	13.0	12.1	11.4	10.7	10.1	9.6	9.1	8.7	8.3	7.9	7.6
	70	0.661	24.6	21.8	19.6	17.9	16.4	15.1	14.0	13.1	12.3	11.6	10.9	10.3	9.8	9.4	8.9	8.5	8.2
BROWN	80	0.707	26.3	23.3	21.0	19.1	17.5	16.2	15.0	14.0	13.1	12.4	11.7	11.1	10.5	10.0	9.5	9.1	8.8
	90	0.750	27.8	24.8	22.3	20.3	18.6	17.1	15.9	14.9	13.9	13.1	12.4	11.7	11.1	10.6	10.1	9.7	9.3
	100	0.791	29.3	26.1	23.5	21.3	19.6	18.1	16.8	15.7	14.7	13.8	13.0	12.4	11.7	11.2	10.7	10.2	9.8
	110	0.829	30.8	27.4	24.6	22.4	20.5	18.9	17.6	16.4	15.4	14.5	13.7	13.0	12.3	11.7	11.2	10.7	10.3
AI11006VS	30	0.520	19.3	17.1	15.4	14.0	12.9	11.9	11.0	10.3	9.6	9.1	8.6	8.1	7.7	7.3	7.0	6.7	6.4
	40	0.600	22.3	19.8	17.8	16.2	14.9	13.7	12.7	11.9	11.1	10.5	9.9	9.4	8.9	8.5	8.1	7.7	7.4

AI 110° / AI UB 85° 40" TIP SPACING

ALL VALUES BASED ON WATER FOR OTHER LIQUIDS SEE USEFUL FORMULAS AND CONVERSIONS

12.5	13.0	13.5	14.0	14.5	15.0	15.5	16.0	16.5	17.0	17.5	18.0	18.5	19.0	19.5	20.0	mph	
																gpm	psi
1.5	1.5	1.4	1.4	1.3	1.3	1.2	1.2	1.2	1.1	1.1	1.1	1.0	1.0	1.0	1.0	0.130	30
1.8	1.7	1.7	1.6	1.5	1.5	1.4	1.4	1.4	1.3	1.3	1.2	1.2	1.2	1.1	1.1	0.150	40
2.0	1.9	1.8	1.8	1.7	1.7	1.6	1.6	1.5	1.5	1.4	1.4	1.3	1.3	1.3	1.2	0.168	50
2.2	2.1	2.0	1.9	1.9	1.8	1.8	1.7	1.7	1.6	1.6	1.5	1.5	1.4	1.4	1.4	0.184	60
2.4	2.3	2.2	2.1	2.0	2.0	1.9	1.8	1.8	1.7	1.7	1.6	1.6	1.6	1.5	1.5	0.198	70
2.5	2.4	2.3	2.3	2.2	2.1	2.0	2.0	1.9	1.9	1.8	1.8	1.7	1.7	1.6	1.6	0.212	80
2.7	2.6	2.5	2.4	2.3	2.2	2.2	2.1	2.0	2.0	1.9	1.9	1.8	1.8	1.7	1.7	0.225	90
2.8	2.7	2.6	2.5	2.4	2.3	2.3	2.2	2.1	2.1	2.0	2.0	1.9	1.9	1.8	1.8	0.237	100
3.0	2.8	2.7	2.6	2.5	2.5	2.4	2.3	2.2	2.2	2.1	2.1	2.0	1.9	1.9	1.8	0.249	110
2.1	2.0	1.9	1.8	1.8	1.7	1.7	1.6	1.6	1.5	1.5	1.4	1.4	1.4	1.3	1.3	0.173	30
2.4	2.3	2.2	2.1	2.0	2.0	1.9	1.9	1.8	1.7	1.7	1.7	1.6	1.6	1.5	1.5	0.200	40
2.7	2.6	2.5	2.4	2.3	2.2	2.1	2.1	2.0	2.0	1.9	1.8	1.8	1.7	1.7	1.7	0.224	50
2.9	2.8	2.7	2.6	2.5	2.4	2.3	2.3	2.2	2.1	2.1	2.0	2.0	1.9	1.9	1.8	0.245	60
3.1	3.0	2.9	2.8	2.7	2.6	2.5	2.5	2.4	2.3	2.2	2.2	2.1	2.1	2.0	2.0	0.265	70
3.4	3.2	3.1	3.0	2.9	2.8	2.7	2.6	2.5	2.5	2.4	2.3	2.3	2.2	2.2	2.1	0.283	80
3.6	3.4	3.3	3.2	3.1	3.0	2.9	2.8	2.7	2.6	2.5	2.5	2.4	2.3	2.3	2.2	0.300	90
3.8	3.6	3.5	3.4	3.2	3.1	3.0	2.9	2.8	2.8	2.7	2.6	2.5	2.5	2.4	2.3	0.316	100
3.9	3.8	3.6	3.5	3.4	3.3	3.2	3.1	3.0	2.9	2.8	2.7	2.7	2.6	2.5	2.5	0.332	110
2.6	2.5	2.4	2.3	2.2	2.1	2.1	2.0	1.9	1.9	1.8	1.8	1.7	1.7	1.6	1.6	0.217	30
3.0	2.9	2.8	2.7	2.6	2.5	2.4	2.3	2.3	2.2	2.1	2.1	2.0	2.0	1.9	1.9	0.250	40
3.3	3.2	3.1	3.0	2.9	2.8	2.7	2.6	2.5	2.4	2.4	2.3	2.2	2.2	2.1	2.1	0.280	50
3.6	3.5	3.4	3.2	3.1	3.0	2.9	2.8	2.8	2.7	2.6	2.5	2.5	2.4	2.3	2.3	0.306	60
3.9	3.8	3.6	3.5	3.4	3.3	3.2	3.1	3.0	2.9	2.8	2.7	2.7	2.6	2.5	2.5	0.331	70
4.2	4.0	3.9	3.8	3.6	3.5	3.4	3.3	3.2	3.1	3.0	2.9	2.8	2.8	2.7	2.6	0.354	80
4.5	4.3	4.1	4.0	3.8	3.7	3.6	3.5	3.4	3.3	3.2	3.1	3.0	2.9	2.9	2.8	0.375	90
4.7	4.5	4.3	4.2	4.0	3.9	3.8	3.7	3.6	3.5	3.4	3.3	3.2	3.1	3.0	2.9	0.395	100
4.9	4.7	4.6	4.4	4.2	4.1	4.0	3.8	3.7	3.6	3.5	3.4	3.3	3.2	3.2	3.1	0.415	110
3.1	3.0	2.9	2.8	2.7	2.6	2.5	2.4	2.3	2.3	2.2	2.1	2.1	2.0	2.0	1.9	0.260	30
3.6	3.4	3.3	3.2	3.1	3.0	2.9	2.8	2.7	2.6	2.5	2.5	2.4	2.3	2.3	2.2	0.300	40
4.0	3.8	3.7	3.6	3.4	3.3	3.2	3.1	3.0	2.9	2.8	2.8	2.7	2.6	2.6	2.5	0.335	50
4.4	4.2	4.0	3.9	3.8	3.6	3.5	3.4	3.3	3.2	3.1	3.0	2.9	2.9	2.8	2.7	0.367	60
4.7	4.5	4.4	4.2	4.1	3.9	3.8	3.7	3.6	3.5	3.4	3.3	3.2	3.1	3.0	2.9	0.397	70
5.0	4.8	4.7	4.5	4.3	4.2	4.1	3.9	3.8	3.7	3.6	3.5	3.4	3.3	3.2	3.2	0.424	80
5.3	5.1	5.0	4.8	4.6	4.5	4.3	4.2	4.1	3.9	3.8	3.7	3.6	3.5	3.4	3.3	0.450	90
5.6	5.4	5.2	5.0	4.9	4.7	4.5	4.4	4.3	4.1	4.0	3.9	3.8	3.7	3.6	3.5	0.474	100
5.9	5.7	5.5	5.3	5.1	4.9	4.8	4.6	4.5	4.3	4.2	4.1	4.0	3.9	3.8	3.7	0.497	110
4.1	4.0	3.8	3.7	3.5	3.4	3.3	3.2	3.1	3.0	2.9	2.9	2.8	2.7	2.6	2.6	0.346	30
4.8	4.6	4.4	4.2	4.1	4.0	3.8	3.7	3.6	3.5	3.4	3.3	3.2	3.1	3.0	3.0	0.400	40
5.3	5.1	4.9	4.7	4.6	4.4	4.3	4.2	4.0	3.9	3.8	3.7	3.6	3.5	3.4	3.3	0.447	50
5.8	5.6	5.4	5.2	5.0	4.8	4.7	4.5	4.4	4.3	4.2	4.0	3.9	3.8	3.7	3.6	0.490	60
6.3	6.0	5.8	5.6	5.4	5.2	5.1	4.9	4.8	4.6	4.5	4.4	4.2	4.1	4.0	3.9	0.529	70
6.7	6.5	6.2	6.0	5.8	5.6	5.4	5.3	5.1	4.9	4.8	4.7	4.5	4.4	4.3	4.2	0.566	80
7.1	6.9	6.6	6.4	6.1	5.9	5.7	5.6	5.4	5.2	5.1	5.0	4.8	4.7	4.6	4.5	0.600	90
7.5	7.2	7.0	6.7	6.5	6.3	6.1	5.9	5.7	5.5	5.4	5.2	5.1	4.9	4.8	4.7	0.632	100
7.9	7.6	7.3	7.0	6.8	6.6	6.4	6.2	6.0	5.8	5.6	5.5	5.3	5.2	5.1	4.9	0.663	110
5.1	4.9	4.8	4.6	4.4	4.3	4.1	4.0	3.9	3.8	3.7	3.6	3.5	3.4	3.3	3.2	0.433	30
5.9	5.7	5.5	5.3	5.1	5.0	4.8	4.6	4.5	4.4	4.2	4.1	4.0	3.9	3.8	3.7	0.500	40
6.6	6.4	6.1	5.9	5.7	5.5	5.4	5.2	5.0	4.9	4.7	4.6	4.5	4.4	4.3	4.2	0.559	50
7.3	7.0	6.7	6.5	6.3	6.1	5.9	5.7	5.5	5.3	5.2	5.1	4.9	4.8	4.7	4.5	0.612	60
7.9	7.6	7.3	7.0	6.8	6.5	6.3	6.1	6.0	5.8	5.6	5.5	5.3	5.2	5.0	4.9	0.661	70
8.4	8.1	7.8	7.5	7.2	7.0	6.8	6.6	6.4	6.2	6.0	5.8	5.7	5.5	5.4	5.3	0.707	80
8.9	8.6	8.3	8.0	7.7	7.4	7.2	7.0	6.8	6.6	6.4	6.2	6.0	5.9	5.7	5.6	0.750	90
9.4	9.0	8.7	8.4	8.1	7.8	7.6	7.3	7.1	6.9	6.7	6.5	6.3	6.2	6.0	5.9	0.791	100
9.9	9.5	9.1	8.8	8.5	8.2	7.9	7.7	7.5	7.2	7.0	6.8	6.7	6.5	6.3	6.2	0.829	110
6.2	5.9	5.7	5.5	5.3	5.1	5.0	4.8	4.7	4.5	4.4	4.3	4.2	4.1	4.0	3.9	0.520	30
7.1	6.9	6.6	6.4	6.1	5.9	5.7	5.6	5.4	5.2	5.1	5.0	4.8	4.7	4.6	4.5	0.600	40

AI 110° / AI UB 85° 40" TIP SPACING

ALL VALUES BASED ON WATER FOR OTHER LIQUIDS SEE USEFUL FORMULAS AND CONVERSIONS

mph		4.0	4.5	5.0	5.5	6.0	6.5	7.0	7.5	8.0	8.5	9.0	9.5	10.0	10.5	11.0	11.5	12.0	
50 MESH	psi																		
	gpm																		
	50	0.671	24.9	22.1	19.9	18.1	16.6	15.3	14.2	13.3	12.5	11.7	11.1	10.5	10.0	9.5	9.1	8.7	8.3
	60	0.735	27.3	24.2	21.8	19.8	18.2	16.8	15.6	14.5	13.6	12.8	12.1	11.5	10.9	10.4	9.9	9.5	9.1
	70	0.794	29.5	26.2	23.6	21.4	19.6	18.1	16.8	15.7	14.7	13.9	13.1	12.4	11.8	11.2	10.7	10.2	9.8
	80	0.849	31.5	28.0	25.2	22.9	21.0	19.4	18.0	16.8	15.8	14.8	14.0	13.3	12.6	12.0	11.5	11.0	10.5
	90	0.900	33.4	29.7	26.7	24.3	22.3	20.6	19.1	17.8	16.7	15.7	14.9	14.1	13.4	12.7	12.2	11.6	11.1
GRAY	100	0.949	35.2	31.3	28.2	25.6	23.5	21.7	20.1	18.8	17.6	16.6	15.7	14.8	14.1	13.4	12.8	12.3	11.7
	110	0.995	36.9	32.8	29.6	26.9	24.6	22.7	21.1	19.7	18.5	17.4	16.4	15.6	14.8	14.1	13.4	12.8	12.3
AI11008VS	30	0.693	25.7	22.9	20.6	18.7	17.1	15.8	14.7	13.7	12.9	12.1	11.4	10.8	10.3	9.8	9.4	8.9	8.6
	40	0.800	29.7	26.4	23.8	21.6	19.8	18.3	17.0	15.8	14.9	14.0	13.2	12.5	11.9	11.3	10.8	10.3	9.9
	50	0.894	33.2	29.5	26.6	24.1	22.1	20.4	19.0	17.7	16.6	15.6	14.8	14.0	13.3	12.6	12.1	11.5	11.1
	60	0.980	36.4	32.3	29.1	26.5	24.2	22.4	20.8	19.4	18.2	17.1	16.2	15.3	14.5	13.9	13.2	12.7	12.1
	70	1.058	39.3	34.9	31.4	28.6	26.2	24.2	22.5	21.0	19.6	18.5	17.5	16.5	15.7	15.0	14.3	13.7	13.1
	80	1.131	42.0	37.3	33.6	30.5	28.0	25.8	24.0	22.4	21.0	19.8	18.7	17.7	16.8	16.0	15.3	14.6	14.0
	90	1.200	44.6	39.6	35.6	32.4	29.7	27.4	25.5	23.8	22.3	21.0	19.8	18.8	17.8	17.0	16.2	15.5	14.9
WHITE	100	1.265	47.0	41.7	37.6	34.2	31.3	28.9	26.8	25.0	23.5	22.1	20.9	19.8	18.8	17.9	17.1	16.3	15.7
	110	1.327	49.3	43.8	39.4	35.8	32.8	30.3	28.1	26.3	24.6	23.2	21.9	20.7	19.7	18.8	17.9	17.1	16.4
AI11010VS	30	0.866	32.2	28.6	25.7	23.4	21.4	19.8	18.4	17.1	16.1	15.1	14.3	13.5	12.9	12.2	11.7	11.2	10.7
	40	1.000	37.1	33.0	29.7	27.0	24.8	22.8	21.2	19.8	18.6	17.5	16.5	15.6	14.9	14.1	13.5	12.9	12.4
	50	1.118	41.5	36.9	33.2	30.2	27.7	25.5	23.7	22.1	20.8	19.5	18.4	17.5	16.6	15.8	15.1	14.4	13.8
	60	1.225	45.5	40.4	36.4	33.1	30.3	28.0	26.0	24.2	22.7	21.4	20.2	19.1	18.2	17.3	16.5	15.8	15.2
	70	1.323	49.1	43.7	39.3	35.7	32.7	30.2	28.1	26.2	24.6	23.1	21.8	20.7	19.6	18.7	17.9	17.1	16.4
	80	1.414	52.5	46.7	42.0	38.2	35.0	32.3	30.0	28.0	26.3	24.7	23.3	22.1	21.0	20.0	19.1	18.3	17.5
	90	1.500	55.7	49.5	44.6	40.5	37.1	34.3	31.8	29.7	27.8	26.2	24.8	23.4	22.3	21.2	20.3	19.4	18.6
LIGHT BLUE	100	1.581	58.7	52.2	47.0	42.7	39.1	36.1	33.5	31.3	29.3	27.6	26.1	24.7	23.5	22.4	21.3	20.4	19.6
	110	1.658	61.6	54.7	49.3	44.8	41.0	37.9	35.2	32.8	30.8	29.0	27.4	25.9	24.6	23.5	22.4	21.4	20.5

AI 110°/ AI UB 85° 40" TIP SPACING

ALL VALUES BASED ON WATER FOR OTHER LIQUIDS SEE USEFUL FORMULAS AND CONVERSIONS

12.5	13.0	13.5	14.0	14.5	15.0	15.5	16.0	16.5	17.0	17.5	18.0	18.5	19.0	19.5	20.0	mph		
																	gpm	psi
8.0	7.7	7.4	7.1	6.9	6.6	6.4	6.2	6.0	5.9	5.7	5.5	5.4	5.2	5.1	5.0	0.671	50	
8.7	8.4	8.1	7.8	7.5	7.3	7.0	6.8	6.6	6.4	6.2	6.1	5.9	5.7	5.6	5.5	0.735	60	
9.4	9.1	8.7	8.4	8.1	7.9	7.6	7.4	7.1	6.9	6.7	6.5	6.4	6.2	6.0	5.9	0.794	70	
10.1	9.7	9.3	9.0	8.7	8.4	8.1	7.9	7.6	7.4	7.2	7.0	6.8	6.6	6.5	6.3	0.849	80	
10.7	10.3	9.9	9.5	9.2	8.9	8.6	8.4	8.1	7.9	7.6	7.4	7.2	7.0	6.9	6.7	0.900	90	
11.3	10.8	10.4	10.1	9.7	9.4	9.1	8.8	8.5	8.3	8.1	7.8	7.6	7.4	7.2	7.0	0.949	100	
11.8	11.4	10.9	10.6	10.2	9.9	9.5	9.2	9.0	8.7	8.4	8.2	8.0	7.8	7.6	7.4	0.995	110	
50 MESH																		
8.2	7.9	7.6	7.3	7.1	6.9	6.6	6.4	6.2	6.1	5.9	5.7	5.6	5.4	5.3	5.1	0.693	30	
9.5	9.1	8.8	8.5	8.2	7.9	7.7	7.4	7.2	7.0	6.8	6.6	6.4	6.3	6.1	5.9	0.800	40	
10.6	10.2	9.8	9.5	9.2	8.9	8.6	8.3	8.0	7.8	7.6	7.4	7.2	7.0	6.8	6.6	0.894	50	
11.6	11.2	10.8	10.4	10.0	9.7	9.4	9.1	8.8	8.6	8.3	8.1	7.9	7.7	7.5	7.3	0.980	60	
12.6	12.1	11.6	11.2	10.8	10.5	10.1	9.8	9.5	9.2	9.0	8.7	8.5	8.3	8.1	7.9	1.058	70	
13.4	12.9	12.4	12.0	11.6	11.2	10.8	10.5	10.2	9.9	9.6	9.3	9.1	8.8	8.6	8.4	1.131	80	
14.3	13.7	13.2	12.7	12.3	11.9	11.5	11.1	10.8	10.5	10.2	9.9	9.6	9.4	9.1	8.9	1.200	90	
15.0	14.4	13.9	13.4	13.0	12.5	12.1	11.7	11.4	11.0	10.7	10.4	10.2	9.9	9.6	9.4	1.265	100	
15.8	15.2	14.6	14.1	13.6	13.1	12.7	12.3	11.9	11.6	11.3	10.9	10.6	10.4	10.1	9.9	1.327	110	
50 MESH																		
10.3	9.9	9.5	9.2	8.9	8.6	8.3	8.0	7.8	7.6	7.3	7.1	7.0	6.8	6.6	6.4	0.866	30	
11.9	11.4	11.0	10.6	10.2	9.9	9.6	9.3	9.0	8.7	8.5	8.3	8.0	7.8	7.6	7.4	1.000	40	
13.3	12.8	12.3	11.9	11.5	11.1	10.7	10.4	10.1	9.8	9.5	9.2	9.0	8.7	8.5	8.3	1.118	50	
14.5	14.0	13.5	13.0	12.5	12.1	11.7	11.4	11.0	10.7	10.4	10.1	9.8	9.6	9.3	9.1	1.225	60	
15.7	15.1	14.6	14.0	13.5	13.1	12.7	12.3	11.9	11.6	11.2	10.9	10.6	10.3	10.1	9.8	1.323	70	
16.8	16.2	15.6	15.0	14.5	14.0	13.5	13.1	12.7	12.4	12.0	11.7	11.4	11.1	10.8	10.5	1.414	80	
17.8	17.1	16.5	15.9	15.4	14.9	14.4	13.9	13.5	13.1	12.7	12.4	12.0	11.7	11.4	11.1	1.500	90	
18.8	18.1	17.4	16.8	16.2	15.7	15.1	14.7	14.2	13.8	13.4	13.0	12.7	12.4	12.0	11.7	1.581	100	
19.7	18.9	18.2	17.6	17.0	16.4	15.9	15.4	14.9	14.5	14.1	13.7	13.3	13.0	12.6	12.3	1.658	110	
LIGHT BLUE																		