

### DRIFT GUARD 80° / 110° 16" TIP SPACING

ALL VALUES BASED ON WATER FOR OTHER LIQUIDS SEE USEFUL FORMULAS AND CONVERSIONS

mph		4.0	4.5	5.0	5.5	6.0	6.5	7.0	7.5	8.0	8.5	9.0	9.5	10.0	10.5	11.0	11.5	12.0	
psi gpm																			
DG80015VS	30	0.130	12.1	10.7	9.6	8.8	8.0	7.4	6.9	6.4	6.0	5.7	5.4	5.1	4.8	4.6	4.4	4.2	4.0
DG110015VS	40	0.150	13.9	12.4	11.1	10.1	9.3	8.6	8.0	7.4	7.0	6.6	6.2	5.9	5.6	5.3	5.1	4.8	4.6
100 MESH	50	0.168	15.6	13.8	12.5	11.3	10.4	9.6	8.9	8.3	7.8	7.3	6.9	6.6	6.2	5.9	5.7	5.4	5.2
GREEN	60	0.184	17.1	15.2	13.6	12.4	11.4	10.5	9.7	9.1	8.5	8.0	7.6	7.2	6.8	6.5	6.2	5.9	5.7
DG8002VS	30	0.217	20.1	17.9	16.1	14.6	13.4	12.4	11.5	10.7	10.0	9.5	8.9	8.5	8.0	7.7	7.3	7.0	6.7
DG11002VS	40	0.250	23.2	20.6	18.6	16.9	15.5	14.3	13.3	12.4	11.6	10.9	10.3	9.8	9.3	8.8	8.4	8.1	7.7
50 MESH	50	0.280	25.9	23.1	20.8	18.9	17.3	16.0	14.8	13.8	13.0	12.2	11.5	10.9	10.4	9.9	9.4	9.0	8.6
YELLOW	60	0.306	28.4	25.3	22.7	20.7	18.9	17.5	16.2	15.2	14.2	13.4	12.6	12.0	11.4	10.8	10.3	9.9	9.5
DG8003VS	30	0.260	24.1	21.4	19.3	17.5	16.1	14.8	13.8	12.9	12.1	11.3	10.7	10.2	9.6	9.2	8.8	8.4	8.0
DG11003VS	40	0.300	27.8	24.8	22.3	20.3	18.6	17.1	15.9	14.9	13.9	13.1	12.4	11.7	11.1	10.6	10.1	9.7	9.3
50 MESH	50	0.335	31.1	27.7	24.9	22.6	20.8	19.2	17.8	16.6	15.6	14.6	13.8	13.1	12.5	11.9	11.3	10.8	10.4
BLUE	60	0.367	34.1	30.3	27.3	24.8	22.7	21.0	19.5	18.2	17.1	16.0	15.2	14.4	13.6	13.0	12.4	11.9	11.4
DG8004VS	30	0.346	32.2	28.6	25.7	23.4	21.4	19.8	18.4	17.1	16.1	15.1	14.3	13.5	12.9	12.2	11.7	11.2	10.7
DG11004VS	40	0.400	37.1	33.0	29.7	27.0	24.8	22.8	21.2	19.8	18.6	17.5	16.5	15.6	14.9	14.1	13.5	12.9	12.4
50 MESH	50	0.447	41.5	36.9	33.2	30.2	27.7	25.5	23.7	22.1	20.8	19.5	18.4	17.5	16.6	15.8	15.1	14.4	13.8
RED	60	0.490	45.5	40.4	36.4	33.1	30.3	28.0	26.0	24.2	22.7	21.4	20.2	19.1	18.2	17.3	16.5	15.8	15.2
DG8005VS	30	0.433	40.2	35.7	32.2	29.2	26.8	24.7	23.0	21.4	20.1	18.9	17.9	16.9	16.1	15.3	14.6	14.0	13.4
DG11005VS	40	0.500	46.4	41.3	37.1	33.8	30.9	28.6	26.5	24.8	23.2	21.8	20.6	19.5	18.6	17.7	16.9	16.1	15.5
50 MESH	50	0.559	51.9	46.1	41.5	37.7	34.6	31.9	29.6	27.7	25.9	24.4	23.1	21.8	20.8	19.8	18.9	18.0	17.3
BROWN	60	0.612	56.8	50.5	45.5	41.3	37.9	35.0	32.5	30.3	28.4	26.7	25.3	23.9	22.7	21.7	20.7	19.8	18.9

**DRIFT GUARD 80° / 110° 16" TIP SPACING**

ALL VALUES BASED ON WATER FOR OTHER LIQUIDS SEE USEFUL FORMULAS AND CONVERSIONS

12.5	13.0	13.5	14.0	14.5	15.0	15.5	16.0	16.5	17.0	17.5	18.0	18.5	19.0	19.5	20.0	mph				
																		gpm	psi	
3.9	3.7	3.6	3.4	3.3	3.2	3.1	3.0	2.9	2.8	2.8	2.7	2.6	2.5	2.5	2.4	0.130	30	DG80015VS		
4.5	4.3	4.1	4.0	3.8	3.7	3.6	3.5	3.4	3.3	3.2	3.1	3.0	2.9	2.9	2.8	0.150	40	DG110015VS		
5.0	4.8	4.6	4.4	4.3	4.2	4.0	3.9	3.8	3.7	3.6	3.5	3.4	3.3	3.2	3.1	0.168	50	100 MESH		
5.5	5.2	5.1	4.9	4.7	4.5	4.4	4.3	4.1	4.0	3.9	3.8	3.7	3.6	3.5	3.4	0.184	60	GREEN		
6.4	6.2	6.0	5.7	5.5	5.4	5.2	5.0	4.9	4.7	4.6	4.5	4.3	4.2	4.1	4.0	0.217	30	DG8002VS		
7.4	7.1	6.9	6.6	6.4	6.2	6.0	5.8	5.6	5.5	5.3	5.2	5.0	4.9	4.8	4.6	0.250	40	DG11002VS		
8.3	8.0	7.7	7.4	7.2	6.9	6.7	6.5	6.3	6.1	5.9	5.8	5.6	5.5	5.3	5.2	0.280	50	50 MESH		
9.1	8.7	8.4	8.1	7.8	7.6	7.3	7.1	6.9	6.7	6.5	6.3	6.1	6.0	5.8	5.7	0.306	60	YELLOW		
7.7	7.4	7.1	6.9	6.7	6.4	6.2	6.0	5.8	5.7	5.5	5.4	5.2	5.1	4.9	4.8	0.260	30	DG8003VS		
8.9	8.6	8.3	8.0	7.7	7.4	7.2	7.0	6.8	6.6	6.4	6.2	6.0	5.9	5.7	5.6	0.300	40	DG11003VS		
10.0	9.6	9.2	8.9	8.6	8.3	8.0	7.8	7.5	7.3	7.1	6.9	6.7	6.6	6.4	6.2	0.335	50	50 MESH		
10.9	10.5	10.1	9.7	9.4	9.1	8.8	8.5	8.3	8.0	7.8	7.6	7.4	7.2	7.0	6.8	0.367	60	BLUE		
10.3	9.9	9.5	9.2	8.9	8.6	8.3	8.0	7.8	7.6	7.3	7.1	7.0	6.8	6.6	6.4	0.346	30	DG8004VS		
11.9	11.4	11.0	10.6	10.2	9.9	9.6	9.3	9.0	8.7	8.5	8.3	8.0	7.8	7.6	7.4	0.400	40	DG11004VS		
13.3	12.8	12.3	11.9	11.5	11.1	10.7	10.4	10.1	9.8	9.5	9.2	9.0	8.7	8.5	8.3	0.447	50	50 MESH		
14.5	14.0	13.5	13.0	12.5	12.1	11.7	11.4	11.0	10.7	10.4	10.1	9.8	9.6	9.3	9.1	0.490	60	RED		
12.9	12.4	11.9	11.5	11.1	10.7	10.4	10.0	9.7	9.5	9.2	8.9	8.7	8.5	8.2	8.0	0.433	30	DG8005VS		
14.9	14.3	13.8	13.3	12.8	12.4	12.0	11.6	11.3	10.9	10.6	10.3	10.0	9.8	9.5	9.3	0.500	40	DG11005VS		
16.6	16.0	15.4	14.8	14.3	13.8	13.4	13.0	12.6	12.2	11.9	11.5	11.2	10.9	10.6	10.4	0.559	50	50 MESH		
18.2	17.5	16.8	16.2	15.7	15.2	14.7	14.2	13.8	13.4	13.0	12.6	12.3	12.0	11.7	11.4	0.612	60	BROWN		