

DRIFT GUARD 80° / 110° 36" TIP SPACING

ALL VALUES BASED ON WATER FOR OTHER LIQUIDS SEE USEFUL FORMULAS AND CONVERSIONS

mph		4.0	4.5	5.0	5.5	6.0	6.5	7.0	7.5	8.0	8.5	9.0	9.5	10.0	10.5	11.0	11.5	12.0	
psi gpm																			
DG80015VS	30	0.130	5.4	4.8	4.3	3.9	3.6	3.3	3.1	2.9	2.7	2.5	2.4	2.3	2.1	2.0	1.9	1.9	1.8
DG110015VS	40	0.150	6.2	5.5	5.0	4.5	4.1	3.8	3.5	3.3	3.1	2.9	2.8	2.6	2.5	2.4	2.3	2.2	2.1
100 MESH	50	0.168	6.9	6.1	5.5	5.0	4.6	4.3	4.0	3.7	3.5	3.3	3.1	2.9	2.8	2.6	2.5	2.4	2.3
GREEN	60	0.184	7.6	6.7	6.1	5.5	5.1	4.7	4.3	4.0	3.8	3.6	3.4	3.2	3.0	2.9	2.8	2.6	2.5
DG8002VS	30	0.217	8.9	7.9	7.1	6.5	6.0	5.5	5.1	4.8	4.5	4.2	4.0	3.8	3.6	3.4	3.2	3.1	3.0
DG11002VS	40	0.250	10.3	9.2	8.3	7.5	6.9	6.3	5.9	5.5	5.2	4.9	4.6	4.3	4.1	3.9	3.8	3.6	3.4
50 MESH	50	0.280	11.5	10.2	9.2	8.4	7.7	7.1	6.6	6.1	5.8	5.4	5.1	4.9	4.6	4.4	4.2	4.0	3.8
YELLOW	60	0.306	12.6	11.2	10.1	9.2	8.4	7.8	7.2	6.7	6.3	5.9	5.6	5.3	5.1	4.8	4.6	4.4	4.2
DG8003VS	30	0.260	10.7	9.5	8.6	7.8	7.1	6.6	6.1	5.7	5.4	5.0	4.8	4.5	4.3	4.1	3.9	3.7	3.6
DG11003VS	40	0.300	12.4	11.0	9.9	9.0	8.3	7.6	7.1	6.6	6.2	5.8	5.5	5.2	5.0	4.7	4.5	4.3	4.1
50 MESH	50	0.335	13.8	12.3	11.1	10.1	9.2	8.5	7.9	7.4	6.9	6.5	6.1	5.8	5.5	5.3	5.0	4.8	4.6
BLUE	60	0.367	15.2	13.5	12.1	11.0	10.1	9.3	8.7	8.1	7.6	7.1	6.7	6.4	6.1	5.8	5.5	5.3	5.1
DG8004VS	30	0.346	14.3	12.7	11.4	10.4	9.5	8.8	8.2	7.6	7.1	6.7	6.4	6.0	5.7	5.4	5.2	5.0	4.8
DG11004VS	40	0.400	16.5	14.7	13.2	12.0	11.0	10.2	9.4	8.8	8.3	7.8	7.3	6.9	6.6	6.3	6.0	5.7	5.5
50 MESH	50	0.447	18.4	16.4	14.8	13.4	12.3	11.4	10.5	9.8	9.2	8.7	8.2	7.8	7.4	7.0	6.7	6.4	6.1
RED	60	0.490	20.2	18.0	16.2	14.7	13.5	12.4	11.5	10.8	10.1	9.5	9.0	8.5	8.1	7.7	7.3	7.0	6.7
DG8005VS	30	0.433	17.9	15.9	14.3	13.0	11.9	11.0	10.2	9.5	8.9	8.4	7.9	7.5	7.1	6.8	6.5	6.2	6.0
DG11005VS	40	0.500	20.6	18.3	16.5	15.0	13.8	12.7	11.8	11.0	10.3	9.7	9.2	8.7	8.3	7.9	7.5	7.2	6.9
50 MESH	50	0.559	23.1	20.5	18.4	16.8	15.4	14.2	13.2	12.3	11.5	10.9	10.2	9.7	9.2	8.8	8.4	8.0	7.7
BROWN	60	0.612	25.3	22.5	20.2	18.4	16.8	15.5	14.4	13.5	12.6	11.9	11.2	10.6	10.1	9.6	9.2	8.8	8.4

