

DRIFT GUARD 80° / 110° 38" TIP SPACING

ALL VALUES BASED ON WATER FOR OTHER LIQUIDS SEE USEFUL FORMULAS AND CONVERSIONS

mph		4.0	4.5	5.0	5.5	6.0	6.5	7.0	7.5	8.0	8.5	9.0	9.5	10.0	10.5	11.0	11.5	12.0	
psi gpm																			
DG80015VS	30	0.130	5.1	4.5	4.1	3.7	3.4	3.1	2.9	2.7	2.5	2.4	2.3	2.1	2.0	1.9	1.8	1.8	1.7
DG110015VS	40	0.150	5.9	5.2	4.7	4.3	3.9	3.6	3.3	3.1	2.9	2.8	2.6	2.5	2.3	2.2	2.1	2.0	2.0
100 MESH	50	0.168	6.6	5.8	5.2	4.8	4.4	4.0	3.7	3.5	3.3	3.1	2.9	2.8	2.6	2.5	2.4	2.3	2.2
GREEN	60	0.184	7.2	6.4	5.7	5.2	4.8	4.4	4.1	3.8	3.6	3.4	3.2	3.0	2.9	2.7	2.6	2.5	2.4
DG8002VS	30	0.217	8.5	7.5	6.8	6.2	5.6	5.2	4.8	4.5	4.2	4.0	3.8	3.6	3.4	3.2	3.1	2.9	2.8
DG11002VS	40	0.250	9.8	8.7	7.8	7.1	6.5	6.0	5.6	5.2	4.9	4.6	4.3	4.1	3.9	3.7	3.6	3.4	3.3
50 MESH	50	0.280	10.9	9.7	8.7	7.9	7.3	6.7	6.2	5.8	5.5	5.1	4.9	4.6	4.4	4.2	4.0	3.8	3.6
YELLOW	60	0.306	12.0	10.6	9.6	8.7	8.0	7.4	6.8	6.4	6.0	5.6	5.3	5.0	4.8	4.6	4.4	4.2	4.0
DG8003VS	30	0.260	10.2	9.0	8.1	7.4	6.8	6.2	5.8	5.4	5.1	4.8	4.5	4.3	4.1	3.9	3.7	3.5	3.4
DG11003VS	40	0.300	11.7	10.4	9.4	8.5	7.8	7.2	6.7	6.3	5.9	5.5	5.2	4.9	4.7	4.5	4.3	4.1	3.9
50 MESH	50	0.335	13.1	11.7	10.5	9.5	8.7	8.1	7.5	7.0	6.6	6.2	5.8	5.5	5.2	5.0	4.8	4.6	4.4
BLUE	60	0.367	14.4	12.8	11.5	10.4	9.6	8.8	8.2	7.7	7.2	6.8	6.4	6.0	5.7	5.5	5.2	5.0	4.8
DG8004VS	30	0.346	13.5	12.0	10.8	9.8	9.0	8.3	7.7	7.2	6.8	6.4	6.0	5.7	5.4	5.2	4.9	4.7	4.5
DG11004VS	40	0.400	15.6	13.9	12.5	11.4	10.4	9.6	8.9	8.3	7.8	7.4	6.9	6.6	6.3	6.0	5.7	5.4	5.2
50 MESH	50	0.447	17.5	15.5	14.0	12.7	11.7	10.8	10.0	9.3	8.7	8.2	7.8	7.4	7.0	6.7	6.4	6.1	5.8
RED	60	0.490	19.1	17.0	15.3	13.9	12.8	11.8	10.9	10.2	9.6	9.0	8.5	8.1	7.7	7.3	7.0	6.7	6.4
DG8005VS	30	0.433	16.9	15.0	13.5	12.3	11.3	10.4	9.7	9.0	8.5	8.0	7.5	7.1	6.8	6.4	6.2	5.9	5.6
DG11005VS	40	0.500	19.5	17.4	15.6	14.2	13.0	12.0	11.2	10.4	9.8	9.2	8.7	8.2	7.8	7.4	7.1	6.8	6.5
50 MESH	50	0.559	21.8	19.4	17.5	15.9	14.6	13.4	12.5	11.7	10.9	10.3	9.7	9.2	8.7	8.3	7.9	7.6	7.3
BROWN	60	0.612	23.9	21.3	19.1	17.4	16.0	14.7	13.7	12.8	12.0	11.3	10.6	10.1	9.6	9.1	8.7	8.3	8.0

DRIFT GUARD 80° / 110° 38" TIP SPACING

ALL VALUES BASED ON WATER FOR OTHER LIQUIDS SEE USEFUL FORMULAS AND CONVERSIONS

12.5	13.0	13.5	14.0	14.5	15.0	15.5	16.0	16.5	17.0	17.5	18.0	18.5	19.0	19.5	20.0	mph				
																			gpm	psi
1.6	1.6	1.5	1.5	1.4	1.4	1.3	1.3	1.2	1.2	1.2	1.1	1.1	1.1	1.0	1.0	0.130	30	DG80015VS		
1.9	1.8	1.7	1.7	1.6	1.6	1.5	1.5	1.4	1.4	1.3	1.3	1.3	1.2	1.2	1.2	0.150	40	DG110015VS		
2.1	2.0	1.9	1.9	1.8	1.7	1.7	1.6	1.6	1.5	1.5	1.5	1.4	1.4	1.3	1.3	0.168	50	100 MESH		
2.3	2.2	2.1	2.1	2.0	1.9	1.9	1.8	1.7	1.7	1.6	1.6	1.6	1.5	1.5	1.4	0.184	60	GREEN		
2.7	2.6	2.5	2.4	2.3	2.3	2.2	2.1	2.1	2.0	1.9	1.9	1.8	1.8	1.7	1.7	0.217	30	DG8002VS		
3.1	3.0	2.9	2.8	2.7	2.6	2.5	2.4	2.4	2.3	2.2	2.2	2.1	2.1	2.0	2.0	0.250	40	DG11002VS		
3.5	3.4	3.2	3.1	3.0	2.9	2.8	2.7	2.6	2.6	2.5	2.4	2.4	2.3	2.2	2.2	0.280	50	50 MESH		
3.8	3.7	3.5	3.4	3.3	3.2	3.1	3.0	2.9	2.8	2.7	2.7	2.6	2.5	2.5	2.4	0.306	60	YELLOW		
3.2	3.1	3.0	2.9	2.8	2.7	2.6	2.5	2.5	2.4	2.3	2.3	2.2	2.1	2.1	2.0	0.260	30	DG8003VS		
3.8	3.6	3.5	3.3	3.2	3.1	3.0	2.9	2.8	2.8	2.7	2.6	2.5	2.5	2.4	2.3	0.300	40	DG11003VS		
4.2	4.0	3.9	3.7	3.6	3.5	3.4	3.3	3.2	3.1	3.0	2.9	2.8	2.8	2.7	2.6	0.335	50	50 MESH		
4.6	4.4	4.3	4.1	4.0	3.8	3.7	3.6	3.5	3.4	3.3	3.2	3.1	3.0	2.9	2.9	0.367	60	BLUE		
4.3	4.2	4.0	3.9	3.7	3.6	3.5	3.4	3.3	3.2	3.1	3.0	2.9	2.8	2.8	2.7	0.346	30	DG8004VS		
5.0	4.8	4.6	4.5	4.3	4.2	4.0	3.9	3.8	3.7	3.6	3.5	3.4	3.3	3.2	3.1	0.400	40	DG11004VS		
5.6	5.4	5.2	5.0	4.8	4.7	4.5	4.4	4.2	4.1	4.0	3.9	3.8	3.7	3.6	3.5	0.447	50	50 MESH		
6.1	5.9	5.7	5.5	5.3	5.1	4.9	4.8	4.6	4.5	4.4	4.3	4.1	4.0	3.9	3.8	0.490	60	RED		
5.4	5.2	5.0	4.8	4.7	4.5	4.4	4.2	4.1	4.0	3.9	3.8	3.7	3.6	3.5	3.4	0.433	30	DG8005VS		
6.3	6.0	5.8	5.6	5.4	5.2	5.0	4.9	4.7	4.6	4.5	4.3	4.2	4.1	4.0	3.9	0.500	40	DG11005VS		
7.0	6.7	6.5	6.2	6.0	5.8	5.6	5.5	5.3	5.1	5.0	4.9	4.7	4.6	4.5	4.4	0.559	50	50 MESH		
7.7	7.4	7.1	6.8	6.6	6.4	6.2	6.0	5.8	5.6	5.5	5.3	5.2	5.0	4.9	4.8	0.612	60	BROWN		