

DRIFT GUARD 80° / 110° 40" TIP SPACING

ALL VALUES BASED ON WATER FOR OTHER LIQUIDS SEE USEFUL FORMULAS AND CONVERSIONS

mph		4.0	4.5	5.0	5.5	6.0	6.5	7.0	7.5	8.0	8.5	9.0	9.5	10.0	10.5	11.0	11.5	12.0	
psi gpm																			
DG80015VS	30	0.130	4.8	4.3	3.9	3.5	3.2	3.0	2.8	2.6	2.4	2.3	2.1	2.0	1.9	1.8	1.8	1.7	1.6
DG110015VS	40	0.150	5.6	5.0	4.5	4.1	3.7	3.4	3.2	3.0	2.8	2.6	2.5	2.3	2.2	2.1	2.0	1.9	1.9
100 MESH	50	0.168	6.2	5.5	5.0	4.5	4.2	3.8	3.6	3.3	3.1	2.9	2.8	2.6	2.5	2.4	2.3	2.2	2.1
GREEN	60	0.184	6.8	6.1	5.5	5.0	4.5	4.2	3.9	3.6	3.4	3.2	3.0	2.9	2.7	2.6	2.5	2.4	2.3
DG8002VS	30	0.217	8.0	7.1	6.4	5.8	5.4	4.9	4.6	4.3	4.0	3.8	3.6	3.4	3.2	3.1	2.9	2.8	2.7
DG11002VS	40	0.250	9.3	8.3	7.4	6.8	6.2	5.7	5.3	5.0	4.6	4.4	4.1	3.9	3.7	3.5	3.4	3.2	3.1
50 MESH	50	0.280	10.4	9.2	8.3	7.5	6.9	6.4	5.9	5.5	5.2	4.9	4.6	4.4	4.2	4.0	3.8	3.6	3.5
YELLOW	60	0.306	11.4	10.1	9.1	8.3	7.6	7.0	6.5	6.1	5.7	5.3	5.1	4.8	4.5	4.3	4.1	4.0	3.8
DG8003VS	30	0.260	9.6	8.6	7.7	7.0	6.4	5.9	5.5	5.1	4.8	4.5	4.3	4.1	3.9	3.7	3.5	3.4	3.2
DG11003VS	40	0.300	11.1	9.9	8.9	8.1	7.4	6.9	6.4	5.9	5.6	5.2	5.0	4.7	4.5	4.2	4.1	3.9	3.7
50 MESH	50	0.335	12.5	11.1	10.0	9.1	8.3	7.7	7.1	6.6	6.2	5.9	5.5	5.2	5.0	4.7	4.5	4.3	4.2
BLUE	60	0.367	13.6	12.1	10.9	9.9	9.1	8.4	7.8	7.3	6.8	6.4	6.1	5.7	5.5	5.2	5.0	4.7	4.5
DG8004VS	30	0.346	12.9	11.4	10.3	9.4	8.6	7.9	7.3	6.9	6.4	6.1	5.7	5.4	5.1	4.9	4.7	4.5	4.3
DG11004VS	40	0.400	14.9	13.2	11.9	10.8	9.9	9.1	8.5	7.9	7.4	7.0	6.6	6.3	5.9	5.7	5.4	5.2	5.0
50 MESH	50	0.447	16.6	14.8	13.3	12.1	11.1	10.2	9.5	8.9	8.3	7.8	7.4	7.0	6.6	6.3	6.0	5.8	5.5
RED	60	0.490	18.2	16.2	14.5	13.2	12.1	11.2	10.4	9.7	9.1	8.6	8.1	7.7	7.3	6.9	6.6	6.3	6.1
DG8005VS	30	0.433	16.1	14.3	12.9	11.7	10.7	9.9	9.2	8.6	8.0	7.6	7.1	6.8	6.4	6.1	5.8	5.6	5.4
DG11005VS	40	0.500	18.6	16.5	14.9	13.5	12.4	11.4	10.6	9.9	9.3	8.7	8.3	7.8	7.4	7.1	6.8	6.5	6.2
50 MESH	50	0.559	20.8	18.4	16.6	15.1	13.8	12.8	11.9	11.1	10.4	9.8	9.2	8.7	8.3	7.9	7.5	7.2	6.9
BROWN	60	0.612	22.7	20.2	18.2	16.5	15.2	14.0	13.0	12.1	11.4	10.7	10.1	9.6	9.1	8.7	8.3	7.9	7.6

