

DRIFT GUARD 95° EVEN 30" TIP SPACING

ALL VALUES BASED ON WATER FOR OTHER LIQUIDS SEE USEFUL FORMULAS AND CONVERSIONS

mph		4.0	4.5	5.0	5.5	6.0	6.5	7.0	7.5	8.0	8.5	9.0	9.5	10.0	10.5	11.0	11.5	12.0	
psi gpm																			
DG95015EVS 100 MESH GREEN	30	0.130	6.4	5.7	5.1	4.7	4.3	4.0	3.7	3.4	3.2	3.0	2.9	2.7	2.6	2.4	2.3	2.2	2.1
	40	0.150	7.4	6.6	5.9	5.4	5.0	4.6	4.2	4.0	3.7	3.5	3.3	3.1	3.0	2.8	2.7	2.6	2.5
	50	0.168	8.3	7.4	6.6	6.0	5.5	5.1	4.7	4.4	4.2	3.9	3.7	3.5	3.3	3.2	3.0	2.9	2.8
	60	0.184	9.1	8.1	7.3	6.6	6.1	5.6	5.2	4.8	4.5	4.3	4.0	3.8	3.6	3.5	3.3	3.2	3.0
DG9502EVS 50 MESH YELLOW	30	0.217	10.7	9.5	8.6	7.8	7.1	6.6	6.1	5.7	5.4	5.0	4.8	4.5	4.3	4.1	3.9	3.7	3.6
	40	0.250	12.4	11.0	9.9	9.0	8.3	7.6	7.1	6.6	6.2	5.8	5.5	5.2	5.0	4.7	4.5	4.3	4.1
	50	0.280	13.8	12.3	11.1	10.1	9.2	8.5	7.9	7.4	6.9	6.5	6.1	5.8	5.5	5.3	5.0	4.8	4.6
	60	0.306	15.2	13.5	12.1	11.0	10.1	9.3	8.7	8.1	7.6	7.1	6.7	6.4	6.1	5.8	5.5	5.3	5.1
DG9503EVS 50 MESH BLUE	30	0.260	12.9	11.4	10.3	9.4	8.6	7.9	7.3	6.9	6.4	6.1	5.7	5.4	5.1	4.9	4.7	4.5	4.3
	40	0.300	14.9	13.2	11.9	10.8	9.9	9.1	8.5	7.9	7.4	7.0	6.6	6.3	5.9	5.7	5.4	5.2	5.0
	50	0.335	16.6	14.8	13.3	12.1	11.1	10.2	9.5	8.9	8.3	7.8	7.4	7.0	6.6	6.3	6.0	5.8	5.5
	60	0.367	18.2	16.2	14.5	13.2	12.1	11.2	10.4	9.7	9.1	8.6	8.1	7.7	7.3	6.9	6.6	6.3	6.1
DG9504EVS 50 MESH RED	30	0.346	17.1	15.2	13.7	12.5	11.4	10.6	9.8	9.1	8.6	8.1	7.6	7.2	6.9	6.5	6.2	6.0	5.7
	40	0.400	19.8	17.6	15.8	14.4	13.2	12.2	11.3	10.6	9.9	9.3	8.8	8.3	7.9	7.5	7.2	6.9	6.6
	50	0.447	22.1	19.7	17.7	16.1	14.8	13.6	12.6	11.8	11.1	10.4	9.8	9.3	8.9	8.4	8.0	7.7	7.4
	60	0.490	24.2	21.6	19.4	17.6	16.2	14.9	13.9	12.9	12.1	11.4	10.8	10.2	9.7	9.2	8.8	8.4	8.1
DG9505EVS 50 MESH BROWN	30	0.433	21.4	19.1	17.1	15.6	14.3	13.2	12.2	11.4	10.7	10.1	9.5	9.0	8.6	8.2	7.8	7.5	7.1
	40	0.500	24.8	22.0	19.8	18.0	16.5	15.2	14.1	13.2	12.4	11.6	11.0	10.4	9.9	9.4	9.0	8.6	8.3
	50	0.559	27.7	24.6	22.1	20.1	18.4	17.0	15.8	14.8	13.8	13.0	12.3	11.7	11.1	10.5	10.1	9.6	9.2
	60	0.612	30.3	26.9	24.2	22.0	20.2	18.7	17.3	16.2	15.2	14.3	13.5	12.8	12.1	11.5	11.0	10.5	10.1

DRIFT GUARD 95° EVEN 30" TIP SPACING

ALL VALUES BASED ON WATER FOR OTHER LIQUIDS SEE USEFUL FORMULAS AND CONVERSIONS

12.5	13.0	13.5	14.0	14.5	15.0	15.5	16.0	16.5	17.0	17.5	18.0	18.5	19.0	19.5	20.0	mph		
																	gpm	psi
2.1	2.0	1.9	1.8	1.8	1.7	1.7	1.6	1.6	1.5	1.5	1.4	1.4	1.4	1.3	1.3	0.130	30	DG95015EVS 100 MESH GREEN
2.4	2.3	2.2	2.1	2.0	2.0	1.9	1.9	1.8	1.7	1.7	1.7	1.6	1.6	1.5	1.5	0.150	40	
2.7	2.6	2.5	2.4	2.3	2.2	2.1	2.1	2.0	2.0	1.9	1.8	1.8	1.7	1.7	1.7	0.168	50	
2.9	2.8	2.7	2.6	2.5	2.4	2.3	2.3	2.2	2.1	2.1	2.0	2.0	1.9	1.9	1.8	0.184	60	
3.4	3.3	3.2	3.1	3.0	2.9	2.8	2.7	2.6	2.5	2.4	2.4	2.3	2.3	2.2	2.1	0.217	30	DG9502EVS 50 MESH YELLOW
4.0	3.8	3.7	3.5	3.4	3.3	3.2	3.1	3.0	2.9	2.8	2.8	2.7	2.6	2.5	2.5	0.250	40	
4.4	4.3	4.1	4.0	3.8	3.7	3.6	3.5	3.4	3.3	3.2	3.1	3.0	2.9	2.8	2.8	0.280	50	
4.8	4.7	4.5	4.3	4.2	4.0	3.9	3.8	3.7	3.6	3.5	3.4	3.3	3.2	3.1	3.0	0.306	60	
4.1	4.0	3.8	3.7	3.5	3.4	3.3	3.2	3.1	3.0	2.9	2.9	2.8	2.7	2.6	2.6	0.260	30	DG9503EVS 50 MESH BLUE
4.8	4.6	4.4	4.2	4.1	4.0	3.8	3.7	3.6	3.5	3.4	3.3	3.2	3.1	3.0	3.0	0.300	40	
5.3	5.1	4.9	4.7	4.6	4.4	4.3	4.2	4.0	3.9	3.8	3.7	3.6	3.5	3.4	3.3	0.335	50	
5.8	5.6	5.4	5.2	5.0	4.8	4.7	4.5	4.4	4.3	4.2	4.0	3.9	3.8	3.7	3.6	0.367	60	
5.5	5.3	5.1	4.9	4.7	4.6	4.4	4.3	4.2	4.0	3.9	3.8	3.7	3.6	3.5	3.4	0.346	30	DG9504EVS 50 MESH RED
6.3	6.1	5.9	5.7	5.5	5.3	5.1	5.0	4.8	4.7	4.5	4.4	4.3	4.2	4.1	4.0	0.400	40	
7.1	6.8	6.6	6.3	6.1	5.9	5.7	5.5	5.4	5.2	5.1	4.9	4.8	4.7	4.5	4.4	0.447	50	
7.8	7.5	7.2	6.9	6.7	6.5	6.3	6.1	5.9	5.7	5.5	5.4	5.2	5.1	5.0	4.8	0.490	60	
6.9	6.6	6.4	6.1	5.9	5.7	5.5	5.4	5.2	5.0	4.9	4.8	4.6	4.5	4.4	4.3	0.433	30	DG9505EVS 50 MESH BROWN
7.9	7.6	7.3	7.1	6.8	6.6	6.4	6.2	6.0	5.8	5.7	5.5	5.4	5.2	5.1	5.0	0.500	40	
8.9	8.5	8.2	7.9	7.6	7.4	7.1	6.9	6.7	6.5	6.3	6.1	6.0	5.8	5.7	5.5	0.559	50	
9.7	9.3	9.0	8.7	8.4	8.1	7.8	7.6	7.3	7.1	6.9	6.7	6.6	6.4	6.2	6.1	0.612	60	