

### DRIFT GUARD 95° EVEN 32" TIP SPACING

ALL VALUES BASED ON WATER FOR OTHER LIQUIDS SEE USEFUL FORMULAS AND CONVERSIONS

mph		4.0	4.5	5.0	5.5	6.0	6.5	7.0	7.5	8.0	8.5	9.0	9.5	10.0	10.5	11.0	11.5	12.0	
psi gpm																			
DG95015EVS  100 MESH GREEN	30	0.130	6.0	5.4	4.8	4.4	4.0	3.7	3.4	3.2	3.0	2.8	2.7	2.5	2.4	2.3	2.2	2.1	2.0
	40	0.150	7.0	6.2	5.6	5.1	4.6	4.3	4.0	3.7	3.5	3.3	3.1	2.9	2.8	2.7	2.5	2.4	2.3
	50	0.168	7.8	6.9	6.2	5.7	5.2	4.8	4.4	4.2	3.9	3.7	3.5	3.3	3.1	3.0	2.8	2.7	2.6
	60	0.184	8.5	7.6	6.8	6.2	5.7	5.2	4.9	4.5	4.3	4.0	3.8	3.6	3.4	3.2	3.1	3.0	2.8
DG9502EVS  50 MESH YELLOW	30	0.217	10.0	8.9	8.0	7.3	6.7	6.2	5.7	5.4	5.0	4.7	4.5	4.2	4.0	3.8	3.7	3.5	3.3
	40	0.250	11.6	10.3	9.3	8.4	7.7	7.1	6.6	6.2	5.8	5.5	5.2	4.9	4.6	4.4	4.2	4.0	3.9
	50	0.280	13.0	11.5	10.4	9.4	8.6	8.0	7.4	6.9	6.5	6.1	5.8	5.5	5.2	4.9	4.7	4.5	4.3
	60	0.306	14.2	12.6	11.4	10.3	9.5	8.7	8.1	7.6	7.1	6.7	6.3	6.0	5.7	5.4	5.2	4.9	4.7
DG9503EVS  50 MESH BLUE	30	0.260	12.1	10.7	9.6	8.8	8.0	7.4	6.9	6.4	6.0	5.7	5.4	5.1	4.8	4.6	4.4	4.2	4.0
	40	0.300	13.9	12.4	11.1	10.1	9.3	8.6	8.0	7.4	7.0	6.6	6.2	5.9	5.6	5.3	5.1	4.8	4.6
	50	0.335	15.6	13.8	12.5	11.3	10.4	9.6	8.9	8.3	7.8	7.3	6.9	6.6	6.2	5.9	5.7	5.4	5.2
	60	0.367	17.1	15.2	13.6	12.4	11.4	10.5	9.7	9.1	8.5	8.0	7.6	7.2	6.8	6.5	6.2	5.9	5.7
DG9504EVS  50 MESH RED	30	0.346	16.1	14.3	12.9	11.7	10.7	9.9	9.2	8.6	8.0	7.6	7.1	6.8	6.4	6.1	5.8	5.6	5.4
	40	0.400	18.6	16.5	14.9	13.5	12.4	11.4	10.6	9.9	9.3	8.7	8.3	7.8	7.4	7.1	6.8	6.5	6.2
	50	0.447	20.8	18.4	16.6	15.1	13.8	12.8	11.9	11.1	10.4	9.8	9.2	8.7	8.3	7.9	7.5	7.2	6.9
	60	0.490	22.7	20.2	18.2	16.5	15.2	14.0	13.0	12.1	11.4	10.7	10.1	9.6	9.1	8.7	8.3	7.9	7.6
DG9505EVS  50 MESH BROWN	30	0.433	20.1	17.9	16.1	14.6	13.4	12.4	11.5	10.7	10.0	9.5	8.9	8.5	8.0	7.7	7.3	7.0	6.7
	40	0.500	23.2	20.6	18.6	16.9	15.5	14.3	13.3	12.4	11.6	10.9	10.3	9.8	9.3	8.8	8.4	8.1	7.7
	50	0.559	25.9	23.1	20.8	18.9	17.3	16.0	14.8	13.8	13.0	12.2	11.5	10.9	10.4	9.9	9.4	9.0	8.6
	60	0.612	28.4	25.3	22.7	20.7	18.9	17.5	16.2	15.2	14.2	13.4	12.6	12.0	11.4	10.8	10.3	9.9	9.5

