

DRIFT GUARD 95° EVEN 40" TIP SPACING

ALL VALUES BASED ON WATER FOR OTHER LIQUIDS SEE USEFUL FORMULAS AND CONVERSIONS

mph		4.0	4.5	5.0	5.5	6.0	6.5	7.0	7.5	8.0	8.5	9.0	9.5	10.0	10.5	11.0	11.5	12.0	
psi gpm																			
DG95015EVS 100 MESH GREEN	30	0.130	4.8	4.3	3.9	3.5	3.2	3.0	2.8	2.6	2.4	2.3	2.1	2.0	1.9	1.8	1.8	1.7	1.6
	40	0.150	5.6	5.0	4.5	4.1	3.7	3.4	3.2	3.0	2.8	2.6	2.5	2.3	2.2	2.1	2.0	1.9	1.9
	50	0.168	6.2	5.5	5.0	4.5	4.2	3.8	3.6	3.3	3.1	2.9	2.8	2.6	2.5	2.4	2.3	2.2	2.1
	60	0.184	6.8	6.1	5.5	5.0	4.5	4.2	3.9	3.6	3.4	3.2	3.0	2.9	2.7	2.6	2.5	2.4	2.3
DG9502EVS 50 MESH YELLOW	30	0.217	8.0	7.1	6.4	5.8	5.4	4.9	4.6	4.3	4.0	3.8	3.6	3.4	3.2	3.1	2.9	2.8	2.7
	40	0.250	9.3	8.3	7.4	6.8	6.2	5.7	5.3	5.0	4.6	4.4	4.1	3.9	3.7	3.5	3.4	3.2	3.1
	50	0.280	10.4	9.2	8.3	7.5	6.9	6.4	5.9	5.5	5.2	4.9	4.6	4.4	4.2	4.0	3.8	3.6	3.5
	60	0.306	11.4	10.1	9.1	8.3	7.6	7.0	6.5	6.1	5.7	5.3	5.1	4.8	4.5	4.3	4.1	4.0	3.8
DG9503EVS 50 MESH BLUE	30	0.260	9.6	8.6	7.7	7.0	6.4	5.9	5.5	5.1	4.8	4.5	4.3	4.1	3.9	3.7	3.5	3.4	3.2
	40	0.300	11.1	9.9	8.9	8.1	7.4	6.9	6.4	5.9	5.6	5.2	5.0	4.7	4.5	4.2	4.1	3.9	3.7
	50	0.335	12.5	11.1	10.0	9.1	8.3	7.7	7.1	6.6	6.2	5.9	5.5	5.2	5.0	4.7	4.5	4.3	4.2
	60	0.367	13.6	12.1	10.9	9.9	9.1	8.4	7.8	7.3	6.8	6.4	6.1	5.7	5.5	5.2	5.0	4.7	4.5
DG9504EVS 50 MESH RED	30	0.346	12.9	11.4	10.3	9.4	8.6	7.9	7.3	6.9	6.4	6.1	5.7	5.4	5.1	4.9	4.7	4.5	4.3
	40	0.400	14.9	13.2	11.9	10.8	9.9	9.1	8.5	7.9	7.4	7.0	6.6	6.3	5.9	5.7	5.4	5.2	5.0
	50	0.447	16.6	14.8	13.3	12.1	11.1	10.2	9.5	8.9	8.3	7.8	7.4	7.0	6.6	6.3	6.0	5.8	5.5
	60	0.490	18.2	16.2	14.5	13.2	12.1	11.2	10.4	9.7	9.1	8.6	8.1	7.7	7.3	6.9	6.6	6.3	6.1
DG9505EVS 50 MESH BROWN	30	0.433	16.1	14.3	12.9	11.7	10.7	9.9	9.2	8.6	8.0	7.6	7.1	6.8	6.4	6.1	5.8	5.6	5.4
	40	0.500	18.6	16.5	14.9	13.5	12.4	11.4	10.6	9.9	9.3	8.7	8.3	7.8	7.4	7.1	6.8	6.5	6.2
	50	0.559	20.8	18.4	16.6	15.1	13.8	12.8	11.9	11.1	10.4	9.8	9.2	8.7	8.3	7.9	7.5	7.2	6.9
	60	0.612	22.7	20.2	18.2	16.5	15.2	14.0	13.0	12.1	11.4	10.7	10.1	9.6	9.1	8.7	8.3	7.9	7.6

