

**TWIN JET 60 80°/ 110° 15" TIP SPACING**

ALL VALUES BASED ON WATER FOR OTHER LIQUIDS SEE USEFUL FORMULAS AND CONVERSIONS

mph		4.0	4.5	5.0	5.5	6.0	6.5	7.0	7.5	8.0	8.5	9.0	9.5	10.0	10.5	11.0	11.5	12.0	
psi gpm																			
TJ60-8002VS	30	0.217	21.4	19.1	17.1	15.6	14.3	13.2	12.2	11.4	10.7	10.1	9.5	9.0	8.6	8.2	7.8	7.5	7.1
TJ60-11002VS	40	0.250	24.8	22.0	19.8	18.0	16.5	15.2	14.1	13.2	12.4	11.6	11.0	10.4	9.9	9.4	9.0	8.6	8.3
100 MESH	50	0.280	27.7	24.6	22.1	20.1	18.4	17.0	15.8	14.8	13.8	13.0	12.3	11.7	11.1	10.5	10.1	9.6	9.2
YELLOW	60	0.306	30.3	26.9	24.2	22.0	20.2	18.7	17.3	16.2	15.2	14.3	13.5	12.8	12.1	11.5	11.0	10.5	10.1
TJ60-8003VS	30	0.260	25.7	22.9	20.6	18.7	17.1	15.8	14.7	13.7	12.9	12.1	11.4	10.8	10.3	9.8	9.4	8.9	8.6
TJ60-11003VS	40	0.300	29.7	26.4	23.8	21.6	19.8	18.3	17.0	15.8	14.9	14.0	13.2	12.5	11.9	11.3	10.8	10.3	9.9
100 MESH	50	0.335	33.2	29.5	26.6	24.1	22.1	20.4	19.0	17.7	16.6	15.6	14.8	14.0	13.3	12.6	12.1	11.5	11.1
BLUE	60	0.367	36.4	32.3	29.1	26.5	24.2	22.4	20.8	19.4	18.2	17.1	16.2	15.3	14.5	13.9	13.2	12.7	12.1
TJ60-8004VS	30	0.346	34.3	30.5	27.4	24.9	22.9	21.1	19.6	18.3	17.1	16.1	15.2	14.4	13.7	13.1	12.5	11.9	11.4
TJ60-11004VS	40	0.400	39.6	35.2	31.7	28.8	26.4	24.4	22.6	21.1	19.8	18.6	17.6	16.7	15.8	15.1	14.4	13.8	13.2
50 MESH	50	0.447	44.3	39.4	35.4	32.2	29.5	27.2	25.3	23.6	22.1	20.8	19.7	18.6	17.7	16.9	16.1	15.4	14.8
RED	60	0.490	48.5	43.1	38.8	35.3	32.3	29.8	27.7	25.9	24.2	22.8	21.6	20.4	19.4	18.5	17.6	16.9	16.2
TJ60-8006VS	30	0.520	51.4	45.7	41.2	37.4	34.3	31.7	29.4	27.4	25.7	24.2	22.9	21.7	20.6	19.6	18.7	17.9	17.1
TJ60-11006VS	40	0.600	59.4	52.8	47.5	43.2	39.6	36.6	33.9	31.7	29.7	28.0	26.4	25.0	23.8	22.6	21.6	20.7	19.8
50 MESH	50	0.671	66.4	59.0	53.1	48.3	44.3	40.9	37.9	35.4	33.2	31.3	29.5	28.0	26.6	25.3	24.1	23.1	22.1
GRAY	60	0.735	72.7	64.7	58.2	52.9	48.5	44.8	41.6	38.8	36.4	34.2	32.3	30.6	29.1	27.7	26.5	25.3	24.2
TJ60-8008VS	30	0.346	34.3	30.5	27.4	24.9	22.9	21.1	19.6	18.3	17.1	16.1	15.2	14.4	13.7	13.1	12.5	11.9	11.4
TJ60-11008VS	40	0.400	39.6	35.2	31.7	28.8	26.4	24.4	22.6	21.1	19.8	18.6	17.6	16.7	15.8	15.1	14.4	13.8	13.2
50 MESH	50	0.447	44.3	39.4	35.4	32.2	29.5	27.2	25.3	23.6	22.1	20.8	19.7	18.6	17.7	16.9	16.1	15.4	14.8
WHITE	60	0.490	48.5	43.1	38.8	35.3	32.3	29.8	27.7	25.9	24.2	22.8	21.6	20.4	19.4	18.5	17.6	16.9	16.2
TJ60-8010VS	30	0.520	51.4	45.7	41.2	37.4	34.3	31.7	29.4	27.4	25.7	24.2	22.9	21.7	20.6	19.6	18.7	17.9	17.1
TJ60-11010VS	40	0.600	59.4	52.8	47.5	43.2	39.6	36.6	33.9	31.7	29.7	28.0	26.4	25.0	23.8	22.6	21.6	20.7	19.8
50 MESH	50	0.671	66.4	59.0	53.1	48.3	44.3	40.9	37.9	35.4	33.2	31.3	29.5	28.0	26.6	25.3	24.1	23.1	22.1
LT.BLUE	60	0.735	72.7	64.7	58.2	52.9	48.5	44.8	41.6	38.8	36.4	34.2	32.3	30.6	29.1	27.7	26.5	25.3	24.2

**TWIN JET 60 80°/ 110° 15" TIP SPACING**

ALL VALUES BASED ON WATER FOR OTHER LIQUIDS SEE USEFUL FORMULAS AND CONVERSIONS

12.5	13.0	13.5	14.0	14.5	15.0	15.5	16.0	16.5	17.0	17.5	18.0	18.5	19.0	19.5	20.0	mph				
																	gpm	psi		
6.9	6.6	6.4	6.1	5.9	5.7	5.5	5.4	5.2	5.0	4.9	4.8	4.6	4.5	4.4	4.3	0.217	30	TJ60-8002VS		
7.9	7.6	7.3	7.1	6.8	6.6	6.4	6.2	6.0	5.8	5.7	5.5	5.4	5.2	5.1	5.0	0.250	40	TJ60-11002VS		
8.9	8.5	8.2	7.9	7.6	7.4	7.1	6.9	6.7	6.5	6.3	6.1	6.0	5.8	5.7	5.5	0.280	50	100 MESH		
9.7	9.3	9.0	8.7	8.4	8.1	7.8	7.6	7.3	7.1	6.9	6.7	6.6	6.4	6.2	6.1	0.306	60	YELLOW		
8.2	7.9	7.6	7.3	7.1	6.9	6.6	6.4	6.2	6.1	5.9	5.7	5.6	5.4	5.3	5.1	0.260	30	TJ60-8003VS		
9.5	9.1	8.8	8.5	8.2	7.9	7.7	7.4	7.2	7.0	6.8	6.6	6.4	6.3	6.1	5.9	0.300	40	TJ60-11003VS		
10.6	10.2	9.8	9.5	9.2	8.9	8.6	8.3	8.0	7.8	7.6	7.4	7.2	7.0	6.8	6.6	0.335	50	100 MESH		
11.6	11.2	10.8	10.4	10.0	9.7	9.4	9.1	8.8	8.6	8.3	8.1	7.9	7.7	7.5	7.3	0.367	60	BLUE		
11.0	10.6	10.2	9.8	9.5	9.1	8.9	8.6	8.3	8.1	7.8	7.6	7.4	7.2	7.0	6.9	0.346	30	TJ60-8004VS		
12.7	12.2	11.7	11.3	10.9	10.6	10.2	9.9	9.6	9.3	9.1	8.8	8.6	8.3	8.1	7.9	0.400	40	TJ60-11004VS		
14.2	13.6	13.1	12.6	12.2	11.8	11.4	11.1	10.7	10.4	10.1	9.8	9.6	9.3	9.1	8.9	0.447	50	50 MESH		
15.5	14.9	14.4	13.9	13.4	12.9	12.5	12.1	11.8	11.4	11.1	10.8	10.5	10.2	9.9	9.7	0.490	60	RED		
16.5	15.8	15.2	14.7	14.2	13.7	13.3	12.9	12.5	12.1	11.8	11.4	11.1	10.8	10.6	10.3	0.520	30	TJ60-8006VS		
19.0	18.3	17.6	17.0	16.4	15.8	15.3	14.9	14.4	14.0	13.6	13.2	12.8	12.5	12.2	11.9	0.600	40	TJ60-11006VS		
21.3	20.4	19.7	19.0	18.3	17.7	17.1	16.6	16.1	15.6	15.2	14.8	14.4	14.0	13.6	13.3	0.671	50	50 MESH		
23.3	22.4	21.6	20.8	20.1	19.4	18.8	18.2	17.6	17.1	16.6	16.2	15.7	15.3	14.9	14.5	0.735	60	GRAY		
11.0	10.6	10.2	9.8	9.5	9.1	8.9	8.6	8.3	8.1	7.8	7.6	7.4	7.2	7.0	6.9	0.346	30	TJ60-8008VS		
12.7	12.2	11.7	11.3	10.9	10.6	10.2	9.9	9.6	9.3	9.1	8.8	8.6	8.3	8.1	7.9	0.400	40	TJ60-11008VS		
14.2	13.6	13.1	12.6	12.2	11.8	11.4	11.1	10.7	10.4	10.1	9.8	9.6	9.3	9.1	8.9	0.447	50	50 MESH		
15.5	14.9	14.4	13.9	13.4	12.9	12.5	12.1	11.8	11.4	11.1	10.8	10.5	10.2	9.9	9.7	0.490	60	WHITE		
16.5	15.8	15.2	14.7	14.2	13.7	13.3	12.9	12.5	12.1	11.8	11.4	11.1	10.8	10.6	10.3	0.520	30	TJ60-8010VS		
19.0	18.3	17.6	17.0	16.4	15.8	15.3	14.9	14.4	14.0	13.6	13.2	12.8	12.5	12.2	11.9	0.600	40	TJ60-11010VS		
21.3	20.4	19.7	19.0	18.3	17.7	17.1	16.6	16.1	15.6	15.2	14.8	14.4	14.0	13.6	13.3	0.671	50	50 MESH		
23.3	22.4	21.6	20.8	20.1	19.4	18.8	18.2	17.6	17.1	16.6	16.2	15.7	15.3	14.9	14.5	0.735	60	LT.BLUE		