

TWIN JET 60 80°/ 110° 32" TIP SPACING

ALL VALUES BASED ON WATER FOR OTHER LIQUIDS SEE USEFUL FORMULAS AND CONVERSIONS

mph		4.0	4.5	5.0	5.5	6.0	6.5	7.0	7.5	8.0	8.5	9.0	9.5	10.0	10.5	11.0	11.5	12.0	
psi gpm																			
TJ60-8002VS	30	0.217	10.0	8.9	8.0	7.3	6.7	6.2	5.7	5.4	5.0	4.7	4.5	4.2	4.0	3.8	3.7	3.5	3.3
TJ60-11002VS	40	0.250	11.6	10.3	9.3	8.4	7.7	7.1	6.6	6.2	5.8	5.5	5.2	4.9	4.6	4.4	4.2	4.0	3.9
100 MESH	50	0.280	13.0	11.5	10.4	9.4	8.6	8.0	7.4	6.9	6.5	6.1	5.8	5.5	5.2	4.9	4.7	4.5	4.3
YELLOW	60	0.306	14.2	12.6	11.4	10.3	9.5	8.7	8.1	7.6	7.1	6.7	6.3	6.0	5.7	5.4	5.2	4.9	4.7
TJ60-8003VS	30	0.260	12.1	10.7	9.6	8.8	8.0	7.4	6.9	6.4	6.0	5.7	5.4	5.1	4.8	4.6	4.4	4.2	4.0
TJ60-11003VS	40	0.300	13.9	12.4	11.1	10.1	9.3	8.6	8.0	7.4	7.0	6.6	6.2	5.9	5.6	5.3	5.1	4.8	4.6
100 MESH	50	0.335	15.6	13.8	12.5	11.3	10.4	9.6	8.9	8.3	7.8	7.3	6.9	6.6	6.2	5.9	5.7	5.4	5.2
BLUE	60	0.367	17.1	15.2	13.6	12.4	11.4	10.5	9.7	9.1	8.5	8.0	7.6	7.2	6.8	6.5	6.2	5.9	5.7
TJ60-8004VS	30	0.346	16.1	14.3	12.9	11.7	10.7	9.9	9.2	8.6	8.0	7.6	7.1	6.8	6.4	6.1	5.8	5.6	5.4
TJ60-11004VS	40	0.400	18.6	16.5	14.9	13.5	12.4	11.4	10.6	9.9	9.3	8.7	8.3	7.8	7.4	7.1	6.8	6.5	6.2
50 MESH	50	0.447	20.8	18.4	16.6	15.1	13.8	12.8	11.9	11.1	10.4	9.8	9.2	8.7	8.3	7.9	7.5	7.2	6.9
RED	60	0.490	22.7	20.2	18.2	16.5	15.2	14.0	13.0	12.1	11.4	10.7	10.1	9.6	9.1	8.7	8.3	7.9	7.6
TJ60-8006VS	30	0.520	24.1	21.4	19.3	17.5	16.1	14.8	13.8	12.9	12.1	11.3	10.7	10.2	9.6	9.2	8.8	8.4	8.0
TJ60-11006VS	40	0.600	27.8	24.8	22.3	20.3	18.6	17.1	15.9	14.9	13.9	13.1	12.4	11.7	11.1	10.6	10.1	9.7	9.3
50 MESH	50	0.671	31.1	27.7	24.9	22.6	20.8	19.2	17.8	16.6	15.6	14.6	13.8	13.1	12.5	11.9	11.3	10.8	10.4
GRAY	60	0.735	34.1	30.3	27.3	24.8	22.7	21.0	19.5	18.2	17.1	16.0	15.2	14.4	13.6	13.0	12.4	11.9	11.4
TJ60-8008VS	30	0.346	16.1	14.3	12.9	11.7	10.7	9.9	9.2	8.6	8.0	7.6	7.1	6.8	6.4	6.1	5.8	5.6	5.4
TJ60-11008VS	40	0.400	18.6	16.5	14.9	13.5	12.4	11.4	10.6	9.9	9.3	8.7	8.3	7.8	7.4	7.1	6.8	6.5	6.2
50 MESH	50	0.447	20.8	18.4	16.6	15.1	13.8	12.8	11.9	11.1	10.4	9.8	9.2	8.7	8.3	7.9	7.5	7.2	6.9
WHITE	60	0.490	22.7	20.2	18.2	16.5	15.2	14.0	13.0	12.1	11.4	10.7	10.1	9.6	9.1	8.7	8.3	7.9	7.6
TJ60-8010VS	30	0.520	24.1	21.4	19.3	17.5	16.1	14.8	13.8	12.9	12.1	11.3	10.7	10.2	9.6	9.2	8.8	8.4	8.0
TJ60-11010VS	40	0.600	27.8	24.8	22.3	20.3	18.6	17.1	15.9	14.9	13.9	13.1	12.4	11.7	11.1	10.6	10.1	9.7	9.3
50 MESH	50	0.671	31.1	27.7	24.9	22.6	20.8	19.2	17.8	16.6	15.6	14.6	13.8	13.1	12.5	11.9	11.3	10.8	10.4
LT.BLUE	60	0.735	34.1	30.3	27.3	24.8	22.7	21.0	19.5	18.2	17.1	16.0	15.2	14.4	13.6	13.0	12.4	11.9	11.4

TWIN JET 60 80°/ 110° 32" TIP SPACING

ALL VALUES BASED ON WATER FOR OTHER LIQUIDS SEE USEFUL FORMULAS AND CONVERSIONS

12.5	13.0	13.5	14.0	14.5	15.0	15.5	16.0	16.5	17.0	17.5	18.0	18.5	19.0	19.5	20.0	mph					
																			gpm	psi	
3.2	3.1	3.0	2.9	2.8	2.7	2.6	2.5	2.4	2.4	2.3	2.2	2.2	2.1	2.1	2.0	0.217	30	TJ60-8002VS			
3.7	3.6	3.4	3.3	3.2	3.1	3.0	2.9	2.8	2.7	2.7	2.6	2.5	2.4	2.4	2.3	0.250	40	TJ60-11002VS			
4.2	4.0	3.8	3.7	3.6	3.5	3.3	3.2	3.1	3.1	3.0	2.9	2.8	2.7	2.7	2.6	0.280	50	100 MESH			
4.5	4.4	4.2	4.1	3.9	3.8	3.7	3.6	3.4	3.3	3.2	3.2	3.1	3.0	2.9	2.8	0.306	60	YELLOW			
3.9	3.7	3.6	3.4	3.3	3.2	3.1	3.0	2.9	2.8	2.8	2.7	2.6	2.5	2.5	2.4	0.260	30	TJ60-8003VS			
4.5	4.3	4.1	4.0	3.8	3.7	3.6	3.5	3.4	3.3	3.2	3.1	3.0	2.9	2.9	2.8	0.300	40	TJ60-11003VS			
5.0	4.8	4.6	4.4	4.3	4.2	4.0	3.9	3.8	3.7	3.6	3.5	3.4	3.3	3.2	3.1	0.335	50	100 MESH			
5.5	5.2	5.1	4.9	4.7	4.5	4.4	4.3	4.1	4.0	3.9	3.8	3.7	3.6	3.5	3.4	0.367	60	BLUE			
5.1	4.9	4.8	4.6	4.4	4.3	4.1	4.0	3.9	3.8	3.7	3.6	3.5	3.4	3.3	3.2	0.346	30	TJ60-8004VS			
5.9	5.7	5.5	5.3	5.1	5.0	4.8	4.6	4.5	4.4	4.2	4.1	4.0	3.9	3.8	3.7	0.400	40	TJ60-11004VS			
6.6	6.4	6.1	5.9	5.7	5.5	5.4	5.2	5.0	4.9	4.7	4.6	4.5	4.4	4.3	4.2	0.447	50	50 MESH			
7.3	7.0	6.7	6.5	6.3	6.1	5.9	5.7	5.5	5.3	5.2	5.1	4.9	4.8	4.7	4.5	0.490	60	RED			
7.7	7.4	7.1	6.9	6.7	6.4	6.2	6.0	5.8	5.7	5.5	5.4	5.2	5.1	4.9	4.8	0.520	30	TJ60-8006VS			
8.9	8.6	8.3	8.0	7.7	7.4	7.2	7.0	6.8	6.6	6.4	6.2	6.0	5.9	5.7	5.6	0.600	40	TJ60-11006VS			
10.0	9.6	9.2	8.9	8.6	8.3	8.0	7.8	7.5	7.3	7.1	6.9	6.7	6.6	6.4	6.2	0.671	50	50 MESH			
10.9	10.5	10.1	9.7	9.4	9.1	8.8	8.5	8.3	8.0	7.8	7.6	7.4	7.2	7.0	6.8	0.735	60	GRAY			
5.1	4.9	4.8	4.6	4.4	4.3	4.1	4.0	3.9	3.8	3.7	3.6	3.5	3.4	3.3	3.2	0.346	30	TJ60-8008VS			
5.9	5.7	5.5	5.3	5.1	5.0	4.8	4.6	4.5	4.4	4.2	4.1	4.0	3.9	3.8	3.7	0.400	40	TJ60-11008VS			
6.6	6.4	6.1	5.9	5.7	5.5	5.4	5.2	5.0	4.9	4.7	4.6	4.5	4.4	4.3	4.2	0.447	50	50 MESH			
7.3	7.0	6.7	6.5	6.3	6.1	5.9	5.7	5.5	5.3	5.2	5.1	4.9	4.8	4.7	4.5	0.490	60	WHITE			
7.7	7.4	7.1	6.9	6.7	6.4	6.2	6.0	5.8	5.7	5.5	5.4	5.2	5.1	4.9	4.8	0.520	30	TJ60-8010VS			
8.9	8.6	8.3	8.0	7.7	7.4	7.2	7.0	6.8	6.6	6.4	6.2	6.0	5.9	5.7	5.6	0.600	40	TJ60-11010VS			
10.0	9.6	9.2	8.9	8.6	8.3	8.0	7.8	7.5	7.3	7.1	6.9	6.7	6.6	6.4	6.2	0.671	50	50 MESH			
10.9	10.5	10.1	9.7	9.4	9.1	8.8	8.5	8.3	8.0	7.8	7.6	7.4	7.2	7.0	6.8	0.735	60	LT.BLUE			