

TWIN JET 60 80°/ 110° 36" TIP SPACING

ALL VALUES BASED ON WATER FOR OTHER LIQUIDS SEE USEFUL FORMULAS AND CONVERSIONS

mph		4.0	4.5	5.0	5.5	6.0	6.5	7.0	7.5	8.0	8.5	9.0	9.5	10.0	10.5	11.0	11.5	12.0	
psi gpm																			
TJ60-8002VS	30	0.217	8.9	7.9	7.1	6.5	6.0	5.5	5.1	4.8	4.5	4.2	4.0	3.8	3.6	3.4	3.2	3.1	3.0
TJ60-11002VS	40	0.250	10.3	9.2	8.3	7.5	6.9	6.3	5.9	5.5	5.2	4.9	4.6	4.3	4.1	3.9	3.8	3.6	3.4
100 MESH	50	0.280	11.5	10.2	9.2	8.4	7.7	7.1	6.6	6.1	5.8	5.4	5.1	4.9	4.6	4.4	4.2	4.0	3.8
YELLOW	60	0.306	12.6	11.2	10.1	9.2	8.4	7.8	7.2	6.7	6.3	5.9	5.6	5.3	5.1	4.8	4.6	4.4	4.2
TJ60-8003VS	30	0.260	10.7	9.5	8.6	7.8	7.1	6.6	6.1	5.7	5.4	5.0	4.8	4.5	4.3	4.1	3.9	3.7	3.6
TJ60-11003VS	40	0.300	12.4	11.0	9.9	9.0	8.3	7.6	7.1	6.6	6.2	5.8	5.5	5.2	5.0	4.7	4.5	4.3	4.1
100 MESH	50	0.335	13.8	12.3	11.1	10.1	9.2	8.5	7.9	7.4	6.9	6.5	6.1	5.8	5.5	5.3	5.0	4.8	4.6
BLUE	60	0.367	15.2	13.5	12.1	11.0	10.1	9.3	8.7	8.1	7.6	7.1	6.7	6.4	6.1	5.8	5.5	5.3	5.1
TJ60-8004VS	30	0.346	14.3	12.7	11.4	10.4	9.5	8.8	8.2	7.6	7.1	6.7	6.4	6.0	5.7	5.4	5.2	5.0	4.8
TJ60-11004VS	40	0.400	16.5	14.7	13.2	12.0	11.0	10.2	9.4	8.8	8.3	7.8	7.3	6.9	6.6	6.3	6.0	5.7	5.5
50 MESH	50	0.447	18.4	16.4	14.8	13.4	12.3	11.4	10.5	9.8	9.2	8.7	8.2	7.8	7.4	7.0	6.7	6.4	6.1
RED	60	0.490	20.2	18.0	16.2	14.7	13.5	12.4	11.5	10.8	10.1	9.5	9.0	8.5	8.1	7.7	7.3	7.0	6.7
TJ60-8006VS	30	0.520	21.4	19.1	17.1	15.6	14.3	13.2	12.2	11.4	10.7	10.1	9.5	9.0	8.6	8.2	7.8	7.5	7.1
TJ60-11006VS	40	0.600	24.8	22.0	19.8	18.0	16.5	15.2	14.1	13.2	12.4	11.6	11.0	10.4	9.9	9.4	9.0	8.6	8.3
50 MESH	50	0.671	27.7	24.6	22.1	20.1	18.4	17.0	15.8	14.8	13.8	13.0	12.3	11.7	11.1	10.5	10.1	9.6	9.2
GRAY	60	0.735	30.3	26.9	24.2	22.0	20.2	18.7	17.3	16.2	15.2	14.3	13.5	12.8	12.1	11.5	11.0	10.5	10.1
TJ60-8008VS	30	0.346	14.3	12.7	11.4	10.4	9.5	8.8	8.2	7.6	7.1	6.7	6.4	6.0	5.7	5.4	5.2	5.0	4.8
TJ60-11008VS	40	0.400	16.5	14.7	13.2	12.0	11.0	10.2	9.4	8.8	8.3	7.8	7.3	6.9	6.6	6.3	6.0	5.7	5.5
50 MESH	50	0.447	18.4	16.4	14.8	13.4	12.3	11.4	10.5	9.8	9.2	8.7	8.2	7.8	7.4	7.0	6.7	6.4	6.1
WHITE	60	0.490	20.2	18.0	16.2	14.7	13.5	12.4	11.5	10.8	10.1	9.5	9.0	8.5	8.1	7.7	7.3	7.0	6.7
TJ60-8010VS	30	0.520	21.4	19.1	17.1	15.6	14.3	13.2	12.2	11.4	10.7	10.1	9.5	9.0	8.6	8.2	7.8	7.5	7.1
TJ60-11010VS	40	0.600	24.8	22.0	19.8	18.0	16.5	15.2	14.1	13.2	12.4	11.6	11.0	10.4	9.9	9.4	9.0	8.6	8.3
50 MESH	50	0.671	27.7	24.6	22.1	20.1	18.4	17.0	15.8	14.8	13.8	13.0	12.3	11.7	11.1	10.5	10.1	9.6	9.2
LT.BLUE	60	0.735	30.3	26.9	24.2	22.0	20.2	18.7	17.3	16.2	15.2	14.3	13.5	12.8	12.1	11.5	11.0	10.5	10.1

TWIN JET 60 80°/ 110° 36" TIP SPACING

ALL VALUES BASED ON WATER FOR OTHER LIQUIDS SEE USEFUL FORMULAS AND CONVERSIONS

12.5	13.0	13.5	14.0	14.5	15.0	15.5	16.0	16.5	17.0	17.5	18.0	18.5	19.0	19.5	20.0	mph				
																	gpm	psi		
2.9	2.7	2.6	2.6	2.5	2.4	2.3	2.2	2.2	2.1	2.0	2.0	1.9	1.9	1.8	1.8	0.217	30	TJ60-8002VS		
3.3	3.2	3.1	2.9	2.8	2.8	2.7	2.6	2.5	2.4	2.4	2.3	2.2	2.2	2.1	2.1	0.250	40	TJ60-11002VS		
3.7	3.5	3.4	3.3	3.2	3.1	3.0	2.9	2.8	2.7	2.6	2.6	2.5	2.4	2.4	2.3	0.280	50	100 MESH		
4.0	3.9	3.7	3.6	3.5	3.4	3.3	3.2	3.1	3.0	2.9	2.8	2.7	2.7	2.6	2.5	0.306	60	YELLOW		
3.4	3.3	3.2	3.1	3.0	2.9	2.8	2.7	2.6	2.5	2.4	2.4	2.3	2.3	2.2	2.1	0.260	30	TJ60-8003VS		
4.0	3.8	3.7	3.5	3.4	3.3	3.2	3.1	3.0	2.9	2.8	2.8	2.7	2.6	2.5	2.5	0.300	40	TJ60-11003VS		
4.4	4.3	4.1	4.0	3.8	3.7	3.6	3.5	3.4	3.3	3.2	3.1	3.0	2.9	2.8	2.8	0.335	50	100 MESH		
4.8	4.7	4.5	4.3	4.2	4.0	3.9	3.8	3.7	3.6	3.5	3.4	3.3	3.2	3.1	3.0	0.367	60	BLUE		
4.6	4.4	4.2	4.1	3.9	3.8	3.7	3.6	3.5	3.4	3.3	3.2	3.1	3.0	2.9	2.9	0.346	30	TJ60-8004VS		
5.3	5.1	4.9	4.7	4.6	4.4	4.3	4.1	4.0	3.9	3.8	3.7	3.6	3.5	3.4	3.3	0.400	40	TJ60-11004VS		
5.9	5.7	5.5	5.3	5.1	4.9	4.8	4.6	4.5	4.3	4.2	4.1	4.0	3.9	3.8	3.7	0.447	50	50 MESH		
6.5	6.2	6.0	5.8	5.6	5.4	5.2	5.1	4.9	4.8	4.6	4.5	4.4	4.3	4.1	4.0	0.490	60	RED		
6.9	6.6	6.4	6.1	5.9	5.7	5.5	5.4	5.2	5.0	4.9	4.8	4.6	4.5	4.4	4.3	0.520	30	TJ60-8006VS		
7.9	7.6	7.3	7.1	6.8	6.6	6.4	6.2	6.0	5.8	5.7	5.5	5.4	5.2	5.1	5.0	0.600	40	TJ60-11006VS		
8.9	8.5	8.2	7.9	7.6	7.4	7.1	6.9	6.7	6.5	6.3	6.1	6.0	5.8	5.7	5.5	0.671	50	50 MESH		
9.7	9.3	9.0	8.7	8.4	8.1	7.8	7.6	7.3	7.1	6.9	6.7	6.6	6.4	6.2	6.1	0.735	60	GRAY		
4.6	4.4	4.2	4.1	3.9	3.8	3.7	3.6	3.5	3.4	3.3	3.2	3.1	3.0	2.9	2.9	0.346	30	TJ60-8008VS		
5.3	5.1	4.9	4.7	4.6	4.4	4.3	4.1	4.0	3.9	3.8	3.7	3.6	3.5	3.4	3.3	0.400	40	TJ60-11008VS		
5.9	5.7	5.5	5.3	5.1	4.9	4.8	4.6	4.5	4.3	4.2	4.1	4.0	3.9	3.8	3.7	0.447	50	50 MESH		
6.5	6.2	6.0	5.8	5.6	5.4	5.2	5.1	4.9	4.8	4.6	4.5	4.4	4.3	4.1	4.0	0.490	60	WHITE		
6.9	6.6	6.4	6.1	5.9	5.7	5.5	5.4	5.2	5.0	4.9	4.8	4.6	4.5	4.4	4.3	0.520	30	TJ60-8010VS		
7.9	7.6	7.3	7.1	6.8	6.6	6.4	6.2	6.0	5.8	5.7	5.5	5.4	5.2	5.1	5.0	0.600	40	TJ60-11010VS		
8.9	8.5	8.2	7.9	7.6	7.4	7.1	6.9	6.7	6.5	6.3	6.1	6.0	5.8	5.7	5.5	0.671	50	50 MESH		
9.7	9.3	9.0	8.7	8.4	8.1	7.8	7.6	7.3	7.1	6.9	6.7	6.6	6.4	6.2	6.1	0.735	60	LT.BLUE		