

TWIN JET 60 80°/ 110° 40" TIP SPACING

ALL VALUES BASED ON WATER FOR OTHER LIQUIDS SEE USEFUL FORMULAS AND CONVERSIONS

mph		4.0	4.5	5.0	5.5	6.0	6.5	7.0	7.5	8.0	8.5	9.0	9.5	10.0	10.5	11.0	11.5	12.0	
psi gpm																			
TJ60-8002VS	30	0.217	8.0	7.1	6.4	5.8	5.4	4.9	4.6	4.3	4.0	3.8	3.6	3.4	3.2	3.1	2.9	2.8	2.7
TJ60-11002VS	40	0.250	9.3	8.3	7.4	6.8	6.2	5.7	5.3	5.0	4.6	4.4	4.1	3.9	3.7	3.5	3.4	3.2	3.1
100 MESH	50	0.280	10.4	9.2	8.3	7.5	6.9	6.4	5.9	5.5	5.2	4.9	4.6	4.4	4.2	4.0	3.8	3.6	3.5
YELLOW	60	0.306	11.4	10.1	9.1	8.3	7.6	7.0	6.5	6.1	5.7	5.3	5.1	4.8	4.5	4.3	4.1	4.0	3.8
TJ60-8003VS	30	0.260	9.6	8.6	7.7	7.0	6.4	5.9	5.5	5.1	4.8	4.5	4.3	4.1	3.9	3.7	3.5	3.4	3.2
TJ60-11003VS	40	0.300	11.1	9.9	8.9	8.1	7.4	6.9	6.4	5.9	5.6	5.2	5.0	4.7	4.5	4.2	4.1	3.9	3.7
100 MESH	50	0.335	12.5	11.1	10.0	9.1	8.3	7.7	7.1	6.6	6.2	5.9	5.5	5.2	5.0	4.7	4.5	4.3	4.2
BLUE	60	0.367	13.6	12.1	10.9	9.9	9.1	8.4	7.8	7.3	6.8	6.4	6.1	5.7	5.5	5.2	5.0	4.7	4.5
TJ60-8004VS	30	0.346	12.9	11.4	10.3	9.4	8.6	7.9	7.3	6.9	6.4	6.1	5.7	5.4	5.1	4.9	4.7	4.5	4.3
TJ60-11004VS	40	0.400	14.9	13.2	11.9	10.8	9.9	9.1	8.5	7.9	7.4	7.0	6.6	6.3	5.9	5.7	5.4	5.2	5.0
50 MESH	50	0.447	16.6	14.8	13.3	12.1	11.1	10.2	9.5	8.9	8.3	7.8	7.4	7.0	6.6	6.3	6.0	5.8	5.5
RED	60	0.490	18.2	16.2	14.5	13.2	12.1	11.2	10.4	9.7	9.1	8.6	8.1	7.7	7.3	6.9	6.6	6.3	6.1
TJ60-8006VS	30	0.520	19.3	17.1	15.4	14.0	12.9	11.9	11.0	10.3	9.6	9.1	8.6	8.1	7.7	7.3	7.0	6.7	6.4
TJ60-11006VS	40	0.600	22.3	19.8	17.8	16.2	14.9	13.7	12.7	11.9	11.1	10.5	9.9	9.4	8.9	8.5	8.1	7.7	7.4
50 MESH	50	0.671	24.9	22.1	19.9	18.1	16.6	15.3	14.2	13.3	12.5	11.7	11.1	10.5	10.0	9.5	9.1	8.7	8.3
GRAY	60	0.735	27.3	24.2	21.8	19.8	18.2	16.8	15.6	14.5	13.6	12.8	12.1	11.5	10.9	10.4	9.9	9.5	9.1
TJ60-8008VS	30	0.346	12.9	11.4	10.3	9.4	8.6	7.9	7.3	6.9	6.4	6.1	5.7	5.4	5.1	4.9	4.7	4.5	4.3
TJ60-11008VS	40	0.400	14.9	13.2	11.9	10.8	9.9	9.1	8.5	7.9	7.4	7.0	6.6	6.3	5.9	5.7	5.4	5.2	5.0
50 MESH	50	0.447	16.6	14.8	13.3	12.1	11.1	10.2	9.5	8.9	8.3	7.8	7.4	7.0	6.6	6.3	6.0	5.8	5.5
WHITE	60	0.490	18.2	16.2	14.5	13.2	12.1	11.2	10.4	9.7	9.1	8.6	8.1	7.7	7.3	6.9	6.6	6.3	6.1
TJ60-8010VS	30	0.520	19.3	17.1	15.4	14.0	12.9	11.9	11.0	10.3	9.6	9.1	8.6	8.1	7.7	7.3	7.0	6.7	6.4
TJ60-11010VS	40	0.600	22.3	19.8	17.8	16.2	14.9	13.7	12.7	11.9	11.1	10.5	9.9	9.4	8.9	8.5	8.1	7.7	7.4
50 MESH	50	0.671	24.9	22.1	19.9	18.1	16.6	15.3	14.2	13.3	12.5	11.7	11.1	10.5	10.0	9.5	9.1	8.7	8.3
LT.BLUE	60	0.735	27.3	24.2	21.8	19.8	18.2	16.8	15.6	14.5	13.6	12.8	12.1	11.5	10.9	10.4	9.9	9.5	9.1

TWIN JET 60 80°/ 110° 40" TIP SPACING

ALL VALUES BASED ON WATER FOR OTHER LIQUIDS SEE USEFUL FORMULAS AND CONVERSIONS

12.5	13.0	13.5	14.0	14.5	15.0	15.5	16.0	16.5	17.0	17.5	18.0	18.5	19.0	19.5	20.0	mph				
																	gpm	psi		
2.6	2.5	2.4	2.3	2.2	2.1	2.1	2.0	1.9	1.9	1.8	1.8	1.7	1.7	1.6	1.6	0.217	30	TJ60-8002VS		
3.0	2.9	2.8	2.7	2.6	2.5	2.4	2.3	2.3	2.2	2.1	2.1	2.0	2.0	1.9	1.9	0.250	40	TJ60-11002VS		
3.3	3.2	3.1	3.0	2.9	2.8	2.7	2.6	2.5	2.4	2.4	2.3	2.2	2.2	2.1	2.1	0.280	50	100 MESH		
3.6	3.5	3.4	3.2	3.1	3.0	2.9	2.8	2.8	2.7	2.6	2.5	2.5	2.4	2.3	2.3	0.306	60	YELLOW		
3.1	3.0	2.9	2.8	2.7	2.6	2.5	2.4	2.3	2.3	2.2	2.1	2.1	2.0	2.0	1.9	0.260	30	TJ60-8003VS		
3.6	3.4	3.3	3.2	3.1	3.0	2.9	2.8	2.7	2.6	2.5	2.5	2.4	2.3	2.3	2.2	0.300	40	TJ60-11003VS		
4.0	3.8	3.7	3.6	3.4	3.3	3.2	3.1	3.0	2.9	2.8	2.8	2.7	2.6	2.6	2.5	0.335	50	100 MESH		
4.4	4.2	4.0	3.9	3.8	3.6	3.5	3.4	3.3	3.2	3.1	3.0	2.9	2.9	2.8	2.7	0.367	60	BLUE		
4.1	4.0	3.8	3.7	3.5	3.4	3.3	3.2	3.1	3.0	2.9	2.9	2.8	2.7	2.6	2.6	0.346	30	TJ60-8004VS		
4.8	4.6	4.4	4.2	4.1	4.0	3.8	3.7	3.6	3.5	3.4	3.3	3.2	3.1	3.0	3.0	0.400	40	TJ60-11004VS		
5.3	5.1	4.9	4.7	4.6	4.4	4.3	4.2	4.0	3.9	3.8	3.7	3.6	3.5	3.4	3.3	0.447	50	50 MESH		
5.8	5.6	5.4	5.2	5.0	4.8	4.7	4.5	4.4	4.3	4.2	4.0	3.9	3.8	3.7	3.6	0.490	60	RED		
6.2	5.9	5.7	5.5	5.3	5.1	5.0	4.8	4.7	4.5	4.4	4.3	4.2	4.1	4.0	3.9	0.520	30	TJ60-8006VS		
7.1	6.9	6.6	6.4	6.1	5.9	5.7	5.6	5.4	5.2	5.1	5.0	4.8	4.7	4.6	4.5	0.600	40	TJ60-11006VS		
8.0	7.7	7.4	7.1	6.9	6.6	6.4	6.2	6.0	5.9	5.7	5.5	5.4	5.2	5.1	5.0	0.671	50	50 MESH		
8.7	8.4	8.1	7.8	7.5	7.3	7.0	6.8	6.6	6.4	6.2	6.1	5.9	5.7	5.6	5.5	0.735	60	GRAY		
4.1	4.0	3.8	3.7	3.5	3.4	3.3	3.2	3.1	3.0	2.9	2.9	2.8	2.7	2.6	2.6	0.346	30	TJ60-8008VS		
4.8	4.6	4.4	4.2	4.1	4.0	3.8	3.7	3.6	3.5	3.4	3.3	3.2	3.1	3.0	3.0	0.400	40	TJ60-11008VS		
5.3	5.1	4.9	4.7	4.6	4.4	4.3	4.2	4.0	3.9	3.8	3.7	3.6	3.5	3.4	3.3	0.447	50	50 MESH		
5.8	5.6	5.4	5.2	5.0	4.8	4.7	4.5	4.4	4.3	4.2	4.0	3.9	3.8	3.7	3.6	0.490	60	WHITE		
6.2	5.9	5.7	5.5	5.3	5.1	5.0	4.8	4.7	4.5	4.4	4.3	4.2	4.1	4.0	3.9	0.520	30	TJ60-8010VS		
7.1	6.9	6.6	6.4	6.1	5.9	5.7	5.6	5.4	5.2	5.1	5.0	4.8	4.7	4.6	4.5	0.600	40	TJ60-11010VS		
8.0	7.7	7.4	7.1	6.9	6.6	6.4	6.2	6.0	5.9	5.7	5.5	5.4	5.2	5.1	5.0	0.671	50	50 MESH		
8.7	8.4	8.1	7.8	7.5	7.3	7.0	6.8	6.6	6.4	6.2	6.1	5.9	5.7	5.6	5.5	0.735	60	LT.BLUE		