

TWIN JET 60 80°/ 40° EVEN 36" TIP SPACING

ALL VALUES BASED ON WATER FOR OTHER LIQUIDS SEE USEFUL FORMULAS AND CONVERSIONS

mph		4.0	4.5	5.0	5.5	6.0	6.5	7.0	7.5	8.0	8.5	9.0	9.5	10.0	10.5	11.0	11.5	12.0	
psi gpm																			
TJ60-8002EVS	30	0.217	8.9	7.9	7.1	6.5	6.0	5.5	5.1	4.8	4.5	4.2	4.0	3.8	3.6	3.4	3.2	3.1	3.0
TJ60-4002EVS	40	0.250	10.3	9.2	8.3	7.5	6.9	6.3	5.9	5.5	5.2	4.9	4.6	4.3	4.1	3.9	3.8	3.6	3.4
100 MESH	50	0.280	11.5	10.2	9.2	8.4	7.7	7.1	6.6	6.1	5.8	5.4	5.1	4.9	4.6	4.4	4.2	4.0	3.8
YELLOW	60	0.306	12.6	11.2	10.1	9.2	8.4	7.8	7.2	6.7	6.3	5.9	5.6	5.3	5.1	4.8	4.6	4.4	4.2
TJ60-8003EVS	30	0.260	10.7	9.5	8.6	7.8	7.1	6.6	6.1	5.7	5.4	5.0	4.8	4.5	4.3	4.1	3.9	3.7	3.6
TJ60-4003EVS	40	0.300	12.4	11.0	9.9	9.0	8.3	7.6	7.1	6.6	6.2	5.8	5.5	5.2	5.0	4.7	4.5	4.3	4.1
100 MESH	50	0.335	13.8	12.3	11.1	10.1	9.2	8.5	7.9	7.4	6.9	6.5	6.1	5.8	5.5	5.3	5.0	4.8	4.6
BLUE	60	0.367	15.2	13.5	12.1	11.0	10.1	9.3	8.7	8.1	7.6	7.1	6.7	6.4	6.1	5.8	5.5	5.3	5.1
TJ60-8004EVS	30	0.346	14.3	12.7	11.4	10.4	9.5	8.8	8.2	7.6	7.1	6.7	6.4	6.0	5.7	5.4	5.2	5.0	4.8
TJ60-4004EVS	40	0.400	16.5	14.7	13.2	12.0	11.0	10.2	9.4	8.8	8.3	7.8	7.3	6.9	6.6	6.3	6.0	5.7	5.5
50 MESH	50	0.447	18.4	16.4	14.8	13.4	12.3	11.4	10.5	9.8	9.2	8.7	8.2	7.8	7.4	7.0	6.7	6.4	6.1
RED	60	0.490	20.2	18.0	16.2	14.7	13.5	12.4	11.5	10.8	10.1	9.5	9.0	8.5	8.1	7.7	7.3	7.0	6.7
TJ60-8006EVS	30	0.520	21.4	19.1	17.1	15.6	14.3	13.2	12.2	11.4	10.7	10.1	9.5	9.0	8.6	8.2	7.8	7.5	7.1
50 MESH	40	0.600	24.8	22.0	19.8	18.0	16.5	15.2	14.1	13.2	12.4	11.6	11.0	10.4	9.9	9.4	9.0	8.6	8.3
	50	0.671	27.7	24.6	22.1	20.1	18.4	17.0	15.8	14.8	13.8	13.0	12.3	11.7	11.1	10.5	10.1	9.6	9.2
GRAY	60	0.735	30.3	26.9	24.2	22.0	20.2	18.7	17.3	16.2	15.2	14.3	13.5	12.8	12.1	11.5	11.0	10.5	10.1

