

TWIN JET 60 80°/ 40° EVEN 38" TIP SPACING

ALL VALUES BASED ON WATER FOR OTHER LIQUIDS SEE USEFUL FORMULAS AND CONVERSIONS

mph		4.0	4.5	5.0	5.5	6.0	6.5	7.0	7.5	8.0	8.5	9.0	9.5	10.0	10.5	11.0	11.5	12.0	
psi gpm																			
TJ60-8002EVS	30	0.217	8.5	7.5	6.8	6.2	5.6	5.2	4.8	4.5	4.2	4.0	3.8	3.6	3.4	3.2	3.1	2.9	2.8
TJ60-4002EVS	40	0.250	9.8	8.7	7.8	7.1	6.5	6.0	5.6	5.2	4.9	4.6	4.3	4.1	3.9	3.7	3.6	3.4	3.3
100 MESH	50	0.280	10.9	9.7	8.7	7.9	7.3	6.7	6.2	5.8	5.5	5.1	4.9	4.6	4.4	4.2	4.0	3.8	3.6
YELLOW	60	0.306	12.0	10.6	9.6	8.7	8.0	7.4	6.8	6.4	6.0	5.6	5.3	5.0	4.8	4.6	4.4	4.2	4.0
TJ60-8003EVS	30	0.260	10.2	9.0	8.1	7.4	6.8	6.2	5.8	5.4	5.1	4.8	4.5	4.3	4.1	3.9	3.7	3.5	3.4
TJ60-4003EVS	40	0.300	11.7	10.4	9.4	8.5	7.8	7.2	6.7	6.3	5.9	5.5	5.2	4.9	4.7	4.5	4.3	4.1	3.9
100 MESH	50	0.335	13.1	11.7	10.5	9.5	8.7	8.1	7.5	7.0	6.6	6.2	5.8	5.5	5.2	5.0	4.8	4.6	4.4
BLUE	60	0.367	14.4	12.8	11.5	10.4	9.6	8.8	8.2	7.7	7.2	6.8	6.4	6.0	5.7	5.5	5.2	5.0	4.8
TJ60-8004EVS	30	0.346	13.5	12.0	10.8	9.8	9.0	8.3	7.7	7.2	6.8	6.4	6.0	5.7	5.4	5.2	4.9	4.7	4.5
TJ60-4004EVS	40	0.400	15.6	13.9	12.5	11.4	10.4	9.6	8.9	8.3	7.8	7.4	6.9	6.6	6.3	6.0	5.7	5.4	5.2
50 MESH	50	0.447	17.5	15.5	14.0	12.7	11.7	10.8	10.0	9.3	8.7	8.2	7.8	7.4	7.0	6.7	6.4	6.1	5.8
RED	60	0.490	19.1	17.0	15.3	13.9	12.8	11.8	10.9	10.2	9.6	9.0	8.5	8.1	7.7	7.3	7.0	6.7	6.4
TJ60-8006EVS	30	0.520	20.3	18.0	16.2	14.8	13.5	12.5	11.6	10.8	10.2	9.6	9.0	8.5	8.1	7.7	7.4	7.1	6.8
50 MESH	40	0.600	23.4	20.8	18.8	17.1	15.6	14.4	13.4	12.5	11.7	11.0	10.4	9.9	9.4	8.9	8.5	8.2	7.8
	50	0.671	26.2	23.3	21.0	19.1	17.5	16.1	15.0	14.0	13.1	12.3	11.7	11.0	10.5	10.0	9.5	9.1	8.7
GRAY	60	0.735	28.7	25.5	23.0	20.9	19.1	17.7	16.4	15.3	14.4	13.5	12.8	12.1	11.5	10.9	10.4	10.0	9.6

