

UB 85° 36" TIP SPACING

ALL VALUES BASED ON WATER FOR OTHER LIQUIDS SEE USEFUL FORMULAS AND CONVERSIONS

mph		4.0	4.5	5.0	5.5	6.0	6.5	7.0	7.5	8.0	8.5	9.0	9.5	10.0	10.5	11.0	11.5	12.0	
psi gpm																			
D25143-UB-8501	20	0.071	2.9	2.6	2.3	2.1	1.9	1.8	1.7	1.6	1.5	1.4	1.3	1.2	1.2	1.1	1.1	1.0	1.0
	30	0.087	3.6	3.2	2.9	2.6	2.4	2.2	2.0	1.9	1.8	1.7	1.6	1.5	1.4	1.4	1.3	1.2	1.2
	40	0.100	4.1	3.7	3.3	3.0	2.8	2.5	2.4	2.2	2.1	1.9	1.8	1.7	1.7	1.6	1.5	1.4	1.4
	50	0.112	4.6	4.1	3.7	3.4	3.1	2.8	2.6	2.5	2.3	2.2	2.0	1.9	1.8	1.8	1.7	1.6	1.5
100 MESH	60	0.122	5.1	4.5	4.0	3.7	3.4	3.1	2.9	2.7	2.5	2.4	2.2	2.1	2.0	1.9	1.8	1.8	1.7
D25143-UB-85015	20	0.106	4.4	3.9	3.5	3.2	2.9	2.7	2.5	2.3	2.2	2.1	1.9	1.8	1.8	1.7	1.6	1.5	1.5
	30	0.130	5.4	4.8	4.3	3.9	3.6	3.3	3.1	2.9	2.7	2.5	2.4	2.3	2.1	2.0	1.9	1.9	1.8
	40	0.150	6.2	5.5	5.0	4.5	4.1	3.8	3.5	3.3	3.1	2.9	2.8	2.6	2.5	2.4	2.3	2.2	2.1
	50	0.168	6.9	6.1	5.5	5.0	4.6	4.3	4.0	3.7	3.5	3.3	3.1	2.9	2.8	2.6	2.5	2.4	2.3
100 MESH	60	0.184	7.6	6.7	6.1	5.5	5.1	4.7	4.3	4.0	3.8	3.6	3.4	3.2	3.0	2.9	2.8	2.6	2.5
D25143-UB-8502	20	0.141	5.8	5.2	4.7	4.2	3.9	3.6	3.3	3.1	2.9	2.7	2.6	2.5	2.3	2.2	2.1	2.0	1.9
	30	0.173	7.1	6.4	5.7	5.2	4.8	4.4	4.1	3.8	3.6	3.4	3.2	3.0	2.9	2.7	2.6	2.5	2.4
	40	0.200	8.3	7.3	6.6	6.0	5.5	5.1	4.7	4.4	4.1	3.9	3.7	3.5	3.3	3.1	3.0	2.9	2.8
	50	0.224	9.2	8.2	7.4	6.7	6.1	5.7	5.3	4.9	4.6	4.3	4.1	3.9	3.7	3.5	3.4	3.2	3.1
50 MESH	60	0.245	10.1	9.0	8.1	7.3	6.7	6.2	5.8	5.4	5.1	4.8	4.5	4.3	4.0	3.8	3.7	3.5	3.4
D25143-UB-8503	20	0.212	8.8	7.8	7.0	6.4	5.8	5.4	5.0	4.7	4.4	4.1	3.9	3.7	3.5	3.3	3.2	3.0	2.9
	30	0.260	10.7	9.5	8.6	7.8	7.1	6.6	6.1	5.7	5.4	5.0	4.8	4.5	4.3	4.1	3.9	3.7	3.6
	40	0.300	12.4	11.0	9.9	9.0	8.3	7.6	7.1	6.6	6.2	5.8	5.5	5.2	5.0	4.7	4.5	4.3	4.1
	50	0.335	13.8	12.3	11.1	10.1	9.2	8.5	7.9	7.4	6.9	6.5	6.1	5.8	5.5	5.3	5.0	4.8	4.6
50 MESH	60	0.367	15.2	13.5	12.1	11.0	10.1	9.3	8.7	8.1	7.6	7.1	6.7	6.4	6.1	5.8	5.5	5.3	5.1
D25143-UB-8504	20	0.283	11.7	10.4	9.3	8.5	7.8	7.2	6.7	6.2	5.8	5.5	5.2	4.9	4.7	4.4	4.2	4.1	3.9
	30	0.346	14.3	12.7	11.4	10.4	9.5	8.8	8.2	7.6	7.1	6.7	6.4	6.0	5.7	5.4	5.2	5.0	4.8
	40	0.400	16.5	14.7	13.2	12.0	11.0	10.2	9.4	8.8	8.3	7.8	7.3	6.9	6.6	6.3	6.0	5.7	5.5
	50	0.447	18.4	16.4	14.8	13.4	12.3	11.4	10.5	9.8	9.2	8.7	8.2	7.8	7.4	7.0	6.7	6.4	6.1
50 MESH	60	0.490	20.2	18.0	16.2	14.7	13.5	12.4	11.5	10.8	10.1	9.5	9.0	8.5	8.1	7.7	7.3	7.0	6.7

UB 85° 36" TIP SPACING

ALL VALUES BASED ON WATER FOR OTHER LIQUIDS SEE USEFUL FORMULAS AND CONVERSIONS

12.5	13.0	13.5	14.0	14.5	15.0	15.5	16.0	16.5	17.0	17.5	18.0	18.5	19.0	19.5	20.0	mph		
																	gpm	psi
0.9	0.9	0.9	0.8	0.8	0.8	0.8	0.7	0.7	0.7	0.7	0.6	0.6	0.6	0.6	0.6	0.071	20	
1.1	1.1	1.1	1.0	1.0	1.0	0.9	0.9	0.9	0.8	0.8	0.8	0.8	0.8	0.7	0.7	0.087	30	
1.3	1.3	1.2	1.2	1.1	1.1	1.1	1.0	1.0	1.0	0.9	0.9	0.9	0.9	0.8	0.8	0.100	40	
1.5	1.4	1.4	1.3	1.3	1.2	1.2	1.2	1.1	1.1	1.1	1.0	1.0	1.0	0.9	0.9	0.112	50	
1.6	1.6	1.5	1.4	1.4	1.3	1.3	1.3	1.2	1.2	1.2	1.1	1.1	1.1	1.0	1.0	0.122	60	
100 MESH																		
1.4	1.3	1.3	1.3	1.2	1.2	1.1	1.1	1.1	1.0	1.0	1.0	0.9	0.9	0.9	0.9	0.106	20	
1.7	1.6	1.6	1.5	1.5	1.4	1.4	1.3	1.3	1.3	1.2	1.2	1.2	1.1	1.1	1.1	0.130	30	
2.0	1.9	1.8	1.8	1.7	1.7	1.6	1.5	1.5	1.5	1.4	1.4	1.3	1.3	1.3	1.2	0.150	40	
2.2	2.1	2.0	2.0	1.9	1.8	1.8	1.7	1.7	1.6	1.6	1.5	1.5	1.5	1.4	1.4	0.168	50	
2.4	2.3	2.2	2.2	2.1	2.0	2.0	1.9	1.8	1.8	1.7	1.7	1.6	1.6	1.6	1.5	0.184	60	
100 MESH																		
1.9	1.8	1.7	1.7	1.6	1.6	1.5	1.5	1.4	1.4	1.3	1.3	1.3	1.2	1.2	1.2	0.141	20	
2.3	2.2	2.1	2.0	2.0	1.9	1.8	1.8	1.7	1.7	1.6	1.6	1.5	1.5	1.5	1.4	0.173	30	
2.6	2.5	2.4	2.4	2.3	2.2	2.1	2.1	2.0	1.9	1.9	1.8	1.8	1.7	1.7	1.7	0.200	40	
3.0	2.8	2.7	2.6	2.5	2.5	2.4	2.3	2.2	2.2	2.1	2.0	2.0	1.9	1.9	1.8	0.224	50	
3.2	3.1	3.0	2.9	2.8	2.7	2.6	2.5	2.4	2.4	2.3	2.2	2.2	2.1	2.1	2.0	0.245	60	
50 MESH																		
2.8	2.7	2.6	2.5	2.4	2.3	2.3	2.2	2.1	2.1	2.0	1.9	1.9	1.8	1.8	1.8	0.212	20	
3.4	3.3	3.2	3.1	3.0	2.9	2.8	2.7	2.6	2.5	2.4	2.4	2.3	2.3	2.2	2.1	0.260	30	
4.0	3.8	3.7	3.5	3.4	3.3	3.2	3.1	3.0	2.9	2.8	2.8	2.7	2.6	2.5	2.5	0.300	40	
4.4	4.3	4.1	4.0	3.8	3.7	3.6	3.5	3.4	3.3	3.2	3.1	3.0	2.9	2.8	2.8	0.335	50	
4.8	4.7	4.5	4.3	4.2	4.0	3.9	3.8	3.7	3.6	3.5	3.4	3.3	3.2	3.1	3.0	0.367	60	
50 MESH																		
3.7	3.6	3.5	3.3	3.2	3.1	3.0	2.9	2.8	2.7	2.7	2.6	2.5	2.5	2.4	2.3	0.283	20	
4.6	4.4	4.2	4.1	3.9	3.8	3.7	3.6	3.5	3.4	3.3	3.2	3.1	3.0	2.9	2.9	0.346	30	
5.3	5.1	4.9	4.7	4.6	4.4	4.3	4.1	4.0	3.9	3.8	3.7	3.6	3.5	3.4	3.3	0.400	40	
5.9	5.7	5.5	5.3	5.1	4.9	4.8	4.6	4.5	4.3	4.2	4.1	4.0	3.9	3.8	3.7	0.447	50	
6.5	6.2	6.0	5.8	5.6	5.4	5.2	5.1	4.9	4.8	4.6	4.5	4.4	4.3	4.1	4.0	0.490	60	
50 MESH																		