

**XR 80° / 110° 15" TIP SPACING**

ALL VALUES BASED ON WATER FOR OTHER LIQUIDS SEE USEFUL FORMULAS AND CONVERSIONS

mph		4.0	4.5	5.0	5.5	6.0	6.5	7.0	7.5	8.0	8.5	9.0	9.5	10.0	10.5	11.0	11.5	12.0	
psi gpm																			
XR8001VS XR1101VS  100 MESH ORANGE	15	0.061	6.1	5.4	4.8	4.4	4.0	3.7	3.5	3.2	3.0	2.9	2.7	2.6	2.4	2.3	2.2	2.1	2.0
	20	0.071	7.0	6.2	5.6	5.1	4.7	4.3	4.0	3.7	3.5	3.3	3.1	2.9	2.8	2.7	2.5	2.4	2.3
	30	0.087	8.6	7.6	6.9	6.2	5.7	5.3	4.9	4.6	4.3	4.0	3.8	3.6	3.4	3.3	3.1	3.0	2.9
	40	0.100	9.9	8.8	7.9	7.2	6.6	6.1	5.7	5.3	5.0	4.7	4.4	4.2	4.0	3.8	3.6	3.4	3.3
	50	0.112	11.1	9.8	8.9	8.0	7.4	6.8	6.3	5.9	5.5	5.2	4.9	4.7	4.4	4.2	4.0	3.8	3.7
60	0.122	12.1	10.8	9.7	8.8	8.1	7.5	6.9	6.5	6.1	5.7	5.4	5.1	4.8	4.6	4.4	4.2	4.0	
XR80015VS XR11015VS  100 MESH GREEN	15	0.092	9.1	8.1	7.3	6.6	6.1	5.6	5.2	4.8	4.5	4.3	4.0	3.8	3.6	3.5	3.3	3.2	3.0
	20	0.106	10.5	9.3	8.4	7.6	7.0	6.5	6.0	5.6	5.3	4.9	4.7	4.4	4.2	4.0	3.8	3.7	3.5
	30	0.130	12.9	11.4	10.3	9.4	8.6	7.9	7.3	6.9	6.4	6.1	5.7	5.4	5.1	4.9	4.7	4.5	4.3
	40	0.150	14.9	13.2	11.9	10.8	9.9	9.1	8.5	7.9	7.4	7.0	6.6	6.3	5.9	5.7	5.4	5.2	5.0
	50	0.168	16.6	14.8	13.3	12.1	11.1	10.2	9.5	8.9	8.3	7.8	7.4	7.0	6.6	6.3	6.0	5.8	5.5
60	0.184	18.2	16.2	14.5	13.2	12.1	11.2	10.4	9.7	9.1	8.6	8.1	7.7	7.3	6.9	6.6	6.3	6.1	
XR8002VS XR1102VS  50 MESH YELLOW	15	0.122	12.1	10.8	9.7	8.8	8.1	7.5	6.9	6.5	6.1	5.7	5.4	5.1	4.8	4.6	4.4	4.2	4.0
	20	0.141	14.0	12.4	11.2	10.2	9.3	8.6	8.0	7.5	7.0	6.6	6.2	5.9	5.6	5.3	5.1	4.9	4.7
	30	0.173	17.1	15.2	13.7	12.5	11.4	10.6	9.8	9.1	8.6	8.1	7.6	7.2	6.9	6.5	6.2	6.0	5.7
	40	0.200	19.8	17.6	15.8	14.4	13.2	12.2	11.3	10.6	9.9	9.3	8.8	8.3	7.9	7.5	7.2	6.9	6.6
	50	0.224	22.1	19.7	17.7	16.1	14.8	13.6	12.6	11.8	11.1	10.4	9.8	9.3	8.9	8.4	8.0	7.7	7.4
60	0.245	24.2	21.6	19.4	17.6	16.2	14.9	13.9	12.9	12.1	11.4	10.8	10.2	9.7	9.2	8.8	8.4	8.1	
XR80025VS XR11025VS  50 MESH PURPLE	15	0.150	14.9	13.2	11.9	10.8	9.9	9.1	8.5	7.9	7.4	7.0	6.6	6.3	5.9	5.7	5.4	5.2	5.0
	20	0.180	17.8	15.8	14.3	13.0	11.9	11.0	10.2	9.5	8.9	8.4	7.9	7.5	7.1	6.8	6.5	6.2	5.9
	30	0.220	21.8	19.4	17.4	15.8	14.5	13.4	12.4	11.6	10.9	10.2	9.7	9.2	8.7	8.3	7.9	7.6	7.3
	40	0.250	24.8	22.0	19.8	18.0	16.5	15.2	14.1	13.2	12.4	11.6	11.0	10.4	9.9	9.4	9.0	8.6	8.3
	50	0.280	27.7	24.6	22.2	20.2	18.5	17.1	15.8	14.8	13.9	13.0	12.3	11.7	11.1	10.6	10.1	9.6	9.2
60	0.310	30.7	27.3	24.6	22.3	20.5	18.9	17.5	16.4	15.3	14.4	13.6	12.9	12.3	11.7	11.2	10.7	10.2	
XR8003VS XR1103VS  50 MESH BLUE	15	0.184	18.2	16.2	14.5	13.2	12.1	11.2	10.4	9.7	9.1	8.6	8.1	7.7	7.3	6.9	6.6	6.3	6.1
	20	0.212	21.0	18.7	16.8	15.3	14.0	12.9	12.0	11.2	10.5	9.9	9.3	8.8	8.4	8.0	7.6	7.3	7.0
	30	0.260	25.7	22.9	20.6	18.7	17.1	15.8	14.7	13.7	12.9	12.1	11.4	10.8	10.3	9.8	9.4	8.9	8.6
	40	0.300	29.7	26.4	23.8	21.6	19.8	18.3	17.0	15.8	14.9	14.0	13.2	12.5	11.9	11.3	10.8	10.3	9.9
	50	0.335	33.2	29.5	26.6	24.1	22.1	20.4	19.0	17.7	16.6	15.6	14.8	14.0	13.3	12.6	12.1	11.5	11.1
60	0.367	36.4	32.3	29.1	26.5	24.2	22.4	20.8	19.4	18.2	17.1	16.2	15.3	14.5	13.9	13.2	12.7	12.1	

**XR 80° / 110° 15" TIP SPACING**

ALL VALUES BASED ON WATER FOR OTHER LIQUIDS SEE USEFUL FORMULAS AND CONVERSIONS

12.5	13.0	13.5	14.0	14.5	15.0	15.5	16.0	16.5	17.0	17.5	18.0	18.5	19.0	19.5	20.0	mph		
																	gpm	psi
1.9	1.9	1.8	1.7	1.7	1.6	1.6	1.5	1.5	1.4	1.4	1.3	1.3	1.3	1.2	1.2	0.061	15	XR8001VS XR1101VS
2.2	2.2	2.1	2.0	1.9	1.9	1.8	1.8	1.7	1.6	1.6	1.6	1.5	1.5	1.4	1.4	0.071	20	
2.7	2.6	2.5	2.4	2.4	2.3	2.2	2.1	2.1	2.0	2.0	1.9	1.9	1.8	1.8	1.7	0.087	30	100 MESH ORANGE
3.2	3.0	2.9	2.8	2.7	2.6	2.6	2.5	2.4	2.3	2.3	2.2	2.1	2.1	2.0	2.0	0.100	40	
3.5	3.4	3.3	3.2	3.1	3.0	2.9	2.8	2.7	2.6	2.5	2.5	2.4	2.3	2.3	2.2	0.112	50	
3.9	3.7	3.6	3.5	3.3	3.2	3.1	3.0	2.9	2.9	2.8	2.7	2.6	2.6	2.5	2.4	0.122	60	
2.9	2.8	2.7	2.6	2.5	2.4	2.3	2.3	2.2	2.1	2.1	2.0	2.0	1.9	1.9	1.8	0.092	15	XR80015VS XR11015VS
3.4	3.2	3.1	3.0	2.9	2.8	2.7	2.6	2.5	2.5	2.4	2.3	2.3	2.2	2.2	2.1	0.106	20	
4.1	4.0	3.8	3.7	3.5	3.4	3.3	3.2	3.1	3.0	2.9	2.9	2.8	2.7	2.6	2.6	0.130	30	100 MESH GREEN
4.8	4.6	4.4	4.2	4.1	4.0	3.8	3.7	3.6	3.5	3.4	3.3	3.2	3.1	3.0	3.0	0.150	40	
5.3	5.1	4.9	4.7	4.6	4.4	4.3	4.2	4.0	3.9	3.8	3.7	3.6	3.5	3.4	3.3	0.168	50	
5.8	5.6	5.4	5.2	5.0	4.8	4.7	4.5	4.4	4.3	4.2	4.0	3.9	3.8	3.7	3.6	0.184	60	
3.9	3.7	3.6	3.5	3.3	3.2	3.1	3.0	2.9	2.9	2.8	2.7	2.6	2.6	2.5	2.4	0.122	15	XR8002VS XR1102VS
4.5	4.3	4.1	4.0	3.9	3.7	3.6	3.5	3.4	3.3	3.2	3.1	3.0	2.9	2.9	2.8	0.141	20	
5.5	5.3	5.1	4.9	4.7	4.6	4.4	4.3	4.2	4.0	3.9	3.8	3.7	3.6	3.5	3.4	0.173	30	50 MESH YELLOW
6.3	6.1	5.9	5.7	5.5	5.3	5.1	5.0	4.8	4.7	4.5	4.4	4.3	4.2	4.1	4.0	0.200	40	
7.1	6.8	6.6	6.3	6.1	5.9	5.7	5.5	5.4	5.2	5.1	4.9	4.8	4.7	4.5	4.4	0.224	50	
7.8	7.5	7.2	6.9	6.7	6.5	6.3	6.1	5.9	5.7	5.5	5.4	5.2	5.1	5.0	4.8	0.245	60	
4.8	4.6	4.4	4.2	4.1	4.0	3.8	3.7	3.6	3.5	3.4	3.3	3.2	3.1	3.0	3.0	0.150	15	XR80025VS XR11025VS
5.7	5.5	5.3	5.1	4.9	4.8	4.6	4.5	4.3	4.2	4.1	4.0	3.9	3.8	3.7	3.6	0.180	20	
7.0	6.7	6.5	6.2	6.0	5.8	5.6	5.4	5.3	5.1	5.0	4.8	4.7	4.6	4.5	4.4	0.220	30	50 MESH PURPLE
7.9	7.6	7.3	7.1	6.8	6.6	6.4	6.2	6.0	5.8	5.7	5.5	5.4	5.2	5.1	5.0	0.250	40	
8.9	8.5	8.2	7.9	7.6	7.4	7.2	6.9	6.7	6.5	6.3	6.2	6.0	5.8	5.7	5.5	0.280	50	
9.8	9.4	9.1	8.8	8.5	8.2	7.9	7.7	7.4	7.2	7.0	6.8	6.6	6.5	6.3	6.1	0.310	60	
5.8	5.6	5.4	5.2	5.0	4.8	4.7	4.5	4.4	4.3	4.2	4.0	3.9	3.8	3.7	3.6	0.184	15	XR8003VS XR1103VS
6.7	6.5	6.2	6.0	5.8	5.6	5.4	5.3	5.1	4.9	4.8	4.7	4.5	4.4	4.3	4.2	0.212	20	
8.2	7.9	7.6	7.3	7.1	6.9	6.6	6.4	6.2	6.1	5.9	5.7	5.6	5.4	5.3	5.1	0.260	30	50 MESH BLUE
9.5	9.1	8.8	8.5	8.2	7.9	7.7	7.4	7.2	7.0	6.8	6.6	6.4	6.3	6.1	5.9	0.300	40	
10.6	10.2	9.8	9.5	9.2	8.9	8.6	8.3	8.0	7.8	7.6	7.4	7.2	7.0	6.8	6.6	0.335	50	
11.6	11.2	10.8	10.4	10.0	9.7	9.4	9.1	8.8	8.6	8.3	8.1	7.9	7.7	7.5	7.3	0.367	60	

**XR 80° / 110° 15" TIP SPACING**

ALL VALUES BASED ON WATER FOR OTHER LIQUIDS SEE USEFUL FORMULAS AND CONVERSIONS

mph		4.0	4.5	5.0	5.5	6.0	6.5	7.0	7.5	8.0	8.5	9.0	9.5	10.0	10.5	11.0	11.5	12.0	
XR8004VS XR1104VS	15	0.245	24.2	21.6	19.4	17.6	16.2	14.9	13.9	12.9	12.1	11.4	10.8	10.2	9.7	9.2	8.8	8.4	8.1
	20	0.283	28.0	24.9	22.4	20.4	18.7	17.2	16.0	14.9	14.0	13.2	12.4	11.8	11.2	10.7	10.2	9.7	9.3
	30	0.346	34.3	30.5	27.4	24.9	22.9	21.1	19.6	18.3	17.1	16.1	15.2	14.4	13.7	13.1	12.5	11.9	11.4
	40	0.400	39.6	35.2	31.7	28.8	26.4	24.4	22.6	21.1	19.8	18.6	17.6	16.7	15.8	15.1	14.4	13.8	13.2
50 MESH RED	50	0.447	44.3	39.4	35.4	32.2	29.5	27.2	25.3	23.6	22.1	20.8	19.7	18.6	17.7	16.9	16.1	15.4	14.8
	60	0.490	48.5	43.1	38.8	35.3	32.3	29.8	27.7	25.9	24.2	22.8	21.6	20.4	19.4	18.5	17.6	16.9	16.2
XR8005VS XR1105VS	15	0.306	30.3	26.9	24.2	22.0	20.2	18.7	17.3	16.2	15.2	14.3	13.5	12.8	12.1	11.5	11.0	10.5	10.1
	20	0.354	35.0	31.1	28.0	25.5	23.3	21.5	20.0	18.7	17.5	16.5	15.6	14.7	14.0	13.3	12.7	12.2	11.7
	30	0.433	42.9	38.1	34.3	31.2	28.6	26.4	24.5	22.9	21.4	20.2	19.1	18.0	17.1	16.3	15.6	14.9	14.3
	40	0.500	49.5	44.0	39.6	36.0	33.0	30.5	28.3	26.4	24.8	23.3	22.0	20.8	19.8	18.9	18.0	17.2	16.5
50 MESH BROWN	50	0.559	55.3	49.2	44.3	40.2	36.9	34.1	31.6	29.5	27.7	26.0	24.6	23.3	22.1	21.1	20.1	19.2	18.4
	60	0.612	60.6	53.9	48.5	44.1	40.4	37.3	34.6	32.3	30.3	28.5	26.9	25.5	24.2	23.1	22.0	21.1	20.2
XR8006VS XR1106VS	15	0.367	36.4	32.3	29.1	26.5	24.2	22.4	20.8	19.4	18.2	17.1	16.2	15.3	14.5	13.9	13.2	12.7	12.1
	20	0.424	42.0	37.3	33.6	30.5	28.0	25.8	24.0	22.4	21.0	19.8	18.7	17.7	16.8	16.0	15.3	14.6	14.0
	30	0.520	51.4	45.7	41.2	37.4	34.3	31.7	29.4	27.4	25.7	24.2	22.9	21.7	20.6	19.6	18.7	17.9	17.1
	40	0.600	59.4	52.8	47.5	43.2	39.6	36.6	33.9	31.7	29.7	28.0	26.4	25.0	23.8	22.6	21.6	20.7	19.8
50 MESH GRAY	50	0.671	66.4	59.0	53.1	48.3	44.3	40.9	37.9	35.4	33.2	31.3	29.5	28.0	26.6	25.3	24.1	23.1	22.1
	60	0.735	72.7	64.7	58.2	52.9	48.5	44.8	41.6	38.8	36.4	34.2	32.3	30.6	29.1	27.7	26.5	25.3	24.2
XR8008VS XR1108VS	15	0.490	48.5	43.1	38.8	35.3	32.3	29.8	27.7	25.9	24.2	22.8	21.6	20.4	19.4	18.5	17.6	16.9	16.2
	20	0.566	56.0	49.8	44.8	40.7	37.3	34.5	32.0	29.9	28.0	26.4	24.9	23.6	22.4	21.3	20.4	19.5	18.7
	30	0.693	68.6	61.0	54.9	49.9	45.7	42.2	39.2	36.6	34.3	32.3	30.5	28.9	27.4	26.1	24.9	23.9	22.9
	40	0.800	79.2	70.4	63.4	57.6	52.8	48.7	45.3	42.2	39.6	37.3	35.2	33.3	31.7	30.2	28.8	27.5	26.4
50 MESH WHITE	50	0.894	88.5	78.7	70.8	64.4	59.0	54.5	50.6	47.2	44.3	41.7	39.4	37.3	35.4	33.7	32.2	30.8	29.5
	60	0.980	97.0	86.2	77.6	70.5	64.7	59.7	55.4	51.7	48.5	45.6	43.1	40.8	38.8	37.0	35.3	33.7	32.3
XR8010SS XR11010SS	15	0.612	60.6	53.9	48.5	44.1	40.4	37.3	34.6	32.3	30.3	28.5	26.9	25.5	24.2	23.1	22.0	21.1	20.2
	20	0.707	70.0	62.2	56.0	50.9	46.7	43.1	40.0	37.3	35.0	32.9	31.1	29.5	28.0	26.7	25.5	24.3	23.3
	30	0.866	85.7	76.2	68.6	62.4	57.2	52.8	49.0	45.7	42.9	40.3	38.1	36.1	34.3	32.7	31.2	29.8	28.6
	40	1.000	99.0	88.0	79.2	72.0	66.0	60.9	56.6	52.8	49.5	46.6	44.0	41.7	39.6	37.7	36.0	34.4	33.0
50 MESH	50	1.118	110.7	98.4	88.5	80.5	73.8	68.1	63.2	59.0	55.3	52.1	49.2	46.6	44.3	42.2	40.2	38.5	36.9
	60	1.225	121.2	107.8	97.0	88.2	80.8	74.6	69.3	64.7	60.6	57.1	53.9	51.1	48.5	46.2	44.1	42.2	40.4
XR8015SS XR11015SS	15	0.919	90.9	80.8	72.7	66.1	60.6	56.0	52.0	48.5	45.5	42.8	40.4	38.3	36.4	34.6	33.1	31.6	30.3
	20	1.061	105.0	93.3	84.0	76.4	70.0	64.6	60.0	56.0	52.5	49.4	46.7	44.2	42.0	40.0	38.2	36.5	35.0
	30	1.299	128.6	114.3	102.9	93.5	85.7	79.1	73.5	68.6	64.3	60.5	57.2	54.1	51.4	49.0	46.8	44.7	42.9
	40	1.500	148.5	132.0	118.8	108.0	99.0	91.4	84.9	79.2	74.3	69.9	66.0	62.5	59.4	56.6	54.0	51.7	49.5
50 MESH	50	1.677	166.0	147.6	132.8	120.7	110.7	102.2	94.9	88.5	83.0	78.1	73.8	69.9	66.4	63.2	60.4	57.7	55.3
	60	1.837	181.9	161.7	145.5	132.3	121.2	111.9	103.9	97.0	90.9	85.6	80.8	76.6	72.7	69.3	66.1	63.3	60.6

**XR 80° / 110° 15" TIP SPACING**

ALL VALUES BASED ON WATER FOR OTHER LIQUIDS SEE USEFUL FORMULAS AND CONVERSIONS

12.5	13.0	13.5	14.0	14.5	15.0	15.5	16.0	16.5	17.0	17.5	18.0	18.5	19.0	19.5	20.0	mph	
7.8	7.5	7.2	6.9	6.7	6.5	6.3	6.1	5.9	5.7	5.5	5.4	5.2	5.1	5.0	4.8	0.245	15
9.0	8.6	8.3	8.0	7.7	7.5	7.2	7.0	6.8	6.6	6.4	6.2	6.1	5.9	5.7	5.6	0.283	20
11.0	10.6	10.2	9.8	9.5	9.1	8.9	8.6	8.3	8.1	7.8	7.6	7.4	7.2	7.0	6.9	0.346	30
12.7	12.2	11.7	11.3	10.9	10.6	10.2	9.9	9.6	9.3	9.1	8.8	8.6	8.3	8.1	7.9	0.400	40
14.2	13.6	13.1	12.6	12.2	11.8	11.4	11.1	10.7	10.4	10.1	9.8	9.6	9.3	9.1	8.9	0.447	50
15.5	14.9	14.4	13.9	13.4	12.9	12.5	12.1	11.8	11.4	11.1	10.8	10.5	10.2	9.9	9.7	0.490	60
50 MESH RED																	
9.7	9.3	9.0	8.7	8.4	8.1	7.8	7.6	7.3	7.1	6.9	6.7	6.6	6.4	6.2	6.1	0.306	15
11.2	10.8	10.4	10.0	9.7	9.3	9.0	8.8	8.5	8.2	8.0	7.8	7.6	7.4	7.2	7.0	0.354	20
13.7	13.2	12.7	12.2	11.8	11.4	11.1	10.7	10.4	10.1	9.8	9.5	9.3	9.0	8.8	8.6	0.433	30
15.8	15.2	14.7	14.1	13.7	13.2	12.8	12.4	12.0	11.6	11.3	11.0	10.7	10.4	10.2	9.9	0.500	40
17.7	17.0	16.4	15.8	15.3	14.8	14.3	13.8	13.4	13.0	12.6	12.3	12.0	11.7	11.4	11.1	0.559	50
19.4	18.7	18.0	17.3	16.7	16.2	15.6	15.2	14.7	14.3	13.9	13.5	13.1	12.8	12.4	12.1	0.612	60
50 MESH BROWN																	
11.6	11.2	10.8	10.4	10.0	9.7	9.4	9.1	8.8	8.6	8.3	8.1	7.9	7.7	7.5	7.3	0.367	15
13.4	12.9	12.4	12.0	11.6	11.2	10.8	10.5	10.2	9.9	9.6	9.3	9.1	8.8	8.6	8.4	0.424	20
16.5	15.8	15.2	14.7	14.2	13.7	13.3	12.9	12.5	12.1	11.8	11.4	11.1	10.8	10.6	10.3	0.520	30
19.0	18.3	17.6	17.0	16.4	15.8	15.3	14.9	14.4	14.0	13.6	13.2	12.8	12.5	12.2	11.9	0.600	40
21.3	20.4	19.7	19.0	18.3	17.7	17.1	16.6	16.1	15.6	15.2	14.8	14.4	14.0	13.6	13.3	0.671	50
23.3	22.4	21.6	20.8	20.1	19.4	18.8	18.2	17.6	17.1	16.6	16.2	15.7	15.3	14.9	14.5	0.735	60
50 MESH GRAY																	
15.5	14.9	14.4	13.9	13.4	12.9	12.5	12.1	11.8	11.4	11.1	10.8	10.5	10.2	9.9	9.7	0.490	15
17.9	17.2	16.6	16.0	15.4	14.9	14.5	14.0	13.6	13.2	12.8	12.4	12.1	11.8	11.5	11.2	0.566	20
21.9	21.1	20.3	19.6	18.9	18.3	17.7	17.1	16.6	16.1	15.7	15.2	14.8	14.4	14.1	13.7	0.693	30
25.3	24.4	23.5	22.6	21.8	21.1	20.4	19.8	19.2	18.6	18.1	17.6	17.1	16.7	16.2	15.8	0.800	40
28.3	27.2	26.2	25.3	24.4	23.6	22.9	22.1	21.5	20.8	20.2	19.7	19.1	18.6	18.2	17.7	0.894	50
31.0	29.8	28.7	27.7	26.8	25.9	25.0	24.2	23.5	22.8	22.2	21.6	21.0	20.4	19.9	19.4	0.980	60
50 MESH WHITE																	
19.4	18.7	18.0	17.3	16.7	16.2	15.6	15.2	14.7	14.3	13.9	13.5	13.1	12.8	12.4	12.1	0.612	15
22.4	21.5	20.7	20.0	19.3	18.7	18.1	17.5	17.0	16.5	16.0	15.6	15.1	14.7	14.4	14.0	0.707	20
27.4	26.4	25.4	24.5	23.7	22.9	22.1	21.4	20.8	20.2	19.6	19.1	18.5	18.0	17.6	17.1	0.866	30
31.7	30.5	29.3	28.3	27.3	26.4	25.5	24.8	24.0	23.3	22.6	22.0	21.4	20.8	20.3	19.8	1.000	40
35.4	34.1	32.8	31.6	30.5	29.5	28.6	27.7	26.8	26.0	25.3	24.6	23.9	23.3	22.7	22.1	1.118	50
38.8	37.3	35.9	34.6	33.4	32.3	31.3	30.3	29.4	28.5	27.7	26.9	26.2	25.5	24.9	24.2	1.225	60
50 MESH																	
29.1	28.0	26.9	26.0	25.1	24.2	23.5	22.7	22.0	21.4	20.8	20.2	19.7	19.1	18.7	18.2	0.919	15
33.6	32.3	31.1	30.0	29.0	28.0	27.1	26.3	25.5	24.7	24.0	23.3	22.7	22.1	21.5	21.0	1.061	20
41.2	39.6	38.1	36.7	35.5	34.3	33.2	32.2	31.2	30.3	29.4	28.6	27.8	27.1	26.4	25.7	1.299	30
47.5	45.7	44.0	42.4	41.0	39.6	38.3	37.1	36.0	34.9	33.9	33.0	32.1	31.3	30.5	29.7	1.500	40
53.1	51.1	49.2	47.4	45.8	44.3	42.8	41.5	40.2	39.1	37.9	36.9	35.9	35.0	34.1	33.2	1.677	50
58.2	56.0	53.9	52.0	50.2	48.5	46.9	45.5	44.1	42.8	41.6	40.4	39.3	38.3	37.3	36.4	1.837	60
50 MESH																	