

XR 80° / 110° 30" TIP SPACING

ALL VALUES BASED ON WATER FOR OTHER LIQUIDS SEE USEFUL FORMULAS AND CONVERSIONS

mph		4.0	4.5	5.0	5.5	6.0	6.5	7.0	7.5	8.0	8.5	9.0	9.5	10.0	10.5	11.0	11.5	12.0	
psi gpm																			
XR8001VS XR1101VS 100 MESH ORANGE	15	0.061	3.0	2.7	2.4	2.2	2.0	1.9	1.7	1.6	1.5	1.4	1.3	1.3	1.2	1.2	1.1	1.1	1.0
	20	0.071	3.5	3.1	2.8	2.5	2.3	2.2	2.0	1.9	1.8	1.6	1.6	1.5	1.4	1.3	1.3	1.2	1.2
	30	0.087	4.3	3.8	3.4	3.1	2.9	2.6	2.4	2.3	2.1	2.0	1.9	1.8	1.7	1.6	1.6	1.5	1.4
	40	0.100	5.0	4.4	4.0	3.6	3.3	3.0	2.8	2.6	2.5	2.3	2.2	2.1	2.0	1.9	1.8	1.7	1.7
	50	0.112	5.5	4.9	4.4	4.0	3.7	3.4	3.2	3.0	2.8	2.6	2.5	2.3	2.2	2.1	2.0	1.9	1.8
60	0.122	6.1	5.4	4.8	4.4	4.0	3.7	3.5	3.2	3.0	2.9	2.7	2.6	2.4	2.3	2.2	2.1	2.0	2.0
XR80015VS XR11015VS 100 MESH GREEN	15	0.092	4.5	4.0	3.6	3.3	3.0	2.8	2.6	2.4	2.3	2.1	2.0	1.9	1.8	1.7	1.7	1.6	1.5
	20	0.106	5.3	4.7	4.2	3.8	3.5	3.2	3.0	2.8	2.6	2.5	2.3	2.2	2.1	2.0	1.9	1.8	1.8
	30	0.130	6.4	5.7	5.1	4.7	4.3	4.0	3.7	3.4	3.2	3.0	2.9	2.7	2.6	2.4	2.3	2.2	2.1
	40	0.150	7.4	6.6	5.9	5.4	5.0	4.6	4.2	4.0	3.7	3.5	3.3	3.1	3.0	2.8	2.7	2.6	2.5
	50	0.168	8.3	7.4	6.6	6.0	5.5	5.1	4.7	4.4	4.2	3.9	3.7	3.5	3.3	3.2	3.0	2.9	2.8
60	0.184	9.1	8.1	7.3	6.6	6.1	5.6	5.2	4.8	4.5	4.3	4.0	3.8	3.6	3.5	3.3	3.2	3.0	
XR8002VS XR1102VS 50 MESH YELLOW	15	0.122	6.1	5.4	4.8	4.4	4.0	3.7	3.5	3.2	3.0	2.9	2.7	2.6	2.4	2.3	2.2	2.1	2.0
	20	0.141	7.0	6.2	5.6	5.1	4.7	4.3	4.0	3.7	3.5	3.3	3.1	2.9	2.8	2.7	2.5	2.4	2.3
	30	0.173	8.6	7.6	6.9	6.2	5.7	5.3	4.9	4.6	4.3	4.0	3.8	3.6	3.4	3.3	3.1	3.0	2.9
	40	0.200	9.9	8.8	7.9	7.2	6.6	6.1	5.7	5.3	5.0	4.7	4.4	4.2	4.0	3.8	3.6	3.4	3.3
	50	0.224	11.1	9.8	8.9	8.0	7.4	6.8	6.3	5.9	5.5	5.2	4.9	4.7	4.4	4.2	4.0	3.8	3.7
60	0.245	12.1	10.8	9.7	8.8	8.1	7.5	6.9	6.5	6.1	5.7	5.4	5.1	4.8	4.6	4.4	4.2	4.0	
XR80025VS XR11025VS 50 MESH PURPLE	15	0.150	7.4	6.6	5.9	5.4	5.0	4.6	4.2	4.0	3.7	3.5	3.3	3.1	3.0	2.8	2.7	2.6	2.5
	20	0.180	8.9	7.9	7.1	6.5	5.9	5.5	5.1	4.8	4.5	4.2	4.0	3.8	3.6	3.4	3.2	3.1	3.0
	30	0.220	10.9	9.7	8.7	7.9	7.3	6.7	6.2	5.8	5.4	5.1	4.8	4.6	4.4	4.1	4.0	3.8	3.6
	40	0.250	12.4	11.0	9.9	9.0	8.3	7.6	7.1	6.6	6.2	5.8	5.5	5.2	5.0	4.7	4.5	4.3	4.1
	50	0.280	13.9	12.3	11.1	10.1	9.2	8.5	7.9	7.4	6.9	6.5	6.2	5.8	5.5	5.3	5.0	4.8	4.6
60	0.310	15.3	13.6	12.3	11.2	10.2	9.4	8.8	8.2	7.7	7.2	6.8	6.5	6.1	5.8	5.6	5.3	5.1	
XR8003VS XR1103VS 50 MESH BLUE	15	0.184	9.1	8.1	7.3	6.6	6.1	5.6	5.2	4.8	4.5	4.3	4.0	3.8	3.6	3.5	3.3	3.2	3.0
	20	0.212	10.5	9.3	8.4	7.6	7.0	6.5	6.0	5.6	5.3	4.9	4.7	4.4	4.2	4.0	3.8	3.7	3.5
	30	0.260	12.9	11.4	10.3	9.4	8.6	7.9	7.3	6.9	6.4	6.1	5.7	5.4	5.1	4.9	4.7	4.5	4.3
	40	0.300	14.9	13.2	11.9	10.8	9.9	9.1	8.5	7.9	7.4	7.0	6.6	6.3	5.9	5.7	5.4	5.2	5.0
	50	0.335	16.6	14.8	13.3	12.1	11.1	10.2	9.5	8.9	8.3	7.8	7.4	7.0	6.6	6.3	6.0	5.8	5.5
60	0.367	18.2	16.2	14.5	13.2	12.1	11.2	10.4	9.7	9.1	8.6	8.1	7.7	7.3	6.9	6.6	6.3	6.1	

XR 80° / 110° 30" TIP SPACING

ALL VALUES BASED ON WATER FOR OTHER LIQUIDS SEE USEFUL FORMULAS AND CONVERSIONS

12.5	13.0	13.5	14.0	14.5	15.0	15.5	16.0	16.5	17.0	17.5	18.0	18.5	19.0	19.5	20.0	mph			
																gpm	psi		
1.0	0.9	0.9	0.9	0.8	0.8	0.8	0.8	0.7	0.7	0.7	0.7	0.7	0.6	0.6	0.6	0.061	15	XR8001VS XR1101VS	
1.1	1.1	1.0	1.0	1.0	0.9	0.9	0.9	0.8	0.8	0.8	0.8	0.8	0.7	0.7	0.7	0.071	20		
1.4	1.3	1.3	1.2	1.2	1.1	1.1	1.1	1.0	1.0	1.0	1.0	0.9	0.9	0.9	0.9	0.087	30	100 MESH ORANGE	
1.6	1.5	1.5	1.4	1.4	1.3	1.3	1.2	1.2	1.2	1.1	1.1	1.1	1.0	1.0	1.0	0.100	40		
1.8	1.7	1.6	1.6	1.5	1.5	1.4	1.4	1.3	1.3	1.3	1.2	1.2	1.2	1.1	1.1	0.112	50		
1.9	1.9	1.8	1.7	1.7	1.6	1.6	1.5	1.5	1.4	1.4	1.3	1.3	1.3	1.2	1.2	0.122	60		
1.5	1.4	1.3	1.3	1.3	1.2	1.2	1.1	1.1	1.1	1.0	1.0	1.0	1.0	0.9	0.9	0.092	15	XR80015VS XR11015VS	
1.7	1.6	1.6	1.5	1.4	1.4	1.4	1.3	1.3	1.2	1.2	1.2	1.1	1.1	1.1	1.1	0.106	20		
2.1	2.0	1.9	1.8	1.8	1.7	1.7	1.6	1.6	1.5	1.5	1.4	1.4	1.4	1.3	1.3	0.130	30	100 MESH GREEN	
2.4	2.3	2.2	2.1	2.0	2.0	1.9	1.9	1.8	1.7	1.7	1.7	1.6	1.6	1.5	1.5	0.150	40		
2.7	2.6	2.5	2.4	2.3	2.2	2.1	2.1	2.0	2.0	1.9	1.8	1.8	1.7	1.7	1.7	0.168	50		
2.9	2.8	2.7	2.6	2.5	2.4	2.3	2.3	2.2	2.1	2.1	2.0	2.0	1.9	1.9	1.8	0.184	60		
1.9	1.9	1.8	1.7	1.7	1.6	1.6	1.5	1.5	1.4	1.4	1.3	1.3	1.3	1.2	1.2	0.122	15	XR8002VS XR1102VS	
2.2	2.2	2.1	2.0	1.9	1.9	1.8	1.8	1.7	1.6	1.6	1.6	1.5	1.5	1.4	1.4	0.141	20		
2.7	2.6	2.5	2.4	2.4	2.3	2.2	2.1	2.1	2.0	2.0	1.9	1.9	1.8	1.8	1.7	0.173	30	50 MESH YELLOW	
3.2	3.0	2.9	2.8	2.7	2.6	2.6	2.5	2.4	2.3	2.3	2.2	2.1	2.1	2.0	2.0	0.200	40		
3.5	3.4	3.3	3.2	3.1	3.0	2.9	2.8	2.7	2.6	2.5	2.5	2.4	2.3	2.3	2.2	0.224	50		
3.9	3.7	3.6	3.5	3.3	3.2	3.1	3.0	2.9	2.9	2.8	2.7	2.6	2.6	2.5	2.4	0.245	60		
2.4	2.3	2.2	2.1	2.0	2.0	1.9	1.9	1.8	1.7	1.7	1.7	1.6	1.6	1.5	1.5	0.150	15	XR80025VS XR11025VS	
2.9	2.7	2.6	2.5	2.5	2.4	2.3	2.2	2.2	2.1	2.0	2.0	1.9	1.9	1.8	1.8	0.180	20		
3.5	3.4	3.2	3.1	3.0	2.9	2.8	2.7	2.6	2.6	2.5	2.4	2.4	2.3	2.2	2.2	0.220	30	50 MESH PURPLE	
4.0	3.8	3.7	3.5	3.4	3.3	3.2	3.1	3.0	2.9	2.8	2.8	2.7	2.6	2.5	2.5	0.250	40		
4.4	4.3	4.1	4.0	3.8	3.7	3.6	3.5	3.4	3.3	3.2	3.1	3.0	2.9	2.8	2.8	0.280	50		
4.9	4.7	4.5	4.4	4.2	4.1	4.0	3.8	3.7	3.6	3.5	3.4	3.3	3.2	3.1	3.1	0.310	60		
2.9	2.8	2.7	2.6	2.5	2.4	2.3	2.3	2.2	2.1	2.1	2.0	2.0	1.9	1.9	1.8	0.184	15	XR8003VS XR1103VS	
3.4	3.2	3.1	3.0	2.9	2.8	2.7	2.6	2.5	2.5	2.4	2.3	2.3	2.2	2.2	2.1	0.212	20		
4.1	4.0	3.8	3.7	3.5	3.4	3.3	3.2	3.1	3.0	2.9	2.9	2.8	2.7	2.6	2.6	0.260	30	50 MESH BLUE	
4.8	4.6	4.4	4.2	4.1	4.0	3.8	3.7	3.6	3.5	3.4	3.3	3.2	3.1	3.0	3.0	0.300	40		
5.3	5.1	4.9	4.7	4.6	4.4	4.3	4.2	4.0	3.9	3.8	3.7	3.6	3.5	3.4	3.3	0.335	50		
5.8	5.6	5.4	5.2	5.0	4.8	4.7	4.5	4.4	4.3	4.2	4.0	3.9	3.8	3.7	3.6	0.367	60		

XR 80° / 110° 30" TIP SPACING

ALL VALUES BASED ON WATER FOR OTHER LIQUIDS SEE USEFUL FORMULAS AND CONVERSIONS

mph			4.0	4.5	5.0	5.5	6.0	6.5	7.0	7.5	8.0	8.5	9.0	9.5	10.0	10.5	11.0	11.5	12.0
XR8004VS XR1104VS	15	0.245	12.1	10.8	9.7	8.8	8.1	7.5	6.9	6.5	6.1	5.7	5.4	5.1	4.8	4.6	4.4	4.2	4.0
	20	0.283	14.0	12.4	11.2	10.2	9.3	8.6	8.0	7.5	7.0	6.6	6.2	5.9	5.6	5.3	5.1	4.9	4.7
	30	0.346	17.1	15.2	13.7	12.5	11.4	10.6	9.8	9.1	8.6	8.1	7.6	7.2	6.9	6.5	6.2	6.0	5.7
	40	0.400	19.8	17.6	15.8	14.4	13.2	12.2	11.3	10.6	9.9	9.3	8.8	8.3	7.9	7.5	7.2	6.9	6.6
50 MESH RED	50	0.447	22.1	19.7	17.7	16.1	14.8	13.6	12.6	11.8	11.1	10.4	9.8	9.3	8.9	8.4	8.0	7.7	7.4
	60	0.490	24.2	21.6	19.4	17.6	16.2	14.9	13.9	12.9	12.1	11.4	10.8	10.2	9.7	9.2	8.8	8.4	8.1
XR8005VS XR1105VS	15	0.306	15.2	13.5	12.1	11.0	10.1	9.3	8.7	8.1	7.6	7.1	6.7	6.4	6.1	5.8	5.5	5.3	5.1
	20	0.354	17.5	15.6	14.0	12.7	11.7	10.8	10.0	9.3	8.8	8.2	7.8	7.4	7.0	6.7	6.4	6.1	5.8
	30	0.433	21.4	19.1	17.1	15.6	14.3	13.2	12.2	11.4	10.7	10.1	9.5	9.0	8.6	8.2	7.8	7.5	7.1
	40	0.500	24.8	22.0	19.8	18.0	16.5	15.2	14.1	13.2	12.4	11.6	11.0	10.4	9.9	9.4	9.0	8.6	8.3
50 MESH BROWN	50	0.559	27.7	24.6	22.1	20.1	18.4	17.0	15.8	14.8	13.8	13.0	12.3	11.7	11.1	10.5	10.1	9.6	9.2
	60	0.612	30.3	26.9	24.2	22.0	20.2	18.7	17.3	16.2	15.2	14.3	13.5	12.8	12.1	11.5	11.0	10.5	10.1
XR8006VS XR1106VS	15	0.367	18.2	16.2	14.5	13.2	12.1	11.2	10.4	9.7	9.1	8.6	8.1	7.7	7.3	6.9	6.6	6.3	6.1
	20	0.424	21.0	18.7	16.8	15.3	14.0	12.9	12.0	11.2	10.5	9.9	9.3	8.8	8.4	8.0	7.6	7.3	7.0
	30	0.520	25.7	22.9	20.6	18.7	17.1	15.8	14.7	13.7	12.9	12.1	11.4	10.8	10.3	9.8	9.4	8.9	8.6
	40	0.600	29.7	26.4	23.8	21.6	19.8	18.3	17.0	15.8	14.9	14.0	13.2	12.5	11.9	11.3	10.8	10.3	9.9
50 MESH GRAY	50	0.671	33.2	29.5	26.6	24.1	22.1	20.4	19.0	17.7	16.6	15.6	14.8	14.0	13.3	12.6	12.1	11.5	11.1
	60	0.735	36.4	32.3	29.1	26.5	24.2	22.4	20.8	19.4	18.2	17.1	16.2	15.3	14.5	13.9	13.2	12.7	12.1
XR8008VS XR1108VS	15	0.490	24.2	21.6	19.4	17.6	16.2	14.9	13.9	12.9	12.1	11.4	10.8	10.2	9.7	9.2	8.8	8.4	8.1
	20	0.566	28.0	24.9	22.4	20.4	18.7	17.2	16.0	14.9	14.0	13.2	12.4	11.8	11.2	10.7	10.2	9.7	9.3
	30	0.693	34.3	30.5	27.4	24.9	22.9	21.1	19.6	18.3	17.1	16.1	15.2	14.4	13.7	13.1	12.5	11.9	11.4
	40	0.800	39.6	35.2	31.7	28.8	26.4	24.4	22.6	21.1	19.8	18.6	17.6	16.7	15.8	15.1	14.4	13.8	13.2
50 MESH WHITE	50	0.894	44.3	39.4	35.4	32.2	29.5	27.2	25.3	23.6	22.1	20.8	19.7	18.6	17.7	16.9	16.1	15.4	14.8
	60	0.980	48.5	43.1	38.8	35.3	32.3	29.8	27.7	25.9	24.2	22.8	21.6	20.4	19.4	18.5	17.6	16.9	16.2
XR8010SS XR11010SS	15	0.612	30.3	26.9	24.2	22.0	20.2	18.7	17.3	16.2	15.2	14.3	13.5	12.8	12.1	11.5	11.0	10.5	10.1
	20	0.707	35.0	31.1	28.0	25.5	23.3	21.5	20.0	18.7	17.5	16.5	15.6	14.7	14.0	13.3	12.7	12.2	11.7
	30	0.866	42.9	38.1	34.3	31.2	28.6	26.4	24.5	22.9	21.4	20.2	19.1	18.0	17.1	16.3	15.6	14.9	14.3
	40	1.000	49.5	44.0	39.6	36.0	33.0	30.5	28.3	26.4	24.8	23.3	22.0	20.8	19.8	18.9	18.0	17.2	16.5
50 MESH	50	1.118	55.3	49.2	44.3	40.2	36.9	34.1	31.6	29.5	27.7	26.0	24.6	23.3	22.1	21.1	20.1	19.2	18.4
	60	1.225	60.6	53.9	48.5	44.1	40.4	37.3	34.6	32.3	30.3	28.5	26.9	25.5	24.2	23.1	22.0	21.1	20.2
XR8015SS XR11015SS	15	0.919	45.5	40.4	36.4	33.1	30.3	28.0	26.0	24.2	22.7	21.4	20.2	19.1	18.2	17.3	16.5	15.8	15.2
	20	1.061	52.5	46.7	42.0	38.2	35.0	32.3	30.0	28.0	26.3	24.7	23.3	22.1	21.0	20.0	19.1	18.3	17.5
	30	1.299	64.3	57.2	51.4	46.8	42.9	39.6	36.7	34.3	32.2	30.3	28.6	27.1	25.7	24.5	23.4	22.4	21.4
	40	1.500	74.3	66.0	59.4	54.0	49.5	45.7	42.4	39.6	37.1	34.9	33.0	31.3	29.7	28.3	27.0	25.8	24.8
50 MESH	50	1.677	83.0	73.8	66.4	60.4	55.3	51.1	47.4	44.3	41.5	39.1	36.9	35.0	33.2	31.6	30.2	28.9	27.7
	60	1.837	90.9	80.8	72.7	66.1	60.6	56.0	52.0	48.5	45.5	42.8	40.4	38.3	36.4	34.6	33.1	31.6	30.3

XR 80° / 110° 30" TIP SPACING

ALL VALUES BASED ON WATER FOR OTHER LIQUIDS SEE USEFUL FORMULAS AND CONVERSIONS

12.5	13.0	13.5	14.0	14.5	15.0	15.5	16.0	16.5	17.0	17.5	18.0	18.5	19.0	19.5	20.0	mph	
3.9	3.7	3.6	3.5	3.3	3.2	3.1	3.0	2.9	2.9	2.8	2.7	2.6	2.6	2.5	2.4	0.245	15
4.5	4.3	4.1	4.0	3.9	3.7	3.6	3.5	3.4	3.3	3.2	3.1	3.0	2.9	2.9	2.8	0.283	20
5.5	5.3	5.1	4.9	4.7	4.6	4.4	4.3	4.2	4.0	3.9	3.8	3.7	3.6	3.5	3.4	0.346	30
6.3	6.1	5.9	5.7	5.5	5.3	5.1	5.0	4.8	4.7	4.5	4.4	4.3	4.2	4.1	4.0	0.400	40
7.1	6.8	6.6	6.3	6.1	5.9	5.7	5.5	5.4	5.2	5.1	4.9	4.8	4.7	4.5	4.4	0.447	50
7.8	7.5	7.2	6.9	6.7	6.5	6.3	6.1	5.9	5.7	5.5	5.4	5.2	5.1	5.0	4.8	0.490	60
50 MESH RED																	
4.8	4.7	4.5	4.3	4.2	4.0	3.9	3.8	3.7	3.6	3.5	3.4	3.3	3.2	3.1	3.0	0.306	15
5.6	5.4	5.2	5.0	4.8	4.7	4.5	4.4	4.2	4.1	4.0	3.9	3.8	3.7	3.6	3.5	0.354	20
6.9	6.6	6.4	6.1	5.9	5.7	5.5	5.4	5.2	5.0	4.9	4.8	4.6	4.5	4.4	4.3	0.433	30
7.9	7.6	7.3	7.1	6.8	6.6	6.4	6.2	6.0	5.8	5.7	5.5	5.4	5.2	5.1	5.0	0.500	40
8.9	8.5	8.2	7.9	7.6	7.4	7.1	6.9	6.7	6.5	6.3	6.1	6.0	5.8	5.7	5.5	0.559	50
9.7	9.3	9.0	8.7	8.4	8.1	7.8	7.6	7.3	7.1	6.9	6.7	6.6	6.4	6.2	6.1	0.612	60
50 MESH BROWN																	
5.8	5.6	5.4	5.2	5.0	4.8	4.7	4.5	4.4	4.3	4.2	4.0	3.9	3.8	3.7	3.6	0.367	15
6.7	6.5	6.2	6.0	5.8	5.6	5.4	5.3	5.1	4.9	4.8	4.7	4.5	4.4	4.3	4.2	0.424	20
8.2	7.9	7.6	7.3	7.1	6.9	6.6	6.4	6.2	6.1	5.9	5.7	5.6	5.4	5.3	5.1	0.520	30
9.5	9.1	8.8	8.5	8.2	7.9	7.7	7.4	7.2	7.0	6.8	6.6	6.4	6.3	6.1	5.9	0.600	40
10.6	10.2	9.8	9.5	9.2	8.9	8.6	8.3	8.0	7.8	7.6	7.4	7.2	7.0	6.8	6.6	0.671	50
11.6	11.2	10.8	10.4	10.0	9.7	9.4	9.1	8.8	8.6	8.3	8.1	7.9	7.7	7.5	7.3	0.735	60
50 MESH GRAY																	
7.8	7.5	7.2	6.9	6.7	6.5	6.3	6.1	5.9	5.7	5.5	5.4	5.2	5.1	5.0	4.8	0.490	15
9.0	8.6	8.3	8.0	7.7	7.5	7.2	7.0	6.8	6.6	6.4	6.2	6.1	5.9	5.7	5.6	0.566	20
11.0	10.6	10.2	9.8	9.5	9.1	8.9	8.6	8.3	8.1	7.8	7.6	7.4	7.2	7.0	6.9	0.693	30
12.7	12.2	11.7	11.3	10.9	10.6	10.2	9.9	9.6	9.3	9.1	8.8	8.6	8.3	8.1	7.9	0.800	40
14.2	13.6	13.1	12.6	12.2	11.8	11.4	11.1	10.7	10.4	10.1	9.8	9.6	9.3	9.1	8.9	0.894	50
15.5	14.9	14.4	13.9	13.4	12.9	12.5	12.1	11.8	11.4	11.1	10.8	10.5	10.2	9.9	9.7	0.980	60
50 MESH WHITE																	
9.7	9.3	9.0	8.7	8.4	8.1	7.8	7.6	7.3	7.1	6.9	6.7	6.6	6.4	6.2	6.1	0.612	15
11.2	10.8	10.4	10.0	9.7	9.3	9.0	8.8	8.5	8.2	8.0	7.8	7.6	7.4	7.2	7.0	0.707	20
13.7	13.2	12.7	12.2	11.8	11.4	11.1	10.7	10.4	10.1	9.8	9.5	9.3	9.0	8.8	8.6	0.866	30
15.8	15.2	14.7	14.1	13.7	13.2	12.8	12.4	12.0	11.6	11.3	11.0	10.7	10.4	10.2	9.9	1.000	40
17.7	17.0	16.4	15.8	15.3	14.8	14.3	13.8	13.4	13.0	12.6	12.3	12.0	11.7	11.4	11.1	1.118	50
19.4	18.7	18.0	17.3	16.7	16.2	15.6	15.2	14.7	14.3	13.9	13.5	13.1	12.8	12.4	12.1	1.225	60
50 MESH																	
14.5	14.0	13.5	13.0	12.5	12.1	11.7	11.4	11.0	10.7	10.4	10.1	9.8	9.6	9.3	9.1	0.919	15
16.8	16.2	15.6	15.0	14.5	14.0	13.5	13.1	12.7	12.4	12.0	11.7	11.4	11.1	10.8	10.5	1.061	20
20.6	19.8	19.1	18.4	17.7	17.1	16.6	16.1	15.6	15.1	14.7	14.3	13.9	13.5	13.2	12.9	1.299	30
23.8	22.8	22.0	21.2	20.5	19.8	19.2	18.6	18.0	17.5	17.0	16.5	16.1	15.6	15.2	14.9	1.500	40
26.6	25.5	24.6	23.7	22.9	22.1	21.4	20.8	20.1	19.5	19.0	18.4	17.9	17.5	17.0	16.6	1.677	50
29.1	28.0	26.9	26.0	25.1	24.2	23.5	22.7	22.0	21.4	20.8	20.2	19.7	19.1	18.7	18.2	1.837	60
50 MESH																	