

**XR 80° / 110° 36" TIP SPACING**

ALL VALUES BASED ON WATER FOR OTHER LIQUIDS SEE USEFUL FORMULAS AND CONVERSIONS

mph		4.0	4.5	5.0	5.5	6.0	6.5	7.0	7.5	8.0	8.5	9.0	9.5	10.0	10.5	11.0	11.5	12.0	
psi gpm																			
XR8001VS XR1101VS  100 MESH ORANGE	15	0.061	2.5	2.2	2.0	1.8	1.7	1.6	1.4	1.3	1.3	1.2	1.1	1.1	1.0	1.0	0.9	0.9	0.8
	20	0.071	2.9	2.6	2.3	2.1	1.9	1.8	1.7	1.6	1.5	1.4	1.3	1.2	1.2	1.1	1.1	1.0	1.0
	30	0.087	3.6	3.2	2.9	2.6	2.4	2.2	2.0	1.9	1.8	1.7	1.6	1.5	1.4	1.4	1.3	1.2	1.2
	40	0.100	4.1	3.7	3.3	3.0	2.8	2.5	2.4	2.2	2.1	1.9	1.8	1.7	1.7	1.6	1.5	1.4	1.4
	50	0.112	4.6	4.1	3.7	3.4	3.1	2.8	2.6	2.5	2.3	2.2	2.0	1.9	1.8	1.8	1.7	1.6	1.5
60	0.122	5.1	4.5	4.0	3.7	3.4	3.1	2.9	2.7	2.5	2.4	2.2	2.1	2.0	1.9	1.8	1.8	1.7	
XR80015VS XR11015VS  100 MESH GREEN	15	0.092	3.8	3.4	3.0	2.8	2.5	2.3	2.2	2.0	1.9	1.8	1.7	1.6	1.5	1.4	1.4	1.3	1.3
	20	0.106	4.4	3.9	3.5	3.2	2.9	2.7	2.5	2.3	2.2	2.1	1.9	1.8	1.8	1.7	1.6	1.5	1.5
	30	0.130	5.4	4.8	4.3	3.9	3.6	3.3	3.1	2.9	2.7	2.5	2.4	2.3	2.1	2.0	1.9	1.9	1.8
	40	0.150	6.2	5.5	5.0	4.5	4.1	3.8	3.5	3.3	3.1	2.9	2.8	2.6	2.5	2.4	2.3	2.2	2.1
	50	0.168	6.9	6.1	5.5	5.0	4.6	4.3	4.0	3.7	3.5	3.3	3.1	2.9	2.8	2.6	2.5	2.4	2.3
60	0.184	7.6	6.7	6.1	5.5	5.1	4.7	4.3	4.0	3.8	3.6	3.4	3.2	3.0	2.9	2.8	2.6	2.5	
XR8002VS XR1102VS  50 MESH YELLOW	15	0.122	5.1	4.5	4.0	3.7	3.4	3.1	2.9	2.7	2.5	2.4	2.2	2.1	2.0	1.9	1.8	1.8	1.7
	20	0.141	5.8	5.2	4.7	4.2	3.9	3.6	3.3	3.1	2.9	2.7	2.6	2.5	2.3	2.2	2.1	2.0	1.9
	30	0.173	7.1	6.4	5.7	5.2	4.8	4.4	4.1	3.8	3.6	3.4	3.2	3.0	2.9	2.7	2.6	2.5	2.4
	40	0.200	8.3	7.3	6.6	6.0	5.5	5.1	4.7	4.4	4.1	3.9	3.7	3.5	3.3	3.1	3.0	2.9	2.8
	50	0.224	9.2	8.2	7.4	6.7	6.1	5.7	5.3	4.9	4.6	4.3	4.1	3.9	3.7	3.5	3.4	3.2	3.1
60	0.245	10.1	9.0	8.1	7.3	6.7	6.2	5.8	5.4	5.1	4.8	4.5	4.3	4.0	3.8	3.7	3.5	3.4	
XR80025VS XR11025VS  50 MESH PURPLE	15	0.150	6.2	5.5	5.0	4.5	4.1	3.8	3.5	3.3	3.1	2.9	2.8	2.6	2.5	2.4	2.3	2.2	2.1
	20	0.180	7.4	6.6	5.9	5.4	5.0	4.6	4.2	4.0	3.7	3.5	3.3	3.1	3.0	2.8	2.7	2.6	2.5
	30	0.220	9.1	8.1	7.3	6.6	6.1	5.6	5.2	4.8	4.5	4.3	4.0	3.8	3.6	3.5	3.3	3.2	3.0
	40	0.250	10.3	9.2	8.3	7.5	6.9	6.3	5.9	5.5	5.2	4.9	4.6	4.3	4.1	3.9	3.8	3.6	3.4
	50	0.280	11.6	10.3	9.2	8.4	7.7	7.1	6.6	6.2	5.8	5.4	5.1	4.9	4.6	4.4	4.2	4.0	3.9
60	0.310	12.8	11.4	10.2	9.3	8.5	7.9	7.3	6.8	6.4	6.0	5.7	5.4	5.1	4.9	4.7	4.4	4.3	
XR8003VS XR1103VS  50 MESH BLUE	15	0.184	7.6	6.7	6.1	5.5	5.1	4.7	4.3	4.0	3.8	3.6	3.4	3.2	3.0	2.9	2.8	2.6	2.5
	20	0.212	8.8	7.8	7.0	6.4	5.8	5.4	5.0	4.7	4.4	4.1	3.9	3.7	3.5	3.3	3.2	3.0	2.9
	30	0.260	10.7	9.5	8.6	7.8	7.1	6.6	6.1	5.7	5.4	5.0	4.8	4.5	4.3	4.1	3.9	3.7	3.6
	40	0.300	12.4	11.0	9.9	9.0	8.3	7.6	7.1	6.6	6.2	5.8	5.5	5.2	5.0	4.7	4.5	4.3	4.1
	50	0.335	13.8	12.3	11.1	10.1	9.2	8.5	7.9	7.4	6.9	6.5	6.1	5.8	5.5	5.3	5.0	4.8	4.6
60	0.367	15.2	13.5	12.1	11.0	10.1	9.3	8.7	8.1	7.6	7.1	6.7	6.4	6.1	5.8	5.5	5.3	5.1	

**XR 80° / 110° 36" TIP SPACING**

ALL VALUES BASED ON WATER FOR OTHER LIQUIDS SEE USEFUL FORMULAS AND CONVERSIONS

12.5	13.0	13.5	14.0	14.5	15.0	15.5	16.0	16.5	17.0	17.5	18.0	18.5	19.0	19.5	20.0	mph		
																	gpm	psi
0.8	0.8	0.7	0.7	0.7	0.7	0.7	0.6	0.6	0.6	0.6	0.6	0.5	0.5	0.5	0.5	0.061	15	XR8001VS
0.9	0.9	0.9	0.8	0.8	0.8	0.8	0.7	0.7	0.7	0.7	0.6	0.6	0.6	0.6	0.6	0.071	20	XR1101VS
1.1	1.1	1.1	1.0	1.0	1.0	0.9	0.9	0.9	0.8	0.8	0.8	0.8	0.8	0.7	0.7	0.087	30	
1.3	1.3	1.2	1.2	1.1	1.1	1.1	1.0	1.0	1.0	0.9	0.9	0.9	0.9	0.8	0.8	0.100	40	
1.5	1.4	1.4	1.3	1.3	1.2	1.2	1.2	1.1	1.1	1.1	1.0	1.0	1.0	0.9	0.9	0.112	50	100 MESH
1.6	1.6	1.5	1.4	1.4	1.3	1.3	1.3	1.2	1.2	1.2	1.1	1.1	1.1	1.0	1.0	0.122	60	ORANGE
1.2	1.2	1.1	1.1	1.0	1.0	1.0	0.9	0.9	0.9	0.9	0.8	0.8	0.8	0.8	0.8	0.092	15	XR80015VS
1.4	1.3	1.3	1.3	1.2	1.2	1.1	1.1	1.1	1.0	1.0	1.0	0.9	0.9	0.9	0.9	0.106	20	XR11015VS
1.7	1.6	1.6	1.5	1.5	1.4	1.4	1.3	1.3	1.3	1.2	1.2	1.2	1.1	1.1	1.1	0.130	30	
2.0	1.9	1.8	1.8	1.7	1.7	1.6	1.5	1.5	1.5	1.4	1.4	1.3	1.3	1.3	1.2	0.150	40	
2.2	2.1	2.0	2.0	1.9	1.8	1.8	1.7	1.7	1.6	1.6	1.5	1.5	1.5	1.4	1.4	0.168	50	100 MESH
2.4	2.3	2.2	2.2	2.1	2.0	2.0	1.9	1.8	1.8	1.7	1.7	1.6	1.6	1.6	1.5	0.184	60	GREEN
1.6	1.6	1.5	1.4	1.4	1.3	1.3	1.3	1.2	1.2	1.2	1.1	1.1	1.1	1.0	1.0	0.122	15	XR8002VS
1.9	1.8	1.7	1.7	1.6	1.6	1.5	1.5	1.4	1.4	1.3	1.3	1.3	1.2	1.2	1.2	0.141	20	XR1102VS
2.3	2.2	2.1	2.0	2.0	1.9	1.8	1.8	1.7	1.7	1.6	1.6	1.5	1.5	1.5	1.4	0.173	30	
2.6	2.5	2.4	2.4	2.3	2.2	2.1	2.1	2.0	1.9	1.9	1.8	1.8	1.7	1.7	1.7	0.200	40	
3.0	2.8	2.7	2.6	2.5	2.5	2.4	2.3	2.2	2.2	2.1	2.0	2.0	1.9	1.9	1.8	0.224	50	50 MESH
3.2	3.1	3.0	2.9	2.8	2.7	2.6	2.5	2.4	2.4	2.3	2.2	2.2	2.1	2.1	2.0	0.245	60	YELLOW
2.0	1.9	1.8	1.8	1.7	1.7	1.6	1.5	1.5	1.5	1.4	1.4	1.3	1.3	1.3	1.2	0.150	15	XR80025VS
2.4	2.3	2.2	2.1	2.0	2.0	1.9	1.9	1.8	1.7	1.7	1.7	1.6	1.6	1.5	1.5	0.180	20	XR11025VS
2.9	2.8	2.7	2.6	2.5	2.4	2.3	2.3	2.2	2.1	2.1	2.0	2.0	1.9	1.9	1.8	0.220	30	
3.3	3.2	3.1	2.9	2.8	2.8	2.7	2.6	2.5	2.4	2.4	2.3	2.2	2.2	2.1	2.1	0.250	40	
3.7	3.6	3.4	3.3	3.2	3.1	3.0	2.9	2.8	2.7	2.6	2.6	2.5	2.4	2.4	2.3	0.280	50	50 MESH
4.1	3.9	3.8	3.7	3.5	3.4	3.3	3.2	3.1	3.0	2.9	2.8	2.8	2.7	2.6	2.6	0.310	60	PURPLE
2.4	2.3	2.2	2.2	2.1	2.0	2.0	1.9	1.8	1.8	1.7	1.7	1.6	1.6	1.6	1.5	0.184	15	XR8003VS
2.8	2.7	2.6	2.5	2.4	2.3	2.3	2.2	2.1	2.1	2.0	1.9	1.9	1.8	1.8	1.8	0.212	20	XR1103VS
3.4	3.3	3.2	3.1	3.0	2.9	2.8	2.7	2.6	2.5	2.4	2.4	2.3	2.3	2.2	2.1	0.260	30	
4.0	3.8	3.7	3.5	3.4	3.3	3.2	3.1	3.0	2.9	2.8	2.8	2.7	2.6	2.5	2.5	0.300	40	
4.4	4.3	4.1	4.0	3.8	3.7	3.6	3.5	3.4	3.3	3.2	3.1	3.0	2.9	2.8	2.8	0.335	50	50 MESH
4.8	4.7	4.5	4.3	4.2	4.0	3.9	3.8	3.7	3.6	3.5	3.4	3.3	3.2	3.1	3.0	0.367	60	BLUE

**XR 80° / 110° 36" TIP SPACING**

ALL VALUES BASED ON WATER FOR OTHER LIQUIDS SEE USEFUL FORMULAS AND CONVERSIONS

mph		4.0	4.5	5.0	5.5	6.0	6.5	7.0	7.5	8.0	8.5	9.0	9.5	10.0	10.5	11.0	11.5	12.0	
XR8004VS XR1104VS	15	0.245	10.1	9.0	8.1	7.3	6.7	6.2	5.8	5.4	5.1	4.8	4.5	4.3	4.0	3.8	3.7	3.5	3.4
	20	0.283	11.7	10.4	9.3	8.5	7.8	7.2	6.7	6.2	5.8	5.5	5.2	4.9	4.7	4.4	4.2	4.1	3.9
	30	0.346	14.3	12.7	11.4	10.4	9.5	8.8	8.2	7.6	7.1	6.7	6.4	6.0	5.7	5.4	5.2	5.0	4.8
	40	0.400	16.5	14.7	13.2	12.0	11.0	10.2	9.4	8.8	8.3	7.8	7.3	6.9	6.6	6.3	6.0	5.7	5.5
50 MESH RED	50	0.447	18.4	16.4	14.8	13.4	12.3	11.4	10.5	9.8	9.2	8.7	8.2	7.8	7.4	7.0	6.7	6.4	6.1
	60	0.490	20.2	18.0	16.2	14.7	13.5	12.4	11.5	10.8	10.1	9.5	9.0	8.5	8.1	7.7	7.3	7.0	6.7
XR8005VS XR1105VS	15	0.306	12.6	11.2	10.1	9.2	8.4	7.8	7.2	6.7	6.3	5.9	5.6	5.3	5.1	4.8	4.6	4.4	4.2
	20	0.354	14.6	13.0	11.7	10.6	9.7	9.0	8.3	7.8	7.3	6.9	6.5	6.1	5.8	5.6	5.3	5.1	4.9
	30	0.433	17.9	15.9	14.3	13.0	11.9	11.0	10.2	9.5	8.9	8.4	7.9	7.5	7.1	6.8	6.5	6.2	6.0
	40	0.500	20.6	18.3	16.5	15.0	13.8	12.7	11.8	11.0	10.3	9.7	9.2	8.7	8.3	7.9	7.5	7.2	6.9
50 MESH BROWN	50	0.559	23.1	20.5	18.4	16.8	15.4	14.2	13.2	12.3	11.5	10.9	10.2	9.7	9.2	8.8	8.4	8.0	7.7
	60	0.612	25.3	22.5	20.2	18.4	16.8	15.5	14.4	13.5	12.6	11.9	11.2	10.6	10.1	9.6	9.2	8.8	8.4
XR8006VS XR1106VS	15	0.367	15.2	13.5	12.1	11.0	10.1	9.3	8.7	8.1	7.6	7.1	6.7	6.4	6.1	5.8	5.5	5.3	5.1
	20	0.424	17.5	15.6	14.0	12.7	11.7	10.8	10.0	9.3	8.8	8.2	7.8	7.4	7.0	6.7	6.4	6.1	5.8
	30	0.520	21.4	19.1	17.1	15.6	14.3	13.2	12.2	11.4	10.7	10.1	9.5	9.0	8.6	8.2	7.8	7.5	7.1
	40	0.600	24.8	22.0	19.8	18.0	16.5	15.2	14.1	13.2	12.4	11.6	11.0	10.4	9.9	9.4	9.0	8.6	8.3
50 MESH GRAY	50	0.671	27.7	24.6	22.1	20.1	18.4	17.0	15.8	14.8	13.8	13.0	12.3	11.7	11.1	10.5	10.1	9.6	9.2
	60	0.735	30.3	26.9	24.2	22.0	20.2	18.7	17.3	16.2	15.2	14.3	13.5	12.8	12.1	11.5	11.0	10.5	10.1
XR8008VS XR1108VS	15	0.490	20.2	18.0	16.2	14.7	13.5	12.4	11.5	10.8	10.1	9.5	9.0	8.5	8.1	7.7	7.3	7.0	6.7
	20	0.566	23.3	20.7	18.7	17.0	15.6	14.4	13.3	12.4	11.7	11.0	10.4	9.8	9.3	8.9	8.5	8.1	7.8
	30	0.693	28.6	25.4	22.9	20.8	19.1	17.6	16.3	15.2	14.3	13.4	12.7	12.0	11.4	10.9	10.4	9.9	9.5
	40	0.800	33.0	29.3	26.4	24.0	22.0	20.3	18.9	17.6	16.5	15.5	14.7	13.9	13.2	12.6	12.0	11.5	11.0
50 MESH WHITE	50	0.894	36.9	32.8	29.5	26.8	24.6	22.7	21.1	19.7	18.4	17.4	16.4	15.5	14.8	14.1	13.4	12.8	12.3
	60	0.980	40.4	35.9	32.3	29.4	26.9	24.9	23.1	21.6	20.2	19.0	18.0	17.0	16.2	15.4	14.7	14.1	13.5
XR8010SS XR11010SS	15	0.612	25.3	22.5	20.2	18.4	16.8	15.5	14.4	13.5	12.6	11.9	11.2	10.6	10.1	9.6	9.2	8.8	8.4
	20	0.707	29.2	25.9	23.3	21.2	19.4	17.9	16.7	15.6	14.6	13.7	13.0	12.3	11.7	11.1	10.6	10.1	9.7
	30	0.866	35.7	31.8	28.6	26.0	23.8	22.0	20.4	19.1	17.9	16.8	15.9	15.0	14.3	13.6	13.0	12.4	11.9
	40	1.000	41.3	36.7	33.0	30.0	27.5	25.4	23.6	22.0	20.6	19.4	18.3	17.4	16.5	15.7	15.0	14.3	13.8
50 MESH	50	1.118	46.1	41.0	36.9	33.5	30.7	28.4	26.4	24.6	23.1	21.7	20.5	19.4	18.4	17.6	16.8	16.0	15.4
	60	1.225	50.5	44.9	40.4	36.7	33.7	31.1	28.9	26.9	25.3	23.8	22.5	21.3	20.2	19.2	18.4	17.6	16.8
XR8015SS XR11015SS	15	0.919	37.9	33.7	30.3	27.6	25.3	23.3	21.7	20.2	18.9	17.8	16.8	16.0	15.2	14.4	13.8	13.2	12.6
	20	1.061	43.8	38.9	35.0	31.8	29.2	26.9	25.0	23.3	21.9	20.6	19.4	18.4	17.5	16.7	15.9	15.2	14.6
	30	1.299	53.6	47.6	42.9	39.0	35.7	33.0	30.6	28.6	26.8	25.2	23.8	22.6	21.4	20.4	19.5	18.6	17.9
	40	1.500	61.9	55.0	49.5	45.0	41.3	38.1	35.4	33.0	30.9	29.1	27.5	26.1	24.8	23.6	22.5	21.5	20.6
50 MESH	50	1.677	69.2	61.5	55.3	50.3	46.1	42.6	39.5	36.9	34.6	32.6	30.7	29.1	27.7	26.4	25.2	24.1	23.1
	60	1.837	75.8	67.4	60.6	55.1	50.5	46.6	43.3	40.4	37.9	35.7	33.7	31.9	30.3	28.9	27.6	26.4	25.3

**XR 80° / 110° 36" TIP SPACING**

ALL VALUES BASED ON WATER FOR OTHER LIQUIDS SEE USEFUL FORMULAS AND CONVERSIONS

12.5	13.0	13.5	14.0	14.5	15.0	15.5	16.0	16.5	17.0	17.5	18.0	18.5	19.0	19.5	20.0	mph	
3.2	3.1	3.0	2.9	2.8	2.7	2.6	2.5	2.4	2.4	2.3	2.2	2.2	2.1	2.1	2.0	0.245	15
3.7	3.6	3.5	3.3	3.2	3.1	3.0	2.9	2.8	2.7	2.7	2.6	2.5	2.5	2.4	2.3	0.283	20
4.6	4.4	4.2	4.1	3.9	3.8	3.7	3.6	3.5	3.4	3.3	3.2	3.1	3.0	2.9	2.9	0.346	30
5.3	5.1	4.9	4.7	4.6	4.4	4.3	4.1	4.0	3.9	3.8	3.7	3.6	3.5	3.4	3.3	0.400	40
5.9	5.7	5.5	5.3	5.1	4.9	4.8	4.6	4.5	4.3	4.2	4.1	4.0	3.9	3.8	3.7	0.447	50
6.5	6.2	6.0	5.8	5.6	5.4	5.2	5.1	4.9	4.8	4.6	4.5	4.4	4.3	4.1	4.0	0.490	60
4.0	3.9	3.7	3.6	3.5	3.4	3.3	3.2	3.1	3.0	2.9	2.8	2.7	2.7	2.6	2.5	0.306	15
4.7	4.5	4.3	4.2	4.0	3.9	3.8	3.6	3.5	3.4	3.3	3.2	3.2	3.1	3.0	2.9	0.354	20
5.7	5.5	5.3	5.1	4.9	4.8	4.6	4.5	4.3	4.2	4.1	4.0	3.9	3.8	3.7	3.6	0.433	30
6.6	6.3	6.1	5.9	5.7	5.5	5.3	5.2	5.0	4.9	4.7	4.6	4.5	4.3	4.2	4.1	0.500	40
7.4	7.1	6.8	6.6	6.4	6.1	6.0	5.8	5.6	5.4	5.3	5.1	5.0	4.9	4.7	4.6	0.559	50
8.1	7.8	7.5	7.2	7.0	6.7	6.5	6.3	6.1	5.9	5.8	5.6	5.5	5.3	5.2	5.1	0.612	60
4.8	4.7	4.5	4.3	4.2	4.0	3.9	3.8	3.7	3.6	3.5	3.4	3.3	3.2	3.1	3.0	0.367	15
5.6	5.4	5.2	5.0	4.8	4.7	4.5	4.4	4.2	4.1	4.0	3.9	3.8	3.7	3.6	3.5	0.424	20
6.9	6.6	6.4	6.1	5.9	5.7	5.5	5.4	5.2	5.0	4.9	4.8	4.6	4.5	4.4	4.3	0.520	30
7.9	7.6	7.3	7.1	6.8	6.6	6.4	6.2	6.0	5.8	5.7	5.5	5.4	5.2	5.1	5.0	0.600	40
8.9	8.5	8.2	7.9	7.6	7.4	7.1	6.9	6.7	6.5	6.3	6.1	6.0	5.8	5.7	5.5	0.671	50
9.7	9.3	9.0	8.7	8.4	8.1	7.8	7.6	7.3	7.1	6.9	6.7	6.6	6.4	6.2	6.1	0.735	60
6.5	6.2	6.0	5.8	5.6	5.4	5.2	5.1	4.9	4.8	4.6	4.5	4.4	4.3	4.1	4.0	0.490	15
7.5	7.2	6.9	6.7	6.4	6.2	6.0	5.8	5.7	5.5	5.3	5.2	5.0	4.9	4.8	4.7	0.566	20
9.1	8.8	8.5	8.2	7.9	7.6	7.4	7.1	6.9	6.7	6.5	6.4	6.2	6.0	5.9	5.7	0.693	30
10.6	10.2	9.8	9.4	9.1	8.8	8.5	8.3	8.0	7.8	7.5	7.3	7.1	6.9	6.8	6.6	0.800	40
11.8	11.4	10.9	10.5	10.2	9.8	9.5	9.2	8.9	8.7	8.4	8.2	8.0	7.8	7.6	7.4	0.894	50
12.9	12.4	12.0	11.5	11.1	10.8	10.4	10.1	9.8	9.5	9.2	9.0	8.7	8.5	8.3	8.1	0.980	60
8.1	7.8	7.5	7.2	7.0	6.7	6.5	6.3	6.1	5.9	5.8	5.6	5.5	5.3	5.2	5.1	0.612	15
9.3	9.0	8.6	8.3	8.0	7.8	7.5	7.3	7.1	6.9	6.7	6.5	6.3	6.1	6.0	5.8	0.707	20
11.4	11.0	10.6	10.2	9.9	9.5	9.2	8.9	8.7	8.4	8.2	7.9	7.7	7.5	7.3	7.1	0.866	30
13.2	12.7	12.2	11.8	11.4	11.0	10.6	10.3	10.0	9.7	9.4	9.2	8.9	8.7	8.5	8.3	1.000	40
14.8	14.2	13.7	13.2	12.7	12.3	11.9	11.5	11.2	10.9	10.5	10.2	10.0	9.7	9.5	9.2	1.118	50
16.2	15.5	15.0	14.4	13.9	13.5	13.0	12.6	12.2	11.9	11.5	11.2	10.9	10.6	10.4	10.1	1.225	60
12.1	11.7	11.2	10.8	10.5	10.1	9.8	9.5	9.2	8.9	8.7	8.4	8.2	8.0	7.8	7.6	0.919	15
14.0	13.5	13.0	12.5	12.1	11.7	11.3	10.9	10.6	10.3	10.0	9.7	9.5	9.2	9.0	8.8	1.061	20
17.1	16.5	15.9	15.3	14.8	14.3	13.8	13.4	13.0	12.6	12.2	11.9	11.6	11.3	11.0	10.7	1.299	30
19.8	19.0	18.3	17.7	17.1	16.5	16.0	15.5	15.0	14.6	14.1	13.8	13.4	13.0	12.7	12.4	1.500	40
22.1	21.3	20.5	19.8	19.1	18.4	17.9	17.3	16.8	16.3	15.8	15.4	15.0	14.6	14.2	13.8	1.677	50
24.2	23.3	22.5	21.7	20.9	20.2	19.6	18.9	18.4	17.8	17.3	16.8	16.4	16.0	15.5	15.2	1.837	60