



www.wyliesprayers.com

1600 SPRAYER



Reduce your spraying time by stepping up to the Wylie 1600!

Check Out These Features...

- ⇒ 1,600 gal. Tank for Large Booms and Large Acreages
- ⇒ Choose From 60', 80', 90', 100' Spray Wyng II Boom, or the 60' Row Wyng Boom
- ⇒ 100 gal. Fresh Water Tank, 15 gal. Handler™ Tank
- ⇒ Optional GPS Guidance or Foam Marker
- ⇒ Loading Stand Easily Services Side Fillwell on Tank



Diamond tread tires provide excellent flotation in wheat

Wylie's 1600 Sprayer is just what larger producers need in today's fast paced farming operations. The capacity of the 1,600 gallon tank coupled with a 60', 80', 90' or 100' Spray Wyng II boom allow the operator to spray more acres in less time than ever before.

There is much more to the Wylie 1600 than just size and capacity. The Spray Wyng II boom has proven itself as the "state of the art" boom for high speed spraying. The Spray Wyng II features an "All Directional" suspension to control movement in three dimensions. The boom can tilt 15° to clear obstacles and follow rolling terrain. The parallel linkage "Hi-Lift" raises the boom in a 5' height range, from 2' to 7'.

The 60' Row Wyng boom is designed to tilt 15° and fold each wing independently over rolling terrain and around obstacles.

Contact your Wylie representative today. Let him show you the Wylie advantage!



Wylie 1600 in transport mode; 12' OAW, 120" wheel track

SPRAYERS...that's it, that's all.



Fast Speed, More Acres...More Profit

The secret to the speed of the Spray Wyng II boom is the "All Directional" suspension which cushions the movement of the boom in all three dimensions. A nitrogen filled accumulator controls the bounce of the boom. The boom is mounted on a spherical bearing. Roll and yaw movement are controlled with coil and poly springs. Uncontrolled movement of these forces in inferior booms result in slow field speeds, metal fatigue and failure of the boom, as well as uneven chemical application. The Spray Wyng II stays in a consistent position over the crop so that you get accurate application at speeds up to 15 mph. Couple that with the large capacity 1,600 gallon tank and the 80', 90' or 100' boom and you have a spraying system that can cover your acreage when the conditions are right --- and free you to get on to other important tasks.



Control and Guidance

The Spray Wyng II boom fold/raise circuits are controlled by a conveniently located console. Fold, tilt, raise or lower the boom with a touch of a switch.

The Spray Wyng II boom can be controlled by a Raven SCS450 automatic controller or by the Raven Envizio Pro control/guidance console.



Safety and ease of operation are key to the design of the 1600. A 100 gallon fresh water tank has a valve for hand washing or can be used to flush the spraying system. The opaque tank prevents algae growth.

The 15 gallon Handler™ tank lowers to waist level for safe and convenient induction of chemicals.

The 1600 can be equipped with a foam marker or a Raven automatic control and GPS guidance system can provide guidance, record keeping, "as applied mapping", and even variable rate application.

The control panel is easy to access and simple to operate. All the filling, mixing and spraying settings are in one convenient location.



Amarillo 888-611-6175	Edinburg 800-514-9381	El Campo 800-474-2416	Garden City 800-995-4342	Lubbock 888-249-5162	Oklahoma City 888-665-5538	Waco 800-803-5845
---------------------------------	---------------------------------	---------------------------------	------------------------------------	--------------------------------	--------------------------------------	-----------------------------